

## LED Floodlight

### Features:

- Perfect solution for outdoor illumination
- Simple housing design, easy to install and replace
- PC + Aluminum body material
- Lifetime of up to 30,000 hrs
- Overall cooling design, low light attenuation
- Up to 80% energy saving
- Lower maintenance cost
- UV & IR free light
- CRI>80
- IP65
- IK08



### Applications:

- Industrial area
- Warehouse
- Park
- Facade



### General Characteristics:

| Item | Watt | Luminous Flux (lm) | CRI (Ra) | CCT (K)    | MOD (mm) | MOL (mm) | Voltage (V) | PF  | Beam Angle |
|------|------|--------------------|----------|------------|----------|----------|-------------|-----|------------|
| F50  | 50W  | 4000-4500          | 80       | 3000-6500K | W254/H43 | 240      | 120/220V    | 0.9 | 90         |
| F80  | 80W  | 8000-8300          | 80       | 3000-6500K | W395/H43 | 300      | 120/220V    | 0.9 | 90         |
| F120 | 120W | 11000-11500        | 80       | 3000-6500K | W357/H43 | 360      | 120/220V    | 0.9 | 90         |
| F140 | 140W | 16000-16500        | 80       | 3000-6500K | W357/H43 | 360      | 120/220V    | 0.9 | 90         |
| F200 | 200W | 20000              | 80       | 3000-6500K | W360/H43 | 480      | 120/220V    | 0.9 | 90         |

#### Cautions:

- Please read the contents on the box and label carefully before installation
- Check if the specification e.g. voltage, current etc meet the requirements
- Power must be cut off before installation, replacement and cleaning
- Don't touch the bulb/luminaire while it is on or immediately after turning it off. Please wait 15 min. for bulb to cool down.
- Black color housing
- Operation temp. : -40°C – 50°C

#### Remarks:

- Power consumption tolerance: +/- 10%.
- Luminous flux & cd tolerance: +/-10%

\*Photos, descriptions and details of the product are subject to change without previous notice.

