



Multifak® Moly EP (old name Molytex® EP)

Extreme Pressure Automotive Grease

Product Data Sheet

Customer benefits

Protects metal surfaces

Effective EP additive and molybdenum disulfide solid film lubricant protect against component wear under high load conditions and/or shock loading. Rust and corrosion inhibitors protect metal surfaces in wet operating conditions. Even if insufficient grease is used, some molybdenum disulfide tends to stay in place and protect metal surfaces.

Enhances service life

Excellent oxidation resistance ensures enhanced grease service life.

Ease of application

NLGI 2 grade provide suitable flow properties for grease pump application systems.

Reduces complexity

Multipurpose capability allows use in a wide range of heavy-duty automotive and industrial applications, reducing the number of different greases required and eliminating product misapplication.

Applications

Can include:

- Automotive
- Construction
- Earthmoving, quarrying and mining
- Agricultural equipment
- Chassis grease point lubrication
- Pins, bushings and other sliding surface or pivot points
- All types of anti-friction bearings
- Ball joints
- Universal joints (U-joints)
- High and shock load applications

Not recommended for constant-velocity joints in front wheel drive vehicles.

Usable temperature range in continuous service is -30 to 130°C.

Maximum temperature for short term exposure is 175°C.

Product features:

- **Multifak® Moly EP** is a dark gray, multipurpose EP grease primarily designed for construction, mining and agricultural equipment where an extra measure of protection in shock loading conditions is required.

- **Multifak® Moly EP** contains a highly refined ISO VG 220 mineral base oil, lithium soap thickener, EP additives, rust and oxidation inhibitors, plus molybdenum disulfide solid film lubricant.

Typical key properties

MULTIFAK® MOLY EP	
NLGI Grade	2
Product Code	510843
Dropping Point, °C	195
Molybdenum Disulfide, m %	3
Oil Viscosity,	
— mm ² /s @ 40°C	220
— mm ² /s @ 100°C	18.2
Penetration, Worked @ 25 °C	280
Thickener (Lithium), m %	7.5
Timken OK Load, kg	20

1605

Performance standard

- Volvo Corporate standard STD 1277.65, lubricating grease 97765

Service considerations

The inclusion of molybdenum disulfide provides an extra measure of protection under shock loading which is very common in construction, off-highway transport and agricultural usage. During heavy shock loading, the lubricant film between metal surfaces can be temporarily ruptured or squeezed out. When using Multifak Moly EP, some molybdenum disulfide stays in place as a solid film lubricant to protect metal surfaces, even under extreme shock loading conditions, preventing metal-to-metal contact which could cause component damage. The presence of molybdenum disulfide is also valuable in dirty environments, or when proper re-greasing intervals cannot be followed.

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.chevronlubricants.com.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific