

# CitoPress-5



**The fastest way to mounting and increased productive capacity**



## **CitoPress-5 is offering ultra-short mounting times and maximum user-friendliness**

### **Features**

- Low mass mounting units for fast heating
- Individually controlled parameters: temperature, force/pressure, heating time, cooling time
- Automatic detection of cylinder dimension
- Display and touch pad controls
- Low build-height for easy visual control
- Triple-threaded, no-jam top closure
- Simple access for easy cleaning
- Top closure elevator for easy positioning
- Powerful heating unit (1000 W)
- Hydraulic system with high accuracy pressure control
- 3 preset cooling levels (Hi/Med/Lo)



## CitoPress-5 increases your capacity

CitoPress-5 is a powerful mounting press, giving you high speed and maximum user-friendliness. The result is faster turn-around and increased productive capacity. CitoPress-5 is provided with a hydraulic system, where the pressure is controlled with very high accuracy, securing fragile specimens. CitoPress-5 is equipped with a single cylinder and all settings and dosing are manual, which makes it ideal for customers doing few samples.

## User-friendly software

### Automatic detection of cylinder dimension

When changing the cylinder dimension, the press automatically detects the new size, and adjusts the method parameters accordingly. In this fashion, errors from an incorrect cylinder setting are eliminated. Pressure as well as heating time and cooling time can be controlled individually, ensuring full flexibility in mounting.


### Acoustic alarm

CitoPress-5 comes with an acoustic alarm, notifying the user when the mount is ready.

## User-friendly design

### Display and touch pad controls

CitoPress-5 features a LCD display, which graphically shows parameter settings and mounting progress. Changing parameters is fast by using the touch pad controls.



The display and touch pad controls facilitate fast selection of parameters


### Low build height

Low build height means easy visual inspection of the mounting cylinder. This is relevant e.g. if tall, thin samples are to be mounted, and the operator wants to check if the sample still stands after adding resin. Another typical situation would be if multiple samples are to be included in the same mount.

### Easy cleaning

The door to the mounting unit tower swings open for easy access to the mounting unit.

CitoPress-5 mounting times for different resins, compared to competing presses (competing presses = 100%)



CitoPress-5 can reduce mounting times to nearly one third, compared to competing presses. (Applies for a 30 mm dia. cylinder. When using a 40 mm dia. cylinder CitoPress-5 can reduce mounting times by half)



Low mass mounting unit and top closure



ClaroFast is a transparent hot mounting resin, offering you transparent mounts with a clear view to all sample details

### Compact mounting units

CitoPress-5 is equipped with compact, low-mass mounting units significantly reducing heating time. Available cylinder diameters: 25, 30, 40, 50 mm, 1¼" and 1½".

### Simple top closure

The press comes with a top-closure elevator. Any handling problems of the top closure as seen on other presses are solved by the top closure design. The CitoPress-5 top closure is with triple-thread. Thus, the entire process of mounting the top closure follows with a minimum of effort.

## Saves money and resource


The benefit of shorter heating times is reduced energy consumption. Compared to competing presses, less than half the power is required to heat the mounting unit.

### Three preset cooling levels

CitoPress-5 comes with three preset cooling levels (Hi/Med/Lo). The main advantage is water saving, meaning that the MEDIUM mode can be used in most cases, and water usage reduced significantly. Thermoplastic resins require far longer cooling times than thermosetting. With CitoPress-5, the cooling level can be set to match the resin. E.g., instead of reducing the flow at the water tap, the level can be reduced by selecting the LOW mode.



Top closure elevator for easy handling



## HandyDoser

HandyDoser is a manual doser which makes resin dosing simple and convenient. No spoons or funnels are required any more, and dosing the right volume becomes really easy. Since there is less mess, cleaning of the hot mounting press is reduced to a minimum.

The dosing unit doses ca 5 ml at a time, and holds enough resin for ca 30 mounts, or ca 550 ml.



## Specifications

Cat. no

### CitoPress-5

Automatic, electro-hydraulic hot mounting press with one cylinder.  
Mounting units are ordered separately.

05776127

### Mounting units

Consisting of heating/cooling unit, lower ram and top closure with upper ram.

Upper ram with waistline.

Cylinder diameter 1½"

05788127

Cylinder diameter 1¼"

05788227

Cylinder diameter 25 mm

05788327

Cylinder diameter 30 mm

05788427

Cylinder diameter 40 mm

05788527

Cylinder diameter 50 mm

05788627

### Chamfered ram

Lower, chamfered ram. To prevent sharp edge on mounted sample.

Cylinder diameter 25 mm

05786900

Cylinder diameter 30 mm

05786901

Cylinder diameter 1¼"

05786902

Cylinder diameter 1½"

05786903

Cylinder diameter 40 mm

05786904

Cylinder diameter 50 mm

05786905

### Accessories

HandyDoser

05736902

*HandyDoser*

*Easy access means quick change of mounting units and easy cleaning*

**Struers ApS**  
Pederstrupvej 84  
DK-2750 Ballerup, Denmark  
Phone +45 44 600 800  
Fax +45 44 600 801  
struers@struers.dk  
www.struers.com

## Technical data

SUBJECT	SPECIFICATION
<b>Mounting unit</b>	
Mounting dia.	25, 30, 40, 50 mm, 1¼", 1½"
<b>Mounting press</b>	
<b>Mounting parameters</b>	
Pressure	(50 mm 50-250 bar / 725-3626 psi) in steps of 25 bar / 363 psi*
Heating time	1-15 min in steps of 0.5 min
Heating temperature	120-150-180°C / 248-302-356°F
Cooling time	1-15 min in steps of 0.5 min
Cooling rate	High: Full flow Medium: 20% of full flow Low: 3% of full flow
<b>Software and electronics</b>	
Controls	Touch pads
LCD display with white	
LED backlight	160x240 dots
<b>Noise levels</b>	
Idle	0 dB (A)
Max.	63 dB(A)
<b>Working environment</b>	
Temperature, operational	5-40°C / 41-104°F
Humidity, non-condensing	0-95% RH
<b>Supply</b>	
Voltage / frequency	100-120V / 50-60Hz, 200-240V / 50-60Hz Auto detection and auto switch over
Power inlet (IEC320-C13)	1-phase (N+L+PE) or 2-phase (L1+L2+PE) <i>The electrical installation must comply with "Installation Category II"</i>
Power, idle	8W
Power, max.	1300W@100-120V / 1300W@200-240V
Current, max.	13A@100-120V / 5.6A@200-240V
Water pressure (tap water)	1-10 bar / 14.5-145 psi
Water inlet	10 mm / ¾"
Water outlet	ø13 mm
<b>Dimensions and weight</b>	
Width	480 mm / 19"
Depth	560 mm / 22"
Height	440 mm / 17½"
Weight	34 kg / 75 lbs

\* With a 50 mm cylinder the pressure can be set to 50 - 250 bar / 725 - 3626 psi.

Struers' equipment is in conformity with the provisions of the applicable International Directives and their appurtenant Standards. (Please contact your local supplier for details)

Struers' products are subject to constant product development. Therefore, we reserve the right to introduce changes in our products without notice

**AUSTRALIA & NEW ZEALAND**  
**Struers Australia**  
27 Mayneview Street  
Milton QLD 4064  
Australia  
Phone +61 7 3512 9600  
Fax +61 7 3369 8200  
info.au@struers.dk

**BELGIQUE (Wallonie)**  
**Struers S.A.S.**  
370, rue du Marché Rollay  
F- 94507 Champigny  
sur Marne Cedex  
Téléphone +33 1 5509 1430  
Télécopie +33 1 5509 1449  
struers@struers.fr

**BELGIUM (Flanders)**  
**Struers GmbH Nederland**  
Zomerdijk 34 A  
3143 CT Maassluis  
Telefoon +31 (10) 599 7209  
Fax +31 (10) 5997201  
netherlands@struers.de

**CANADA**  
**Struers Ltd.**  
7275 West Credit Avenue  
Mississauga, Ontario L5N 5M9  
Phone +1 905-814-8855  
Fax +1 905-814-1440  
info@struers.com

**CHINA**  
**Struers Ltd.**  
No. 1696 Zhang Heng Road  
Zhang Jiang Hi-Tech Park  
Shanghai 201203, P.R. China  
Phone +86 (21) 6035 3900  
Fax +86 (21) 6035 3999  
struers@struers.cn

**CZECH REPUBLIC & SLOVAKIA**  
**Struers GmbH Organizační složka**  
vědeckotechnický park  
Přílepská 1920,  
CZ-252 63 Roztoky u Prahy  
Phone +420 233 312 625  
Fax +420 233 312 640  
czechrepublic@struers.de  
slovakia@struers.de

**DEUTSCHLAND**  
**Struers GmbH**  
Carl-Friedrich-Benz-Straße 5  
D-47877 Willich  
Telefon +49 (0) 2154 486-0  
Fax +49 (0) 2154 486-222  
verkauf@struers.de

**FRANCE**  
**Struers S.A.S.**  
370, rue du Marché Rollay  
F-94507 Champigny  
sur Marne Cedex  
Téléphone +33 1 5509 1430  
Télécopie +33 1 5509 1449  
struers@struers.fr

**HUNGARY**  
**Struers GmbH**  
Magyarországi Fióktelep  
Tatai ut 53  
2821 Gyermely  
Phone +36 (34) 880546  
Fax +36 (34) 880547  
hungary@struers.de

**IRELAND**  
**Struers Ltd.**  
Unit 11 Evolution@ AMP  
Whittle Way, Catcliffe  
Rotherham S60 5BL  
Tel. +44 0845 604 6664  
Fax +44 0845 604 6651  
info@struers.co.uk

**ITALY**  
**Struers Italia**  
Via Monte Grappa 80/4  
20020 Arese (MI)  
Tel. +39-02/38236281  
Fax +39-02/38236274  
struers.it@struers.it

**JAPAN**  
**Marumoto Struers K.K.**  
Takara 3rd Building  
18-6, Higashi Ueno 1-chome  
Taito-ku, Tokyo 110-0015  
Phone +81 3 5688 2914  
Fax +81 3 5688 2927  
struers@struers.co.jp

**NETHERLANDS**  
**Struers GmbH Nederland**  
Zomerdijk 34 A  
3143 CT Maassluis  
Telefoon +31 (10) 599 7209  
Fax +31 (10) 5997201  
netherlands@struers.de

**NORWAY**  
**Struers ApS, Norge**  
Sjaskogenveien 44C  
1407 Vinterbro  
Telefon +47 970 94 285  
info@struers.no

**ÖSTERREICH**  
**Struers GmbH**  
Zweigniederlassung Österreich  
Betriebsgebiet Puch Nord 8  
5412 Puch  
Telefon +43 6245 70567  
Fax +43 6245 70567-78  
austria@struers.de

**POLAND**  
**Struers Sp. z o.o.**  
Oddział w Polsce  
ul. Jasnogórska 44  
31-358 Kraków  
Phone +48 12 661 20 60  
Fax +48 12 626 01 46  
poland@struers.de

**ROMANIA**  
**Struers GmbH, Sucursala Bucuresti**  
Str. Preciziei nr. 6R  
062203 sector 6, Bucuresti  
Phone +40 (31) 101 9548  
Fax +40 (31) 101 9549  
romania@struers.de

**SCHWEIZ**  
**Struers GmbH**  
Zweigniederlassung Schweiz  
Weissenbrunnenstraße 41  
CH-8903 Birmsdorf  
Telefon +41 44 777 63 07  
Fax +41 44 777 63 09  
switzerland@struers.de

**SINGAPORE**  
**Struers Singapore**  
627A Aljunied Road,  
#07-08 BizTech Centre  
Singapore 389842  
Phone +65 6299 2268  
Fax +65 6299 2661  
struers.sg@struers.dk

**SPAIN**  
**Struers España**  
Camino Cerro de los Gamos 1  
Building 1 - Pozuelo de Alarcón  
CP 28224 Madrid  
Teléfono +34 917 901 204  
Fax +34 917 901 112  
struers.es@struers.es

**SUOMI**  
**Struers ApS, Suomi**  
Hietalahdenranta 13  
00180 Helsinki  
Puhelin +358 (0)207 919 430  
Faksi +358 (0)207 919 431  
finland@struers.fi

**SWEDEN**  
**Struers Sverige**  
Box 20038  
161 02 Bromma  
Telefon +46 (0)8 447 53 90  
Telefax +46 (0)8 447 53 99  
info@struers.se

**UNITED KINGDOM**  
**Struers Ltd.**  
Unit 11 Evolution @ AMP  
Whittle Way, Catcliffe  
Rotherham S60 5BL  
Tel. +44 0845 604 6664  
Fax +44 0845 604 6651  
info@struers.co.uk

**USA**  
**Struers Inc.**  
24766 Detroit Road  
Westlake, OH 44145-1598  
Phone +1 440 871 0071  
Fax +1 440 871 8188  
info@struers.com