



# Safety Data Sheet

Issue Date: 10-Jun-2016

Revision Date: 01-2017

Version 2

## 1. IDENTIFICATION

### Product Identifier

**Product Name** ECB, ECB75, ECB Green, Strataflex, SAM 3, Super SAM 125 and 6" Seam Tape

### Other means of identification

**SDS #** NACP-005

**Product Code** 010011200, 010010548, 010012400, 010010550, 010013600, 010013675, 010015333, 020020150, 020020153, 020020190, 020020160, 020020151 and 020020152

### Recommended use of the chemical and restrictions on use

**Recommended Use** Self-adhering membrane used for waterproofing barrier/sealing systems.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

National Applied Construction Products, Inc.  
3200 Main St.  
Akron, OH 44319

### Emergency Telephone Number

**Company Phone Number** 1-800-633-4622  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

**Appearance** Black pliable solid, rubber

**Physical state** Solid

**Odor** Slight petroleum

### Classification

As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, the products listed below are considered articles and do not require an SDS. In addition, articles are not included in the scope of the Globally Harmonization System (GHS). As such, the GHS labeling elements are not included on this SDS. All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk. Although these products are not subject to the OSHA Standard or GHS labeling elements, National Applied Construction Products, Inc. would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and be made available for employees and other users of this product. In addition, the recommendations for handling and use of these products should be included in worker training programs. PLEASE SEE SECTION 4 FOR ADDITIONAL FIRST AID INFORMATION.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Petroleum Asphalt	8052-42-4	60-70
Crystalline silica	14808-60-7	10-25
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	<5

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST AID MEASURES

#### First Aid Measures

<b>General Advice</b>	If exposed or concerned: Get medical advice/attention. Under extreme and non-normal circumstances such as extensive cutting, grinding and pulverizing, there is some potential exposure to respirable crystalline silica (quartz). Prolonged and frequent exposure to such conditions could in some instances cause silicosis, a fibrosis of the lungs.
<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	Call a poison center or doctor/physician if you feel unwell. Rinse mouth.

#### Most important symptoms and effects

<b>Symptoms</b>	Some individuals find this product may cause skin irritation or redness. It may aggravate pre-existing skin conditions. Ingestion can cause irritation, nausea, or stomach distress.
-----------------	--

#### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media** Not determined.

#### Specific Hazards Arising from the Chemical

Product is not flammable.

**Hazardous Combustion Products** Carbon monoxide. Sulfur oxides. Various hydrocarbons.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Use personal protective equipment as required.

**Environmental precautions**

**Environmental precautions** See Section 12 for additional Ecological Information. Avoid release to the environment. See Section 13: DISPOSAL CONSIDERATIONS.

**Methods and material for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Clean-Up** Clean up in accordance with all applicable regulations. Sweep up, pick up and put into an approved waste container for disposal.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on Safe Handling** Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep container tightly closed and store in a cool, dry and well-ventilated place. Store in secured area.

**Incompatible Materials** None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Exposures at these levels are not expected to occur under normal use. These exposure guidelines are provided as a general method for safe workplace monitoring.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Asphalt 8052-42-4	TWA: 0.5 mg/m <sup>3</sup> benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m <sup>3</sup> fume 15 min
Crystalline silica 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	(vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

**Other Information** \*Because of product form, exposure to dust or fumes is not expected to occur in normal use.

**Appropriate engineering controls**

**Engineering Controls** Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Use approved eye protection to avoid eye contact. Refer to 29 CFR 1910.133 for eye and face protection regulations.

**Skin and Body Protection** Wear normal working gloves of 100% cotton or leather. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

**Respiratory Protection**

Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Refer to 29 CFR 1910.134 for respiratory protection requirements.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

<b>Physical state</b>	Solid	<b>Odor</b>	Slight petroleum
<b>Appearance</b>	Black pliable solid, rubber	<b>Odor Threshold</b>	Not determined
<b>Color</b>	Black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	Not applicable due to product form	
<b>Melting Point/Freezing Point</b>	Not applicable due to product form	
<b>Boiling Point/Boiling Range</b>	Not applicable due to product form	
<b>Flash Point</b>	Not applicable due to product form	
<b>Evaporation Rate</b>	Not applicable due to product form	
<b>Flammability (Solid, Gas)</b>	Not applicable due to product form	
<b>Flammability Limits in Air</b>		
<b>Upper Flammability Limits</b>	Not applicable due to product form	
<b>Lower Flammability Limit</b>	Not applicable due to product form	
<b>Vapor Pressure</b>	Not applicable due to product form	
<b>Vapor Density</b>	Not applicable due to product form	
<b>Relative Density</b>	Not applicable due to product form	
<b>Water Solubility</b>	Insoluble in water	
<b>Solubility in other solvents</b>	Not applicable due to product form	
<b>Partition Coefficient</b>	Not applicable due to product form	
<b>Auto-ignition Temperature</b>	Not applicable due to product form	
<b>Decomposition Temperature</b>	Not applicable due to product form	
<b>Kinematic Viscosity</b>	Not applicable due to product form	
<b>Dynamic Viscosity</b>	Not applicable due to product form	
<b>Explosive Properties</b>	Not an explosive	
<b>Oxidizing Properties</b>	Not applicable due to product form	

Other Information

**VOC Content** 0.0 g/l

**10. STABILITY AND REACTIVITY**

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures over 400°F may cause resin degradation. Keep out of reach of children.

Incompatible Materials

None known based on information supplied.

**Hazardous Decomposition Products**

Carbon monoxide. Various hydrocarbons. Sulfur oxides.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

<b>Eye Contact</b>	Avoid contact with eyes.
<b>Skin Contact</b>	Some individuals find this product may cause skin irritation or redness. It may aggravate pre-existing skin conditions.
<b>Inhalation</b>	Do not inhale.
<b>Ingestion</b>	Ingestion can cause irritation, nausea, or stomach distress.

**Component Information**

\*Because of product form, exposure to dust or fumes is not expected to occur in normal use

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Petroleum Asphalt 8052-42-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-
Crystalline silica 14808-60-7	= 500 mg/kg ( Rat )	-	-

**Information on physical, chemical and toxicological effects**

**Symptoms** Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Carcinogenicity** Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder). Because of product form, exposure to dust or fumes is not expected to occur in normal use.

Chemical Name	ACGIH	IARC	NTP	OSHA
Crystalline silica 14808-60-7	A2	Group 1	Known	X

**Legend***ACGIH (American Conference of Governmental Industrial Hygienists)**A2 - Suspected Human Carcinogen**IARC (International Agency for Research on Cancer)**Group 1 - Carcinogenic to Humans**NTP (National Toxicology Program)**Known - Known Carcinogen**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**X - Present***Numerical measures of toxicity**

Not applicable due to form of the product.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

The product is not classified as environmentally hazardous.

**13. DISPOSAL CONSIDERATIONS****Waste Treatment Methods**

**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations. This product is not regulated as a hazardous waste by the U.S. EPA under the Resource Conservation and Recovery Act (RCRA).

**14. TRANSPORT INFORMATION**

**DOT** Not regulated

**IATA** Not regulated

**IMDG** Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Petroleum Asphalt	X	X	X		X	Present	X	X
Crystalline silica	X	X	X	Present	X	Present	X	X
1,3-butadiene-styrene block polymer	X	X		Present	X	Present	X	X
Petroleum distillates, solvent dewaxed heavy paraffinic	X	X	X		X	Present	X	X

**Legend:**

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

**US Federal Regulations**

**SARA 313**

Not applicable

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Crystalline silica - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Petroleum Asphalt 8052-42-4	X	X	X
Crystalline silica 14808-60-7	X	X	X

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	1	1	0	Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical hazards</b>	<b>Personal Protection</b>
	Not determined	Not determined	Not determined	Not determined

Issue Date: 10-Jun-2016  
 Revision Date: 06-Jul-2016  
 Revision Note: Additional information

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**