

SPECIFICATIONS

Mechanical

Size: HxWxD

1.72 in. (4.37 cm) H

17 in. (43.18 cm) W

16- or 32-port models: 13.38 in. (34 cm) D

4- or 8-port models: 9.2 in. (23.4 cm) D

Weight:

4- and 8-port single power: 6.3 lbs. (2.86 Kg)

8-port dual power: 6.8 lbs. (3.08 Kg)

16- and 32-port single power: 8.1 lbs. (3.67 Kg)

16- and 32-port dual power: 8.6 lbs. (3.9 Kg)

Ports/Connections

Network: Number: 2

Type: 10/100/1000 Ethernet

Power Control Ports: Number: 2

Type: RS232 serial

Connector: 8-pin modular

Device Ports: Number: 4, 8, 16 or 32

Connector: 8-pin modular

Local Console: Number: 1

Connector: USB and VGA

Supported Target Video: VGA, DVI-I,

Display Port and HDMI

Power Supply

Number: Single or dual power supplies

Type: Internal

AC input range: 100-240V

Video Resolution

Maximum local video resolution 1920x1080;

maximum remote resolution 1440x900

Standards

Approved Agency: UL, FCC, cUL, ICES-003,
CE, VCCI, KCC, C-Tick, GOST.

* MPU108 is EAC Approved

Warranty

Two Years

