
SALES ORGANIZER







Lubricants are vital for sustaining the life of engines and vehicles, and supporting our transport, industrial activities and daily lives. The products must be selected with great care, if they are to enhance the performance and prolong the life of the vehicle.

We believe the market will continue to evolve towards top-tier products. Emissions, durability and fuel economy are driving demand for higher value engine oils with lower viscosity grades, formulated with superior quality base oils and new, innovative additive chemistry.

As oil changes are carried out on cars equipped with the latest engine technology and modern after-treatment systems, it will be essential to ensure that the right engine oil is selected, in order to protect the engine and maintain the emissions compliance of the vehicle.

Answering customer needs

Based on the latest developments in technology and regulations, we have created advanced lubricant solutions and a segmented range that responds exactly to the market requirements of today, and of the future. Our customers are assured to find specifically tailored products for their application, meeting all the specifications of the Original Equipment Manufacturer.

As a leading lubricants manufacturer, we are committed to addressing the environmental challenges of the future, and to play our role in the drive for greener, cleaner engineering, industry and transportation.

For people who demand the very best for their vehicles, Wolf brings pioneering, competitively priced lubricants which bring engines to life and give them the vital energy to optimize their performance and prolong their endurance.



CONTENT

PASSENGER CAR MOTOR OILS		11
OFFICIA	LTECH	11
65621	WOLF OFFICIALTECH OW20 LL FE	11
65617	WOLF OFFICIALTECH OW20 MS-V	11
65619	WOLF OFFICIALTECH OW30 MS-BFE	11
65615	WOLF OFFICIALTECH 0W30 MS-BHDI	11
65618	WOLF OFFICIALTECH 0W30 MS-FFE	12
65612	WOLF OFFICIALTECH 5W20 MS-FE	12
65605	WOLF OFFICIALTECH 5W30 C1	12
65610	WOLF OFFICIALTECH 5W30 C2	12
65607	WOLF OFFICIAL TECH 5W30 C3	13
65608	WOLF OFFICIALTECH 5W30 C4	13
65604 65609	WOLF OFFICIALTECH 5W30 LL III WOLF OFFICIALTECH 5W30 MS-F	13 13
00009	WOLF OFFICIALIECH SWSU WIS-F	15
ECOTEC	Н	14
16104	WOLF ECOTECH OW20 FE	14
14105	WOLF ECOTECH 0W30 FE	14
16105	WOLF ECOTECH 0W30 C3 FE	14
16106	WOLF ECOTECH 0W40 FE	14
VITALTE	СН	15
22105	WOLF VITALTECH OW30 V	15
14115	WOLF VITALTECH 5W30	15
16115	WOLF VITALTECH 5W30 ASIA/US	15
16125	WOLF VITALTECH 10W30 ASIA/US	15
17125	WOLF VITALTECH 10W30	16
21116	WOLF VITALTECH 5W40 PI C3	16
16116	WOLF VITALTECH 5W40	16
26116	WOLF VITALTECH 5W40 B4 DIESEL	16
22116	WOLF VITALTECH 5W40 GAS	17
23117	WOLF VITALTECH 5W50	17
16128	WOLF VITALTECH 10W60 M	17
24118	WOLF VITALTECH 10W60	17
EXTEND	TECH	18
28116	WOLF EXTENDTECH 5W40 HM	18
15127	WOLE EXTENDIFCH 10W/10 HM	18



GUARD	TECH	19
16127 23127 23126 14136 26136 14138 16147 14147 1336 1347 184 185 4704	WOLF GUARDTECH 10W40 SN WOLF GUARDTECH 10W40 B4 WOLF GUARDTECH 10W40 B4 DIESEL WOLF GUARDTECH 15W40 SL/CF WOLF GUARDTECH 15W40 B4 DIESEL WOLF GUARDTECH 15W50 SL/CF WOLF GUARDTECH 20W50 SN/CF WOLF GUARDTECH 20W50 SL/CF WOLF GUARDTECH 15W40 SF/CD WOLF GUARDTECH 20W50 SF/CD WOLF GUARDTECH SAE 40 SF/CD WOLF GUARDTECH SAE 50 SF/CD WOLF GUARDTECH SAE 50 WOLF GUARDTECH SAE 50	19
HEAVY	DUTY MOTOR OILS	23
OFFICI <i>E</i>	ALTECH	23
65613 15726 15725 65603 1727 1627 15736	WOLF OFFICIALTECH 5W30 UHPD WOLF OFFICIALTECH 10W40 UHPD WOLF OFFICIALTECH 10W30 MS WOLF OFFICIALTECH 10W40 ULTRA N WOLF OFFICIALTECH 10W40 S3 WOLF OFFICIALTECH 10W40 S2 WOLF OFFICIALTECH 15W40 MS	23 23 23 23 24 24 24
ECOTEC	CH CH	25
1215	WOLF ECOTECH 5W30 ULTRA	25
VITALTE	ECH	26
1227 26626 14626 26636 14636	WOLF VITALTECH 10W40 ULTRA WOLF VITALTECH 10W40 EXTRA WOLF VITALTECH 10W40 WOLF VITALTECH 15W40 EXTRA WOLF VITALTECH 15W40	26 26 26 26 27
EXTENI	DTECH	28
13536	WOLF EXTENDTECH 15W40	28



GUARDTECH		
1236	WOLF GUARDTECH 15W40 SHPD	29
1247	WOLF GUARDTECH 20W50 SHPD	29
13236	WOLF GUARDTECH 15W40 PLUS CF-4	29
11236	WOLF GUARDTECH 15W40 CF-4	29
11247	WOLF GUARDTECH 20W50 CF-4	30
21204	WOLF GUARDTECH SAE 40 CF-4/SG	30
21205	WOLF GUARDTECH SAE 50 CF-4/SG	30
TRANSI	MISSION FLUIDS	31
OFFICIA	ILTECH	31
2306	WOLF OFFICIALTECH 75W90 G 50	31
2307	WOLF OFFICIALTECH 75W140 LS GL 5	31
23310	WOLF OFFICIALTECH 85W90 M GL 5	31
2202	WOLF OFFICIALTECH 75W80 ZF	31
2212	WOLF OFFICIALTECH SAE 80W ZF GL 4	32
3012	WOLF OFFICIALTECH ATF LIFE PROTECT 6	32
3016	WOLF OFFICIALTECH ATF LIFE PROTECT 8	32
3008	WOLF OFFICIALTECH ATF D VI	32
3011	WOLF OFFICIALTECH ATF MB	33
3013	WOLF OFFICIALTECH ATF MB FE	33
3015	WOLF OFFICIALTECH MULTI VEHICLE ATF HD-LD	33
ECOTEC	н	34
2314	WOLF ECOTECH 75W FE	34
3014	WOLF ECOTECH MULTI VEHICLE ATF FE	34
3020	WOLF ECOTECH CVT FLUID	34
5080	WOLF ECOTECH DSG FLUID	34
VITALTE	CCH	35
2305	WOLF VITALTECH 75W90 GL 5	35
2211	WOLF VITALTECH 75W80 MULTI VEHICLE	35
2312	WOLF VITALTECH 80W90 GL 5	35
3010	WOLF VITALTECH MULTI VEHICLE ATF	35
3006	WOLF VITALTECH ATF DIII	36



DTECH	37
WOLF EXTENDTECH 75W90 LS GL 5 WOLF EXTENDTECH 80W90 LS GL 5 WOLF EXTENDTECH 85W140 LS GL 5 WOLF EXTENDTECH 75W80 GL 5 WOLF EXTENDTECH 75W90 GL 5 WOLF EXTENDTECH 80W90 GL 5 WOLF EXTENDTECH 80W140 GL 5 WOLF EXTENDTECH 85W140 GL 5 WOLF EXTENDTECH ATF DII	37 37 37 37 38 38 38 38
TECH	40
WOLF GUARDTECH 80W GL 4 WOLF GUARDTECH 80W90 GL 4 WOLF GUARDTECH 85W90 GL 4 WOLF GUARDTECH 80W90 GL 1, GL 3 WOLF GUARDTECH SAE 140 GL 1, GL 3 WOLF GUARDTECH ATF F/G WOLF GUARDTECH ATF D	40 40 40 40 41 41
STEERING/LEVELING FLUIDS	42
WOLF BRAKE FLUID DOT 5.1 WOLF BRAKE FLUID DOT 3.1 WOLF BRAKE FLUID DOT 3&4 WOLF BRAKE FLUID WOLF MINERAL FLUID LHM WOLF CENTRAL HYDRAULIC FLUID WOLF LDS FLUID	42 42 42 43 43 43
R FLUIDS	44
WOLF ANTI-FREEZE LONGLIFE G13 WOLF COOLANT -36°C LONGLIFE G13 WOLF ANTI-FREEZE LONGLIFE G12+ WOLF COOLANT-36°C LONGLIFE G12+	44 44 44
	WOLF EXTENDTECH 80W90 LS GL 5 WOLF EXTENDTECH 85W140 LS GL 5 WOLF EXTENDTECH 75W80 GL 5 WOLF EXTENDTECH 75W90 GL 5 WOLF EXTENDTECH 80W90 GL 5 WOLF EXTENDTECH 80W140 GL 5 WOLF EXTENDTECH 85W140 GL 5 WOLF EXTENDTECH ATF DII TECH WOLF GUARDTECH 80W GL 4 WOLF GUARDTECH 80W90 GL 4 WOLF GUARDTECH 80W90 GL 4 WOLF GUARDTECH 80W90 GL 1, GL 3 WOLF GUARDTECH ATF F/G WOLF GUARDTECH ATF DI VSTEERING/LEVELING FLUIDS WOLF BRAKE FLUID DOT 5.1 WOLF BRAKE FLUID DOT 5.1 WOLF BRAKE FLUID DOT 3.84 WOLF BRAKE FLUID LHM WOLF CENTRAL HYDRAULIC FLUID WOLF LDS FLUID R FLUIDS WOLF ANTI-FREEZE LONGLIFE G13 WOLF COOLANT -36°C LONGLIFE G13 WOLF ANTI-FREEZE LONGLIFE G13 WOLF ANTI-FREEZE LONGLIFE G12+



MAINT	ENANCE	47
55571	WOLF MOTO WASH	47
70310	WOLF GASOLINE TREATMENT	47
70301	WOLF LEAD SUBSTITUTE	47
70311	WOLF DIESEL TREATMENT	47
70312	WOLF DIESEL PARTICULATE FILTER CLEANER	48
70304	WOLF LPG TREATMENT	48
70313	WOLF ENGINE FLUSH	48
70314	WOLF OIL LEAK STOP	48
70315	WOLF RADIATOR CLEANER	49
70316	WOLF RADIATOR SEALER & CONDITIONER	49
5002	WOLF COLDCLEANER	49
MOTOR	CYCLE	50
29183	WOLF RACING 4T 5W50 ESTER	50
29182	WOLF RACING 41 5W50 ESTER WOLF RACING 4T 15W50 ESTER	50
29447	WOLF RACING 4T 15W50 ESTER	50
29180	WOLF CHRONO 4T 10W30	50
29185	WOLF CHRONO 4T 10W40	51
29184	WOLF CHRONO 4T 10W50	51
29189	WOLF CHRONO 4T 10W60	51
29186	WOLF CHRONO 4T 15W50	51
29147	WOLF V TWIN 4T 20W50	52
29187	WOLF PRO SCOOTER 4T 5W40	52
29188	WOLF FUN 4T 15W40	52
29179	WOLF FUN 4T 20W40	52
29193	WOLF RACING 2T	53
29195	WOLF CHRONO 2T	53
29198	WOLF SCOOTER 2T	53
1918	WOLF FUN 2T	53
29181	WOLF SNOW SCOOTER 4T 0W40 ESTER	54
1916	WOLF SNOW SCOOTER 2T TC-W3 EXTRA	54
1917	WOLF SNOW SCOOTER 2T TC-W3	54
29209	WOLF MOTOGEAR 75W90 GL 5	54
29308	WOLF MOTOGEAR 80W90 GL 5	55
2001	WOLF TRANSLUBE 10W30 80W	55
4655	WOLF FORK OIL 5W	55
4656	WOLF FORK OIL 10W	55
4657	WOLF FORK OIL 15W	56
4658	WOLF FORK OIL 20W	56
55504	WOLF CHAIN LUBE	56
55524	WOLF BRAKE CLEANER	56
55544	WOLF SILICONE CLEAN	57
55564	WOLF MULTISPRAY	57



MARINE		58
1925	WOLF OUTBOARD 4T 10W30	58
1956	WOLF IN-OUTBOARD 4T 25W40	58
1912	WOLF OUTBOARD 2TTC-W3	58
1915	WOLF UNIVERSAL 2T BIO	58
AGRICU	ILTURE	59
1425	WOLF S.T.O.U. 10W30	59
1426	WOLF S.T.O.U. 10W40	59
1435	WOLF S.T.O.U. 15W30	59
1436	WOLF S.T.O.U. 15W40	59
1446	WOLF S.T.O.U. 20W40	60
3119	WOLF TRACTOFLUID 50	60
3120	WOLF TRACTOFLUID 100	60
3121	WOLF TRACTOFLUID 170	60
23121	WOLF TRACTOFLUID 170 BM	61
3122	WOLF TRACTOFLUID 400	61
3123	WOLF TRACTOFLUID 500	61
3124	WOLF TRACTOFLUID 600	61
1726	WOLF SUPER CPO 10W40	62
13125	WOLF AGRIFLOW 4T 10W30	62
1406	WOLF AGRIFLOW 4T 15W40	62
1503	WOLF AGRIFLOW 4T SAE 30 SJ	62
1905	WOLF SYNTH 2T	63
1908	WOLF SEMI-SYNT 2T WOLF UNIVERSAL 2T	63
1900 1910	WOLF UNIVERSAL 21 WOLF AGRIFLOW 2T	63
29081	WOLF AGRIFLOW CHAIN SAW	64
2908 I 5503	WOLF AGRIFLOW CHAIN SAW	64
	VVOLI MUNI LOVV DIOCI MIN	()4



RY	65
WOLF AROW HVLPD ISO 46	65
WOLF AROW ISO 5	65
WOLF AROW ISO 10	65
WOLF AROW ISO 15	65
WOLF AROW ISO 22	66
WOLF AROW ISO 32	66
WOLF AROW ISO 46	66
WOLF AROW ISO 68	66
WOLF AROW ISO 100	67
WOLF AROW ISO 150	67
WOLF AROW ISO 220	67
WOLF AROW ISO 320	67
WOLF AROW SAE 10W	68
WOLF AROW HV ISO 15	68
WOLF AROW HV ISO 22	68
WOLF AROW HV ISO 32	68
WOLF AROW HV ISO 46	69
WOLF AROW HV ISO 68	69
WOLF AROW HV ISO 100	69
WOLF AROW XHV ISO 32	69
WOLF AROWEP ISO 46	70
WOLF AROWEP ISO 68	70
WOLF AROWEP ISO 100	70
WOLF AROWEP ISO 150	70
WOLF AROWEP ISO 220	71
	71
	71
	71
	72
	72
	72
	72
	73
	73
	73
	73
	74
	74
	74
	74
	75 75
	75 75
	75
	75
WOLF REAL TRANSPER OIL 130 32	76
	WOLF AROW HVLPD ISO 46 WOLF AROW ISO 5 WOLF AROW ISO 10 WOLF AROW ISO 15 WOLF AROW ISO 22 WOLF AROW ISO 32 WOLF AROW ISO 32 WOLF AROW ISO 46 WOLF AROW ISO 68 WOLF AROW ISO 100 WOLF AROW ISO 150 WOLF AROW ISO 220 WOLF AROW ISO 320 WOLF AROW ISO 320 WOLF AROW ISO 320 WOLF AROW ISO 320 WOLF AROW HV ISO 15 WOLF AROW HV ISO 32 WOLF AROW HV ISO 38 WOLF AROW ISO 39 WOLF AROW ISO 30 WOLF AROW ISO 320 WOLF WAY LUBRICANT ISO 32 WOLF WAY LUBRICANT ISO 32 WOLF WAY LUBRICANT ISO 320



GREAS	ES	77
9141	WOLF LITHIUM COMPLEX EP 2	77
9126	WOLF LITHIUM GREASE EP 1	77
9130	WOLF LITHIUM GREASE EP 2	77
9115	WOLF LITHIUM GREASE EP 3	77
9100	WOLF MULTIPURPOSE GREASE 2	78
9103	WOLF MULTIPURPOSE GREASE 3	78
9182	WOLF ALL-PURPOSE EP NR. 0	78
9180	WOLF ALL-PURPOSE EP NR. 00	78
9183	WOLF CALCIUM LITHIUM EP2 HEAVY	79
9184	WOLF LITHIUM CALCIUM EP2 GREEN	79
9140	WOLF LITHIUM GREASE EPA	79
9120	WOLF MULTI MOLY GREASE 2	79
9150	WOLE HIGH TEMPERATURE GREASE 2	80





OW20 LL FE
This is a full synthetic lub for the newest engines o

This is a full synthetic lubricant mandatory for the newest engines of VW/Audi . It provides outstanding engine cleanliness, wear protection, strong durability and Fuel Economy.

OFFICIALTECH

FEATURES

Performance in keeping the engine clean Superior fuel economy and CO2 reduction Excellent fluidity at low temperature

SPECIFICATION LEVEL

VW 508 00/509 00 VW TL 525 77

CONTENT PN CODE

250ML	_
500ML	_
1L	8331138
4L	_
5L	8331336
20L	8331732
60L	8331831
205L	8331930
1000L	8331534
BULK	

PRODUCTCODE 65621

OFFICIALTECH OW20 MS-V

Full synthetic lubricant for gasoline and diesel direct injection Volvo Engine Architecture engines. Ensures oil drain intervals of up to 30000 km. Fuel economy benefit over a reference oil of 3.4 %.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A1/B1-12 VOLVO Approval VCC RBS0-2AE

CONTENT PN CODE

250IVIL	
500ML	_
1L	8332517
4L	_
5L	8332715
20L	8333217
60L	8333316
205L	8333118
1000L	8332913
BULK	_

PRODUCTCODE 65617

OFFICIALTECH OW30 MS-BFE

Full synthetic lubricant meeting the BMW Longlife-12 FE specification. Adapted to meet the requirements of the latest technology of turbo engines requiring high performance and lower viscosity oils.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA C2-12 BMW LONGLIFE-12 FE

CONTENT PN CODE

250ML	_
500ML	_
1L	8336317
4L	_
5L	8336515
20L	8336911
60L	8337017
205L	8337116
1000L	8336713
BULK	_

PRODUCTCODE 65619

OFFICIALTECH OW30 MS-BHDI

This is a full synthetic lubricant based on carefully selected very high quality base oils, specially developed for the PSA EURO VI Blue HDi DW10F engines. 4,2% Fuel Economy over a 5W40 reference oil.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA C2-12 PSA Approval B71 2312

CON	ITEN	ΓPN	I CODE

250ML	_
500ML	_
1L	8323393
4L	_
5L	8323591
20L	8323898
60L	8323997
205L	8324093
1000L	8323690
BULK	_



PRODUCTCODE 65615

11





OFFICIALTECH OW30 MS-FFE

Full synthetic lubricant for EURO 6 TDCI Duratorq engines of Ford models from 2014 onwards. Ensures long oil drain intervals, has special elastomer compatibility and antichain wear characteristics.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA C2-12 FORD WSS-M2C950-A

CONTENT PN CODE

250ML	_
500ML	_
1L	8333712
4L	_
5L	8333910
20L	8334313
60L	8334412
205L	8334511
1000L	8334115
BULK	_



OFFICIALTECH 5W20 MS-FE

Full synthetic motor oil meeting the requirements of the new Ford EcoBoost petrol engines. Ensures reduced fuel consumption and exhaust emission reduction, combined with excellent cold start behavior.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A1/B1-12 API SN FORD Approval WSS-M2C948-B

CONTENT PN CODE

250ML	_
500ML	_
1L	8329975
4L	8320187
5L	8320385
20L	8324611
60L	8324512
205L	8321917
1000L	8322570
BULK	_

PRODUCTCODE 65612

OFFICIALTECH 5W30 C1

Full synthetic, fuel economy "Low SAPS" motor oil for gasoline/LPG and diesel engines of passenger cars with or without turbo, requiring the lowest levels of sulphated ash, phosphorus and sulfur.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

ACEA C1-12 FORD WSS-M2C934-B JASO DL-1

CONTENT PN CODE

250ML	_
500ML	_
1L	8307713
4L	8307812
5L	8307911
20L	8317279
50L	8317477
205L	8317576
1000L	8317675
BULK	_

PRODUCTCODE 65605

OFFICIALTECH 5W30 C2

This is a full synthetic high-performance engine oil with low viscosity, especially developed to provide the highest fuel economy and lowest CO2 emissions.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

ACEA C2-12 API SN/CF FIAT 9.55535-S1 PSA Approval B71 2290 RENAULT RN 0700

CONTENT PN CODE

250ML	_
500ML	_
1L	8308918
4L	8309014
5L	8309113
20L	8319679
60L	8319877
205L	8319976
1000L	8310089
BULK	_





OFFICIALTECH 5W30 C3

Full synthetic lubricant, formulated with the latest Mid SAPS technology. It provides fuel economy, extends the service life and protects particulate filters and exhaust after-treatment devices.

FEATURES

Full aftertreatment device protection. Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

ACEA C3-12 BMW LONGLIFE-04 GM Approval dexos 2 MB Approval 229.51 MB Approval 229.52 VW Approval 502 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8308017
4L	8308116
5L	8308215
20L	8317873
60L	8318078
205L	8318177
1000L	8318276
BULK	_



PRODUCTCODE 65608

OFFICIALTECH 5W30 C4

This is a latest generation, full synthetic high-performance lubricant, especially formulated to provide superior protection of the after-treatment systems of Renault engines.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

ACEA C4-12 MB 229.51 MB 226.51 RENAULT Approval RN 0720

CONTENT PN CODE

250ML	_
500ML	_
1L	8308314
4L	8308413
5L	8308512
20L	8318474
60L	8318672
205L	8318771
1000L	8318870
BULK	_

OFFICIALTECH 5W30 LL III

This is a full synthetic, new generation highperformance lubricant. It is a Mid SAPS oil which meets Euro 4 and Euro 5 norms and provides protection to the DPF.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

ACEA C3-12 ACEA C2* BMW LONGLIFE-04 MB Approval 229.51 PORSCHE C30 VW Approval 504 00/507 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8307416
4L	8307515
5L	8307614
20L	8316678
60L	8316876
205L	8316975
1000L	8317071
BULK	_

PRODUCTCODE 65604

OFFICIALTECH 5W30 MS-F

Full synthetic motor oil developed for the requirements of Ford WSS-M2C913-C/D specification. It is characterized by significantly improved lubricating properties and provides Fuel Economy (>3%).

FEATURES

Superior fuel economy and CO2 reduction. Performance in keeping the engine clean. Excellent fluidity at low temperature .

SPECIFICATION LEVEL

ACEA A1/B1-12 ACEA A5/B5-12 API SL/CF FORD Approval WSS-M2C913-C/D RENAULT RN 0700

CONTENT PN CODE

250ML	_
500ML	_
1L	8308611
4L	8308710
5L	8308819
20L	8319075
60L	8319273
205L	8319372
1000L	8319471
BULK	_





ECOTECH OW20 FE

Full synthetic motor oil with high level fuel economy capacities and excellent fluidity at very low temperatures.

SPECIFICATION LEVEL

ACEA A1/B1-10 API SN ILSAC GF-5

CONTENT PN CODE

250ML	_
500ML	_
1L	8324208
4L	8324307
5L	8324406
20L	8325007
60L	8325106
205L	8325205
1000L	8324802
BULK	_

PRODUCTCODE 16104

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction.

PRODUCTCODE 16104

ECOTECH OW30 FE

Full synthetic engine oil of the latest generation. It offers excellent fluidity, which ensures immediate lubrication after starting. Because of its low viscosity, it is fuel-saving.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A3/B4-12 API SM BMW LONGLIFE-01 MB 229.3 VW 502 00 VW 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8309205
4L	8309304
5L	8309403
20L	8311451
60L	8311659
205L	8311758
1000L	8311857
BULK	_

PRODUCTCODE 14105

ECOTECH OW30 C3 FE

Full synthetic "low saps" and low viscosity engine for the lubrication of gasoline and diesel engines. Significant fuel economy can be obtained, compaired to standard motor oils.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA C2* ACEA C3-12 Level API SN/CF BMW LONGLIFE-04 Level MB 229.31 Level

CONTENT PN CODE

250ML	_
500ML	_
1L	8332302
4L	_
5L	8332500
20L	8324000
50L	8329241
205L	8320651
1000L	8332906
BULK	_

PRODUCTCODE 16105

ECOTECH OW40 FE

Full synthetic engine oil of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.

FEATURES

Performance in keeping the engine clean. Superior fuel economy and CO2 reduction. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A3/B4-12 API SN BMW LONGLIFE-01 MB Approval 229.5 VW 502 00 VW 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8320507
4L	8320705
5L	8320903
20L	8321306
60L	8321405
205L	8321504
1000L	8321207
BULK	_





VITALTECH 0W30 V

Full synthetic oil meeting the requirements of Volvo cars. It has increased lubricating properties and better fuel economy. It procures a reduced fuel consumption and a longer lifetime of the engine.

FEATURES

Very good fluidity at low temperature. Performance in keeping the engine clean. Superior fuel economy and CO2 reduction.

SPECIFICATION LEVEL

ACEA A5/B5-12 API SL/CF

CONTENT PN CODE

250ML	_
500ML	_
1L	8324062
4L	_
5L	8324260
20L	8326707
60L	8326806
205L	8326905
1000L	8326851
BULK	_



PRODUCTCODE 14115

VITALTECH 5W30

Full synthetic engine oil of the latest generation for gasoline and diesel engines with turbocharging. Due to the excellent fluidity and low resistance at start this product is fuel saving.

FEATURES

Performance in keeping the engine clean. Excellent fluidity at low temperature. Longer oil drain interval.

SPECIFICATION LEVEL

ACEA A3/B4-12 API SL/CF MB 229.3 OPEL GM-LL-B-025 VW 502 00 VW 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8309809
4L	8309908
5L	8300011
20L	8312656
60L	8312854
205L	8312953
1000L	8313059
BULK	_



VITALTECH 5W30 ASIA/US

This is a full synthetic motor oil, providing outstanding wear and sludge protection. Thanks to its enhanced frictional properties, it actively contributes to fuel economy.

FEATURES

Outstanding engine cleanliness and durability. Excellent fluidity at low temperature. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

API SN CHRYSLER MS 6395 FORD WSS-M2C946-A GM dexos 1 ILSAC GF-5

CONTENT PN CODE

250ML	_
500ML	_
1L	8302510
4L	8302619
5L	8302718
20L	8319853
60L	8310065
205L	8310164
1000L	8310263
BULK	_

PRODUCTCODE 16115

VITALTECH 10W30 ASIA/US

This is a high quality lubricant, providing outstanding wear and sludge protection. Due to its enhanced frictional properties, improved fuel economy is obtained.

FEATURES

Outstanding engine cleanliness and durability. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

API SN ILSAC GF-5

250ML	_
500ML	_
1L	8327698
4L	8327896
5L	_
20L	8328299
60L	8328398
205L	8328497
1000L	8328091
BULK	_







VITALTECH 10W30

This is a semi synthetic lubricant based on carefully selected highly refined base oils. Providing outstanding wear and sludge protection, even under the most severe driving conditions.

FEATURES

Outstanding engine cleanliness and durability.

Excellent fluidity at low temperature.

SPECIFICATION LEVEL

API SN ILSAC GF-5

CONTENT PN CODE

250ML	_
500ML	_
1L	8338304
4L	8338403
5L	_
20L	8338908
60L	8339004
205L	8339103
1000L	8339202
BULK	_



VITALTECH 5W40 PI C3

This is a full synthetic, high-performance Mid SAPS engine oil. It meets the requirements of VW 505.01 specification, corresponds to Euro 4 and Euro 5 norms, and protects the DPF.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Superior fuel economy and CO2 reduction.

SPECIFICATION LEVEL

ACEA C3-12 API SN/CF BMW LONGLIFE-04 GM dexos 2 MB 229.31 VW Approval 505 01

CONTENT PN CODE

250ML	_
500ML	_
1L	8302817
4L	8302916
5L	8303012
20L	8310461
60L	8310669
205L	8310768
1000L	8310867
BULK	_

PRODUCTCODE 21116

VITALTECH 5W40

Full synthetic engine oil designed to meet the strict requirements of manufacturers. It provides excellent fluidity at low temperatures, a very low resistance when starting and an exceptional VI.

FEATURES

Outstanding engine cleanliness and durability. Excellent fluidity at low temperature. Longer oil drain interval.

SPECIFICATION LEVEL

ACEA A3/B4-12 API SN/CF BMW LONGLIFE-01 MB 229.3 PSA B71 2296 VW Approval 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8311093
4L	8311192
5L	8311291
20L	8311895
50L	8311994
205L	8312090
1000L	8312199
BULK	_

PRODUCTCODE 16116

VITALTECH 5W40 B4 DIESEL

This is a full synthetic lubricant based on carefully selected very high quality base oils and additives of the latest generation, specially designed to meet the strict requirements of manufacturers.

FEATURES

Total engine protection. Excellent fluidity at low temperature. Longer oil drain interval.

SPECIFICATION LEVEL

ACEA A3/B4-10 API SN/CF BMW LONGLIFE-01 MB 229.3 PSA B71 2296 RENAULT RN 0710

CONTENT PN CODE

_
_
8333903
8334009
_
8334306
8334405
8334504
8334603
_





VITALTECH 5W40 GAS

Full synthetic lubricant designed to meet the strict requirements of LPG, CNG and Duel Fuel powered passenger cars. The special technology protects the valves and neutralizes the acid compounds.

FEATURES

Total gas engines protection. Cold start. Drain interval extension.

PRODUCTCODE 22116

SPECIFICATION LEVEL

ACEA C3-08 API SN/CF FIAT 9.55535-T2 MB 229.3 RENAULT RN 0710 VW 502 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8325892
4L	_
5L	_
20L	8326493
60L	8326592
205L	8326691
1000L	8326295
BULK	_



VITALTECH 5W50

Full synthetic engine oil with excellent cold start properties and a high viscosity at hot engine.

FEATURES

Performance in keeping the engine clean. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A3/B4-08 API SN/CF BMW LONGLIFE-01 MB 229.3 VW 501 01 VW 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8314629
4L	_
5L	8314728
20L	8315893
60L	8315992
205L	8316098
1000L	8316197
BULK	_

PRODUCTCODE 23117

VITALTECH 10W60 M

This is a full synthetic lubricant based on carefully selected very high quality base oils. This passenger car engine oil is for severe duty use, like racing and hot climates.

FEATURES

Very good fluidity at low temperature. Outstanding engine cleanliness and durability. Excellent protection for high output engines.

SPECIFICATION LEVEL

ACEA A3/B4-08 API SN/CF BMW M-MODELS MB 229.3 Level VW 501 01 VW 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8335709
4L	_
5L	8335808
20L	8327056
60L	8336201
205L	8336300
1000L	8336409
BULK	_

PRODUCTCODE 16128

VITALTECH 10W60

Semi synthetic motor oil for gasoline and diesel engines used for racing and hot climate use, ensuring a perfect lubrication.


FEATURES

Performance in keeping the engine clean. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A3/B4-08 API SN/CF VW 501 01 VW 505 00

CONTENT PN CODE



PRODUCTCODE 24118

17



EXTENDTECH



PRODUCTCODE 28116

EXTENDTECH 5W40 HM

Full synthetic engine oil for the lubrication of most petrol and diesel engines with turbocharging.

FEATURES

Performance in keeping the engine clean. Excellent fluidity at low temperature. Longer oil drain interval

SPECIFICATION LEVEL

ACEA A3/B4-12 API SN MB Approval 229.5 PSA B71 2296 VW Approval 502 00 VW Approval 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8321184
4L	8321382
5L	8321580
20L	8321986
60L	8322181
205L	8322082
1000L	8321788
BULK	_



PRODUCTCODE 15127

EXTENDTECH 10W40 HM

Semi synthetic motor oil for gasoline and diesel engines with direct fuel injection. Meets the API SM specification for gasoline engines with extended oil drain intervals.

FEATURES

Outstanding engine cleanliness and durability. Very good fluidity at low temperature. Longer oil drain interval.

SPECIFICATION LEVEL

ACEA A3/B4-08 API SM/CF MB 229.3 RENAULT RN 0700 RENAULT RN 0710 VW 505 00

250ML	_
500ML	_
1L	8302114
4L	8302213
5L	8302312
20L	8318054
60L	8318252
205L	8318351
1000L	8318450
BUI K	_



GUARDTECH



GUARDTECH 10W40 SN

Semi synthetic engine oil for petrol and diesel engines of passenger cars and vans. It ensures great fluidity at low temperature and a stable viscosity at high temperatures.

FEATURES

Excellent engine cleanliness and durability. Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A3/B3-10 ACEA A3/B4-08 API SN/CF MB 229.1

CONTENT PN CODE

_
_
8310195
8310294
_
8310393
8310492
8310591
8310690
_

PRODUCTCODE 16127

GUARDTECH 10W40 B4

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is an advanced engine oil developed to meet ACEA A3/B4-08 requirements and to fulfill Euro 4 norms.

FEATURES

Performance in keeping the engine clean. Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A3/B3-10 ACEA A3/B4-08 API SL/CF MB Approval 229.1 VW 501 01 Level VW 505 00 Level

CONTENT PN CODE

250IVIL	_
500ML	_
1L	8303616
4L	8303814
5L	8304019
20L	8313462
60L	8313660
205L	8313769
1000L	8313868
BULK	_

PRODUCTCODE 23127

GUARDTECH 10W40 B4 DIESEL

Semi synthetic engine oil for diesel engines with direct injection like HDI or CDI. Its highquality components ensure a great fluidity at low temperature and a stable viscosity at high temperature.

FEATURES

Performance in keeping the engine clean. Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA A3/B4-08 ACEA A3/B3-10 API SL/CF MB 229.1 VW 505 00

CONTENT PN CODE

250ML	_
500ML	_
1L	8303517
4L	8303715
5L	8303913
20L	8312861
60L	8313066
205L	8313165
1000L	8313264
BULK	_

PRODUCTCODE 23126

GUARDTECH 15W40 SL/CF

This is a very high-quality mineral oil with proven performance, suitable for a wide range of applications. It can be used in most 4-stroke gasoline and diesel cars and light

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 14136

SPECIFICATION LEVEL

ACFA A3/B3-10 ACEA A3/B4-08 APISL/CF MB 229.1 VW 501 01 Level VW 505 00 Level

250ML	_
500ML	_
1L	8300110
4L	8300219
5L	8300318
20L	8313257
60L	8313455
205L	8313554
1000L	8313653
BULK	_





GUARDTECH 15W40 B4 DIESEL

Mineral oil for four-stroke diesel cars, including diesel engines with direct injection such as Common Rail, HDI, CDI, etc. Shows great fluidity, a stable viscosity and high resistance to ageing.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 26136

SPECIFICATION LEVEL

ACEA A3/B3-10 ACEA A3/B4-08 API SL/CF MB 229.1

CONTENT PN CODE

250ML	_
500ML	_
1L	8334801
4L	8334900
5L	_
20L	8335204
60L	8335303
205L	8335402
1000L	8335501
BULK	_



GUARDTECH 15W50 SL/CF

Semi synthetic oil of the highest quality. Its adapted composition ensures optimal cleanliness of the engine in all conditions. It protects the catalyst and ensures optimal performance.

FEATURES

Good engine protection and cleanliness.

PRODUCTCODE 14138

SPECIFICATION LEVEL

ACEA A3/B3-10 ACEA A3/B4-08 API SL/CF MB 229.1

250ML	_
500ML	_
1L	8300417
4L	_

CONTENT PN CODE

1L 8300417 4L — 5L 8300516 20L 8313851 60L 8314056 205L 8314155 1000L 8314254 BULK —



GUARDTECH 20W50 SN/CF

A very high quality motor oil, suitable for most of gasoline and diesel cars and light trucks. It has a very good resistance to oxidation and optimal detergent and dispersion properties are obtained.

FEATURES

Engine protection and cleanliness.

SPECIFICATION LEVEL

ACEA A3/B3-10 ACEA A3/B4-08 API SN/CF MB 229.1

CONTENT PN CODE

250ML	_
500ML	_
1L	8326790
4L	8326998
5L	_
20L	8327391
50L	8327490
205L	8327599
1000L	8327193
BULK	_



GUARDTECH 20W50 SL/CF

A very high quality mineral engine oil for most 4-stroke engines. Provides very good resistance to oxidation and has optimal detergent and dispersion properties. Has very high lubricating power.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 14147

SPECIFICATION LEVEL

ACEA A3/B3-10 ACEA A3/B4-08 API SL/CF MB 229.1 VW 505 00 Level VW 501 01 Level

250ML	_
500ML	_
1L	8300615
4L	8300714
5L	8300813
20L	8314452
60L	8314650
205L	8314759
1000L	8314858
BULK	_



GUARDTECH



GUARDTECH 15W40 SF/CD

Multigrade engine oil for the lubrication of gasoline and diesel engines of passenger cars with naturall aspiration or turbocharging. This oil is characterized by a combination of good detergent and dispersion properties, together with a low ash content.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 1336

SPECIFICATION LEVEL

API SF/CD MIL MIL-L-46152 B

CONTENT PN CODE

250ML	_
500ML	_
1L	8325052
4L	_
5L	8325458
20L	8326158
60L	8317491
205L	8326257
1000L	8325953
BULK	_



GUARDTECH 20W50 SF/CD

Multigrade engine oil for the lubrication of gasoline and diesel engines of passenger cars with natural aspiration or turbo charging. This oil is characterized by a combination of good detergent and good dispersion properties, together with a low ash content.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 1347

SPECIFICATION LEVEL

API SF/CD MIL MIL-L-46152 B

250ML	_
500ML	_
1L	8325250
4L	_
5L	8325656
20L	8326554
60L	8326653
205L	8326752
1000L	8326356
BULK	_



GUARDTECH SAE 40 SF/CD

Light detergent monograde oil, made of paraffinic base oils and selected additives. It offers good protection against oxidation and corrosion.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 184

SPECIFICATION LEVEL

API SF/CD MB 226.0 MIL MIL-L-46152 B

CONTENT PN CODE

250ML	_
500ML	_
1L	8300004
4L	_
5L	8300103
20L	8301025
60L	8301223
205L	8301322
1000L	8301421
BULK	_



GUARDTECH SAE 50 SF/CD

Monograde engine oil for the lubrication of gasoline and diesel engines of passenger cars. Characterized by good detergent and dispersant properties, together with a low ash content.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 185

SPECIFICATION LEVEL

API SF/CD MB 226.0 MIL MIL-L-46152 B

250ML	_
500ML	_
1L	8300202
4L	_
5L	8300301
20L	8301629
60L	8301827
205L	8301926
1000L	8302022
BULK	_



GUARDTECH



GUARDTECH SAE 40

This is a straight mineral oil, made of highly refined base oils.

SPECIFICATION LEVEL

API SA

CONTENT PN CODE

250ML	_
500ML	_
1L	8307003
4L	8307102
5L	8307201
20L	8305894
60L	8306099
205L	8306198
1000L	8306297
BULK	_

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 4704

GUARDTECH SAE 50

This is a straight mineral oil, made of highly refined base oils.

Engine protection and cleanliness.

SPECIFICATION LEVEL

API SA

CONTENT PN CODE

250ML	_
500ML	_
1L	8307300
4L	8307409
5L	8307508
20L	8306495
60L	8306693
205L	8306792
1000L	8306891
BULK	_

FEATURES





OFFICIALTECH 5W30 UHPD

Full synthetic lubricant satisfying the highest performance standards for large trucks. The formulation includes a state of the art friction modifier for improved fuel economy.

FEATURES

Full aftertreatment system protection. Superior fuel economy and CO2 reduction. Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

ACEA E6-12 ACEA E9-12 MAN Approval M3477 MAN Approval M3677 MB Approval 228.51 VOLVO Approval VDS-4

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8325663
60L	8325762
205L	8325861
1000L	8325465
BULK	_



PRODUCTCODE 15726

OFFICIALTECH 10W40 UHPD

This is a full synthetic lubricant which satisfies the highest performance standards for large trucks. Used for engines equipped with after treatment systems, in combination with low-sulfur diesel.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

ACEA E6-12 ACEA E9-12 API CJ-4 MAN Approval M3477 MB Approval 228.51 VOLVO Approval VDS-4

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8323973
60L	8329067
205L	8329166
1000L	8325694
BULK	_



This is a semi synthetic lubricant based on carefully selected highly refined base oils. It is "Low SAPS" developped to meet Euro V, Euro VI and U.S. EPA 07 emission standards.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

ACEA E9-12 API CJ-4/SN CATERPILLAR ECF-3 MAN Approval M3575 RENAULT Approval RLD-3 VOLVO Approval VDS-4

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8318658	
60L	8318856	
205L	8318955	
1000L	8319051	
BULK	_	

PRODUCTCODE 15725

OFFICIALTECH 10W40 ULTRA MS

This is a full synthetic ultra-high performance oil of the latest technology. Suitable for engines of large trucks with particulate filters, in combination with lowsulfur diesel (maximum 50 ppm).

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

ACEA E6-12 API CI-4 MAN Approval M3477 MB Approval 228.51 RENAULT Approval RLD-2 VOLVO Approval VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8307317
20L	8316074
60L	8316272
205L	8316371
1000L	8316470
BULK	_



OFFICIALTECH 10W40 S3

Full synthetic lubricant based on carefully selected very high quality base oils. This "long-drain" oil is engineered to provide outstanding lubrication to modern, high performance diesel engines.

FEATURES

Superior emmission reduction. Outstanding engine cleanliness and durability. Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA E4-12 MACK Approval EO-N MAN M3277 MB 228.5 VOLVO Approval VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8313790
60L	8313899
205L	8313998
1000L	8314094
BULK	_



OFFICIALTECH 10W40 S2

Semi-synthetic "long-drain" UHPD engine oil. Meets the toughest requirements of the European manufacturers of heavy trucks and guarantees the highest level of engine cleanliness.

FEATURES

Outstanding engine cleanliness and durability. Very long oil drain interval. Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA E7-08 Issue 2 API CI-4 MACK Approval EO-N RENAULT Approval RLD-2 VOLVO Approval VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8300042
60L	8300240
205L	8300349
1000L	8300448
BULK	_

PRODUCTCODE 1627

OFFICIALTECH 15W40 MS

This is a "Low SAPS" oil, made of specially selected, high-quality base oils and a customized additive package, in order to meet Euro V, Euro VI and U.S. EPA 07 emission standards.

FEATURES

Full aftertreatment system protection. Outstanding engine cleanliness and durability. Long oil drain interval.

SPECIFICATION LEVEL

ACEA E9-12 API CJ-4/SN CATERPILLAR ECF-3 CUMMINS CES 20081 MAN Approval M3575 VOLVO Approval VDS-4

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8302411
20L	8319259
60L	8319457
205L	8319556
1000L	8319655
BULK	_







ECOTECH 5W30 ULTRA

Full synthetic Ultra High Performance Diesel engine oil, meeting the highest performance standards for heavy trucks. It provides optimal protection against wear and ageing.

FEATURES

Outstanding engine cleanliness and durability. Excellent fluidity at low temperature. Very long oil drain interval.

SPECIFICATION LEVEL

ACEA E4-12
ACEA E7-12
API CI-4
DAF EXTENDED DRAIN
DEUTZ DQC-IV-10
MACK Approval EO-N Premium Plus
MAN Approval M3277
MB Approval 228.5
MTU Oil Category 3

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8302237
60L	8302435
205L	8302534
1000L	8302633
BULK	_



VITALTECH 10W40 ULTRA

This is a semi synthetic Ultra High Performance Diesel engine oil that meets the highest performance standards for heavy trucks. This oil is not suitable for vehicles fitted with particulate filters.

FEATURES

Outstanding engine cleanliness and durability. Lower fuel consumption and CO2 emissions. Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA E7-12 ACEA E4-12 API CI-4 MAN Approval M3277 MB Approval 228.5 VOLVO Approval VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8300806
20L	8303432
60L	8303630
205L	8303739
1000L	8303838
BULK	_



PRODUCTCODE 26626

VITALTECH 10W40 EXTRA

Synthetic base lubricant for geographical regions with high sulphur content fuels. Excellent protection against deposits in oil pipes, turbo's and provides improved protection against camshaft wear.

FEATURES

Outstanding engine cleanliness and durability.
Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA E7-08 Issue 2 API CI-4/SL MAN M3275-1 MB 228.3 RENAULT RLD-2 VOLVO VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8337314
20L	8337710
60L	8337819
205L	8337918
1000L	8337512
BULK	_



VITALTECH 10W40

Semi synthetic motor oil, which provides excellent protection against deposits in pipes and turbo engines. It also ensures optimal protection against camshaft wear.

FEATURES

Outstanding engine cleanliness and durability.
Very good fluidity at low temperature.

SPECIFICATION LEVEL

ACEA E7-12 API CI-4/SL MAN Approval M3275-1 MB Approval 228.3 VOLVO Approval VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8300912
20L	8315053
60L	8315251
205L	8315350
1000L	8315459
BULK	_

PRODUCTCODE 14626

VITALTECH 15W40 EXTRA

Universal mineral heavy duty Long Drain diesel oil with higher TBN providing excellent protection against deposits and showing an improved camshaft wear protection.

FEATURES

Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

ACEA E7-08 Issue 2 API CI-4/SL CUMMINS CES 20078 MAN M3275-1 MB 228.3 VOLVO VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8319426
20L	8319488
60L	8319587
205L	8319686
1000L	8319785
RI II K	







VITALTECH 15W40

This is a high-performance mineral diesel engine oil which delivers reliable performance in a broad range of heavy-duty applications. Suitable for Euro II, Euro III and some Euro IV engines.

FEATURES

Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

ACEA E7-12 API CI-4/SL MAN Approval M3275-1 MB Approval 228.3 RENAULT Approval RLD-2 VOLVO Approval VDS-3

CONTENT PN CODE

250ML	_
500ML	_
1L	8301018
4L	_
5L	8301117
20L	8315657
60L	8315855
205L	8315954
1000L	8316050
BULK	_

EXTENDTECH



PRODUCTCODE 13536

EXTENDTECH 15W40

Universal engine oil meeting the specifications of European and American manufacturers of heavy duty diesel.
Suitable for Euro II, Euro III and some Euro IV engines, but not for Euro IV with DPF.

FEATURES

Performance in keeping the engine clean. Very long oil drain interval.

SPECIFICATION LEVEL

ACEA E5 Level
ACEA A3/B4-10
ALLISON C4
API CH-4/SJ
CATERPILLAR ECF-1a
CUMMINS CES 20071
CUMMINS CES 20072
CUMMINS CES 20076
CUMMINS CES 20077
DEUTZ DQC II-05

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8310850
60L	8311055
205L	8311154
1000L	8311253
BUI K	_





GUARDTECH 15W40 SHPD

This is a high-quality mineral oil delivering protection to all diesel engines. It can be used all year round in the toughest conditions. Its high resistance against ageing results in long drain periods.

FEATURES

Performance in keeping the engine clean. Long period between oil change.

SPECIFICATION LEVEL

ACEA E3-96 Issue 4 API CG-4/SJ MACK EO-L MAN Approval M3275-1 MB Approval 228.3 VOLVO VDS-2

CONTENT PN CODE

250ML	_
500ML	_
1L	8300905
4L	_
5L	8301001
20L	8304033
60L	8304231
205L	8304330
1000L	8304439
BULK	_

PRODUCTCODE 1236

GUARDTECH 20W50 SHPD

This is a high-quality mineral oil delivering protection to all diesel engines. It can be used all year round in the toughest conditions. Its high resistance against ageing results in long drain periods.

FEATURES

Performance in keeping the engine clean. Long period between oil change.

SPECIFICATION LEVEL

ACEA E3-96 Issue 4 API CG-4/SI MACK EO-L MAN M3275-1 MB 228.3 VOLVO VDS-2

CONTENT PN CODE

250ML	
500ML	_
1L	8301100
4L	_
5L	8301209
20L	8305238
60L	8305436
205L	8305535
1000L	8305634
BULK	_

PRODUCTCODE 1247

GUARDTECH 15W40 PLUS CF-4

High-quality universal engine oil of the latest generation for gasoline, diesel, and mixed fleets. It has good detergent and dispersant properties and a good capacity to neutralize acid.

FEATURES

Performance in keeping the engine clean.

SPECIFICATION LEVEL

ACEA E2-level API CF-4/SJ CATERPILLAR TO-2 MB 228.1 VOLVO VDS level

CONTENT PN CODE

2EOV1

250IVIL		
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8319044	
60L	8319242	
205L	8319341	
1000L	8319440	
BULK	_	

PRODUCTCODE 13236

GUARDTECH 15W40 CF-4

Universal motor oil for 4-stroke gasoline and diesel engines between 1989 and 1994. It has high resistance to oxidation, good detergent and dispersant properties and high lubricity

FEATURES

Performance in keeping the engine clean.

SPECIFICATION LEVEL

API CF-4/SG CATERPILLAR TO-2 **MAN 271** MB 227.1 VOLVO VDS level

CONTENT PN CODE

250ML	_
500ML	_
1L	8308901
4L	_
5L	8309007
20L	8317248
60L	8317446
205L	8317545
1000L	8317644
BULK	_



GUARDTECH 20W50 CF-4

Universal motor oil for 4-stroke gasoline and diesel engines between 1989 and 1994. It has high resistance to oxidation, good detergent and dispersant properties and high lubricity.

FEATURES

Performance in keeping the engine clean.

PRODUCTCODE 11247

SPECIFICATION LEVEL CONTENT PN CODE

API CF-4/SG CATERPILLAR TO-2 MAN 271 MB 227.1 VOLVO VDS level

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8317842
60L	8318047
205L	8318146
1000L	8318245
BULK	_



GUARDTECH SAE 40 CF-4/SG

Monograde motor oil of high quality, suitable for diesel engines (supercharged or naturally aspirated) and gasoline engines in all circumstances.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 21204

SPECIFICATION LEVEL

API CF-4/SG MB 227.0

CONTENT PN CODE

250ML	_
500ML	_
1L	8303111
4L	_
5L	8303210
20L	8311062
60L	8311260
205L	8311369
1000L	8311468
BULK	_



GUARDTECH SAE 50 CF-4/SG

Monograde oil, mainly used in diesel engines with or without turbo between 1989 and 1994. It has high resistance to oxydation, good detergent and dispersant properties, and high lubricity.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 21205

SPECIFICATION LEVEL

API CF-4/SG MB 227.0

250ML	_
500ML	_
1L	8303319
4L	_
5L	8303418
20L	8311666
60L	8311864
205L	8311963
1000L	8312069
BULK	_





OFFICIALTECH



PRODUCTCODE 2306

OFFICIALTECH 75W90 G 50

Full synthetic lubricant which avoids gear squawk and prolongs the lifetime of the gear. It noticably improves low temperature gear shifts and ensures easy gear change at high temperature.

FEATURES

Very smooth gear shifting, no vibration. Significantly extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

API GL-4+ BMW MTF LT-4 FORD WSD-M2C200-C VW 501 50

CONTENT PN CODE

250ML	_
500ML	_
1L	8304101
4L	_
5L	_
20L	8305054
60L	8305252
205L	8305351
1000L	8305450
BULK	_

OFFICIALTECH 75W140 LS GL 5

This is a high performance semi synthetic transmission oil for all differentials, including "limited slip". It has exceptionally high viscosity stability and very high fluidity at low temperature.

FEATURES

Very smooth gear shifting, no vibration. Extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

API GL-5 BMW MSP/A MIL MIL-L-2105 D MIL MIL-L-2105 C

CONTENT PN CODE

250ML	_
500ML	_
1L	8304200
4L	_
5L	_
20L	8305658
60L	8305856
205L	8305955
1000L	8306051
BULK	_

PRODUCTCODE 2307

OFFICIALTECH 85W90 M GL 5

This gear oil is specifically designed to meet the Mercedes Benz 235.0 requirement. It has excellent properties during prolonged operation under heavy load and high temperatures.

FEATURES

Very smooth gear shifting, no vibration. Significantly extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

API GL-5 MAN 342 M-1 MB Approval 235.0 VOLVO 97310 VOLVO 97316 ZF TE-ML 07A

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8318986	
60L	8319082	
205L	8319181	
1000L	8319280	
BULK	_	

PRODUCTCODE 23310

OFFICIALTECH 75W80 ZF

This full synthetic gear oil is used in manual syncromesh transmissions, procuring improved shift comfort, low temperature fluidity and longer service life.

FEATURES

Very smooth shift performance. Significantly extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

MAN 341 F-3 MAN 341 Z-4 MB 235.4 VOLVO 97307 ZF TE-ML 01L ZF TE-ML 02L

CONTENT PN CODE

250ML	_
500ML	_
1L	8325601
4L	_
5L	_
20L	8326400
60L	8326509
205L	8326608
1000L	8326202
BULK	_





OFFICIALTECHSAE 80W ZF GL 4

This mineral gear oil is specifically designed to meet the Mercedes Benz 235.1 requirement. It has excellent properties during prolonged operation under heavy conditions.

FEATURES

Very smooth gear shifting, no vibration. Significantly extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

API GL-4 MAN 341 E-1 MAN 341 Z-2 MB Approval 235.1 ZF TE-ML 02B ZF 19C

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8318481	
60L	8318580	
205L	8318689	
1000L	8318788	
BULK	_	



A full synthetic lubricant formulated with high quality base oils specifically developed for ZF 6-speed automatic transmissions ensuring a trouble-free operation and smooth gear shifting.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

BMW M-1375.4 BMW 83220142516 HYUNDAI 040000C90SG LAND ROVER TYK500050 VW G 055 005 ZF TE-ML 11

CONTENT PN CODE

250ML	_
500ML	_
1L	8305900
4L	_
5L	_
20L	8305269
60L	8305467
205L	8305566
1000L	8305665
BULK	_

PRODUCTCODE 3012

OFFICIALTECH ATF LIFE PROTECT 8

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

BMW 83222152426 CHRYSLER 68157995AA FIAT 9.55550-AV5 JAGUAR 02JDE26444 LAND ROVER LR023288 VW G 060 162

CONTENT PN CODE

250ML	_
500ML	_
1L	8326479
4L	_
5L	_
20L	8326677
60L	8326776
205L	8326875
1000L	8326974
BULK	_

PRODUCTCODE 3016

OFFICIALTECH ATF D VI

Full synthetic Automatic Transmission Fluid. Meets the requirements of the General Motors Dexron VI specification. It can be used in applications where Dexron II and Dexron III are recommended.

FEATURES

Very smooth gear shifting, no vibration. Significantly extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

GM DEXRON VI MB 236.41 VOITH H55.6335xx

CONTENT PN CODE

250ML	_
500ML	_
1L	8305504
4L	_
5L	_
20L	8303463
60L	8303661
205L	8303760
1000L	8303869
BULK	_







OFFICIALTECH ATF MB

This is a full synthetic Automatic Transmission Fluid, mainly intended for all MB 7-speed and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

MB 236.14

250ML 500ML 1L 8305801

CONTENT PN CODE

4L 5L 8304668 20L 60L 8304866 205L 8304965 10001 8305061 BULK

OFFICIALTECH ATF MB FE

This is a full synthetic lubricant, intended for the latest MB 7-speed automatic transmissions from MB (NAG2FE+). It provides excellent frictional durability, superior performance and fuel economy.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

MB 236.15

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8328794
60L	8328893
205L	8328992
1000L	8328596
BULK	_

PRODUCTCODE 3013

OFFICIALTECH

MULTI VEHICLE ATF HD-LD

A heavy duty synthetic transmission fluid designed to deliver significantly extended drain capabilities. Suitable for automatic transmission systems in both heavy duty trucks and buses.

FEATURES

Very smooth gear shifting, no vibration. Significantly extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

MAN 339 Z3 MB 236.9 VOITH H55.6336xx VOLVO STD 1273,41 (97341) ZF TE-ML 14C ZF TE-ML 20C

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8338229
60L	8338328
205L	8338427
1000L	8337727
BULK	_





ECOTECH 75W FE

High quality full synthetic gear oil with low viscosity specifically meeting the VW Gearbox Oil SAE 75W requirement and also used in manual gear boxes of passenger cars.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

API GL-4 VW TL 521 71 VW TL 521 78 VW TL 726 VW TL 525 12

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8308659
60L	8308857
205L	_
1000L	8309052
BULK	_

ECOTECHMULTI VEHICLE ATF FE

Full synthetic Automatic Transmission Fluid meeting the requirements of most American, Japanese and European manufacturers. It has excellent oxidation stability and superior anti-wear properties.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

AISIN-WARNER JWS 3324 BMW M-1375.4 FORD MERCON SP MB 236.12 VW G 055 162 VW G 060 162

CONTENT PN CODE

250ML	_
500ML	_
1L	8329449
4L	_
5L	_
20L	8320057
60L	8320156
205L	8320255
1000L	8329944
BULK	_

PRODUCTCODE 3014

ECOTECHCVT FLUID

Full synthetic fluid designed for most CVT (Continuously Variable Transmission) gearboxes with steel push-belts or chains. It offers superior anti-wear protection and stable friction characteristics.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

FORD WSS-M2C928-A MB 236.20 MITSUBISHI CVTF-J1/SP-III NISSAN NS-1/NS-2/NS-3 TOYOTA TC VW G 052 180

CONTENT PN CODE

250ML	_
500ML	_
1L	8306006
4L	_
5L	_
20L	8305863
60L	8306068
205L	8306167
1000L	8306266
BULK	_

PRODUCTCODE 3020

ECOTECHDSG FLUID

This is a full synthetic transmission fluid, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes.

FEATURES

Significantly extended transmission life. Very smooth gear shifting, no vibration. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

BMW DCTF-1 BMW MTF LT-5 FORD WSS-M2C 936-A MB 236.21 VW G 052 182 VW G 052 529

CONTENT PN CODE

250ML	_
500ML	_
1L	8308604
4L	_
5L	_
20L	8314247
60L	8314445
205L	8314544
1000L	8314643
BULK	_





VITALTECH 75W90 GL 5

Full synthetic transmission oil for a wide field of applications. Suitable for synchronized gear boxes and heavily loaded differentials and ensures perfect service in the most difficult conditions.

FEATURES

Very smooth gear shifting, no vibration. Superior protection of critical parts. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

API MT-1 API GL-5 MAN 341 Z-2 MAN 342 M-3 MB 235.8 SCANIA STO 1:0

CONTENT PN CODE

250ML	_
500ML	_
1L	8303906
4L	8323669
5L	8304002
20L	8304453
60L	8304651
205L	8304750
1000L	8304859
BULK	_

ATAL TECH

PRODUCTCODE 2211

VITALTECH 75W80 MULTI VEHICLE

This is a high quality oil, suitable for nearly all manual gearboxes of passenger cars. It is suitable as a replacement for specific OEM original oils and reduces the complexity and storage.

FEATURES

Very smooth gear shifting, no vibration. Significantly extended transmission life. Proven resistance to oil degradation.

SPECIFICATION LEVEL

API GL-4+ FORD WSD-M2C200-D GM 1940182 HONDA MTF 94 MB 235.10 PSA B71 2330

CONTENT PN CODE

250ML	_
500ML	_
1L	8303609
4L	_
5L	8303708
20L	8303258
60L	8303456
205L	8303555
1000L	8303654
BULK	_

VITALTECH 80W90 GL 5

A synthetic based lubricant for transmissions, which distinguishes itself from the classic, hypoid GL 5-oils by its multifunctional character and its exceptional oxidation and thermal stability.

FEATURES

Very smooth gear shifting, no vibration. Optimized thermal and oxidation stability. Long transmission life.

SPECIFICATION LEVEL

API MT-1 API GL-5 MAN 342 M-2 MAN 341 E-2 MB 235.0 SCANIA STO:1

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8308055
60L	8308253
205L	8308352
1000L	8308451
BULK	_

PRODUCTCODE 2312

VITALTECH MULTI VEHICLE ATF

A full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers.

FEATURES

Very smooth gear shifting, no vibration. Significantly extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

AISIN-WARNER JWS 3309 CHRYSLER ATF +3 AND +4 FORD MERCON V GM DEXRON III-H TOYOTA TYPE T-IV VW G 055 025

CONTENT PN CODE

250ML	_
500ML	_
1L	8305603
4L	_
5L	8305702
20L	8304064
60L	8304262
205L	8304361
1000L	8304460
BULK	_





VITALTECH ATF DIII

Semi synthetic oil suitable for most automatic transmissions. Its optimal fluidity at low temperatures and exceptional frictional characteristics provide smooth switching and driving comfort.

FEATURES

Smooth shift performance. Extended transmission life. Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

FORD MERCON GM 6417-M DEXRON III-G MAN 339 V1/Z1 MB 236.5 MB 236.9 VOITH H55.6335xx

250ML	_
500ML	_
1L	8305306
4L	_
5L	8305405
20L	8302862
60L	8303067
205L	8303166
1000L	8303265
BULK	_



33

EXTENDTECH



PRODUCTCODE 2410

EXTENDTECH 75W90 LS GL 5

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is an extreme-pressure lubricant for differentials equipped with a limited slip or lock-up mechanism.

FEATURES

Smooth gear shifting.
Extended transmission life.
Optimized thermal and oxidation stability.

SPECIFICATION LEVEL

API GL-5 MIL MIL-L-2105 C MIL MIL-L-2105 D

CONTENT PN CODE

250ML	_
500ML	_
1L	8300721
4L	_
5L	_
20L	8300462
60L	8300660
205L	8300769
1000L	8300868
BULK	_

EXTENDTECH 80W90 LS GL 5

Mineral oil based on specific base oils and selected sulfur-phosphorus additives. These components ensure good performance in differentials equipped with a "limited-slip" mechanism.

FEATURES

Easy shift performance. Long transmission life. Proven resistance to oil degradation.

SPECIFICATION LEVEL

API GL-5 MIL MIL-L-2105 C MIL MIL-L-2105 D

250ML — 500ML — 1L 8300622 4L — 5L — 20L 8309250 60L 8309458 205L 8309557 1000L 8309656

BULK

CONTENT PN CODE

PRODUCTCODE 2408

EXTENDTECH 85W140 LS GL 5

Mineral oil composed of paraffinic base oils and selected additives based on sulfur-phosphorus. A special friction additive emparts to this oil the necessary properties to be used in differentials, which are equipped with a "limited-slip" mechanism.

FEATURES

Easy gear shifting. Long transmission life.

SPECIFICATION LEVEL

API GL-5 MIL MIL-L-2105 C MIL MIL-L-2105 D

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8309854
60L	8300066
205L	8300165
1000L	8300264
BULK	_

CONTENT PN CODE

PRODUCTCODE 2409

EXTENDTECH 75W80 GL 5

This is an extreme-pressure lubricant for gear boxes, specially formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.


FEATURES

Smooth shift performance. Long transmission life. Proven resistance to oil degradation.

SPECIFICATION LEVEL

API GL-5 MIL MIL-L-2105 C MIL MIL-L-2105 D

CONTENT PN CODE



PRODUCTCODE 2300

37



EXTENDTECH



PRODUCTCODE 2209

EXTENDTECH 75W90 GL 5

Semi synthetic transmission oil with an exceptionally high viscosity index. It exhibits excellent fluidity at low temperatures and ensures a long life of the oil and gears.

FEATURES

Smooth shift performance. Long transmission life. Proven resistance to oil degradation.

SPECIFICATION LEVEL

API GL-5 MIL MIL-L-2105 D

CONTENT PN CODE

250ML	_
500ML	_
1L	8303302
4L	8323461
5L	8303500
20L	8302053
60L	8302251
205L	8302350
1000L	8302459
BULK	_

EXTENDTECH 80W90 GL 5

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

FEATURES

Easy gear shifting.

Long transmission life.

SPECIFICATION LEVEL

API GL-5 MAN 342 M-1 MAN 342 M-2 ZF TE-ML 05A ZF TE-ML 16C ZF TE-ML 19B

CONTENT PN CODE

250ML	_
500ML	_
1L	8304309
4L	8323867
5L	8304507
20L	8306259
60L	8306457
205L	8306556
1000L	8306655
BULK	_

PRODUCTCODE 2308

EXTENDTECH 80W140 GL 5

This is an extreme-pressure lubricant for gear boxes, specially formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

FEATURES

Easy gear shifting. Extended transmission life. Proven resistance to oil degradation.

SPECIFICATION LEVEL

API GL-5 MAN 342 M-2 ZF TE-ML 05A ZF TE-ML 12E ZF TE-ML 16D ZF TE-ML 19B

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307454
50L	8307652
205L	8307751
1000L	8307850
BULK	_

PRODUCTCODE 2311

EXTENDTECH 85W140 GL 5

This is an extreme-pressure lubricant for gear boxes, specially formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

FEATURES

Easy gear shifting. Long transmission life.

SPECIFICATION LEVEL

API GI -5 ZF TE-ML 05A ZF TE-ML 12E ZF TE-ML 16D ZF TE-ML 17B ZF TE-ML 19B

CONTENT PN CODE

250ML	_
500ML	_
1L	8304606
4L	_
5L	8304705
20L	8306853
60L	8307058
205L	8307157
1000L	8307256
BULK	_





EXTENDTECH



EXTENDTECH ATF DII

This is an oil with a high viscosity index for automatic transmissions. It is has a high chemical stability, increased anti-wear properties and an excellent resistance to ageing.

FEATURES

Extended transmission life.
Optimized thermal and oxidation stability.

SPECIFICATION LEVEL

ALLISON C4 FORD M2C-138CJ, Mercon GM 6137-M DEXRON II-D MAN 339 V1/Z1 MB 236.7 VOITH H55.6335xx

CONTENT PN CODE

250ML	_
500ML	_
1L	8305108
4L	_
5L	8305207
20L	8302268
60L	8302466
205L	8302565
1000L	8302664
BULK	_



GUARDTECH



GUARDTECH 80W GL 4

This is a gear oil for mechanical transmissions with moderate "extreme pressure" characteristics and is specifically developed to avoid corrosion of copper alloys.

FEATURES

Easy gear shifting. Long transmission life.

PRODUCTCODE 2201

SPECIFICATION LEVEL

API GL-4 MIL MIL-L-2105

250ML	_
500ML	_
1L	8303104
4L	_
5L	_
20L	8309649
60L	8309847
205L	8309946
10001	8300059

BULK

CONTENT PN CODE

wolf.

GUARDTECH 80W90 GL 4

This is a gear oil for mechanical transmissions with moderate "extreme pressure" characteristics and is specifically developed to avoid corrosion of copper alloys.

FEATURES

Easy gear shifting. Long transmission life. Proven resistance to oil degradation.

SPECIFICATION LEVEL

API GL-4 MIL MIL-L-2105

250ML	_	
500ML	_	
1L	_	
		ī

CONTENT PN CODE

4L — 5L — 20L 8301452 60L 8301650 205L 8301858 BULK —

PRODUCTCODE 2208

GUARDTECH 85W90 GL 4

This is a gear oil for mechanical transmissions with moderate "extreme pressure" characteristics and is specifically developed to avoid corrosion of copper alloys.

FEATURES

Long transmission life.

SPECIFICATION LEVEL

API GL-4 FORD WSD-M2C200-D GM 1940182 HONDA MTF 94 MB 235.10 PSA B71 2330

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8302657
60L	8302855
205L	8302954
1000L	8303050
BLILK	_



GUARDTECH 80W90 GL 1, GL 3

This is a lubricant for gearboxes and rear axles with conical teeth or screw type. This is made with highly refined base oils and anti-wear additives and an additive to lower the pour point.

FEATURES

Long transmission life.

PRODUCTCODE 2108

L 1, GL 3 SPECIFICATION LEVEL

API GL-1 API GL-3 VOLVO 97305

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8309045
60L	8309243
205L	8309342
1000L	8309441
BULK	_





GUARDTECH



GUARDTECH SAE 140 GL 1, GL 3

This is a lubricant for gearboxes and rear axles with conical teeth or screw type. This is made with highly refined base oils and anti-wear additives and an additive to lower the pour point.

FEATURES

Proven resistance to oil degradation.

PRODUCTCODE 2104

SPECIFICATION LEVEL

API GL-1 API GL-3

CONTENT PN CODE

250ML	_
500ML	_
1L	8303005
4L	_
5L	_
20L	8308444
60L	8308642
205L	8308741
1000L	8308840
BULK	_



GUARDTECH ATF F/G

ATF TYPE F/G oil has been specifically designed for the automatic FORD-transmissions (GLIDE). It has a very high viscosity index and low pour point, which ensure optimal performance in a broad temperature range.

FEATURES

Long transmission life. Optimized thermal and oxidation stability.

SPECIFICATION LEVEL

FORD ESW-M2C33-F FORD ESP-M2C33-G FORD SQM2-9007-AA JD JDM J21A VOLVO 97330

CONTENT PN CODE

250ML	_
500ML	_
1L	8305009
4L	_
5L	_
20L	8301667
60L	8301865
205L	8301964
1000L	8302060
BULK	_

PRODUCTCODE 3002

GUARDTECH

This is a high viscosity index oil for the first generation of General Motors automatic transmissions. Very good anti-wear, detergent qualities, anti-foam and anticorrosion.

FEATURES

Long transmission life. Optimized thermal and oxidation stability.

SPECIFICATION LEVEL

ALLISON C2/C3 ATF TYPE A SUFFIX A GM 6032-M DEXRON MB 236.2

CONTENT PN CODE

250ML	_
500ML	_
1L	8304903
4L	_
5L	_
20L	8301063
60L	8301261
205L	8301360
1000L	8301469
BULK	_

L.	_	
iL	_	
OL.	8301063	
OL.	8301261	
:05L	8301360	
000L	8301469	
BULK	_	



BRAKE FLUID DOT 5.1

Synthetic brake fluid, intended for hydraulic brake systems, where a superior quality is required. Its composition provides a high chemical stability, excellent resistance against residues, high resistance against oxidation and can be used with all materials, normally used in brake systems.

FEATURES

Very high boiling point, safe braking. Complete brake system protection. No leakage or fluid losses.

SPECIFICATION LEVEL

FMVSS 116 DOT 5.1 FMVSS 116 DOT3 FMVSS 116 DOT 4 ISO 4925 Class 3&4 ISO 4925 Class 5.1 SAE J 1704

CONTENT PN CODE

250ML	8308109
500ML	8308208
1L	8308307
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_



PRODUCTCODE 5075

BRAKE FLUID DOT 5.1

Synthetic brake fluid, intended for hydraulic brake systems, where a superior quality is required. Its composition provides a high chemical stability, excellent resistance against residues, high resistance against oxidation and can be used with all materials, normally used in brake systems.

FEATURES

Very high boiling point, safe braking. Complete brake system protection. No leakage or fluid losses.

SPECIFICATION LEVEL

FMVSS 116 DOT 5.1 FMVSS 116 DOT3 FMVSS 116 DOT 4 ISO 4925 Class 3&4 ISO 4925 Class 5.1 SAE J 1704

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8312441
60L	8312649
205L	8312748
1000L	8312847
BULK	_



BRAKE FLUID DOT 3&4

Brake fluid, intended for hydraulic brake systems. Its composition provides a high chemical stability, excellent resistance against residue formation, very good stability towards oxidation and is compatible with all materials present in the circuit.

FEATURES

High boiling point, safe braking. Complete brake system protection. No leakage or fluid losses.

SPECIFICATION LEVEL

FMVSS 116 DOT 4 FMVSS 116 DOT3 ISO 4925 Class 3&4 SAE J 1703 SAE J 1704

CONTENT PN CODE

250ML	8307607
500ML	8307706
1L	8307805
4L	_
5L	_
20L	_
50L	_
205L	_
1000L	_
BULK	_

PRODUCTCODE 5039

BRAKE FLUID



PRODUCTCODE 5015

Brake fluid, intended for hydraulic brake systems. Its composition provides a high chemical stability, excellent resistance against residue formation, very good stability towards oxidation and is compatible with all materials present in the circuit.

FEATURES

High boiling point, safe braking. Complete brake system protection. No leakage or fluid losses.

SPECIFICATION LEVEL

FMVSS 116 DOT 4 FMVSS 116 DOT3 ISO 4925 Class 3&4 SAE J 1703 SAE J 1704

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307690
60L	8307898
205L	8307997
1000L	8308093
BULK	_





MINERAL FLUID

This is a mineral hydraulic fluid for Peugeot and Citroen vehicles. It can be used until -40°C, has a high boiling temperature and is insensible to humidity. Not aggressive towards usual elastomers.

FEATURES

Excellent low temperature properties. No leakage or fluid losses. Complete brake system protection.

SPECIFICATION LEVEL

AFNOR NF E 48-602 HV AFNOR NF E 48-603 HV PSA B71 2710

CONTENT PN CODE

250ML	_
500ML	_
1L	8308406
4L	_
5L	_
20L	8313042
60L	8313240
205L	8313349
1000L	8313448
BULK	_



CENTRAL HYDRAULIC FLUID

Full synthetic hydraulic "multipurpose" fluid for all circuits and in a temperature range between -40°C and 130°C. It reduces friction-induced wear and the noise production of the hydraulic pump.

FEATURES

Excellent low temperature properties.

SPECIFICATION LEVEL

FORD WSS-M2C204-A MAN M3289 MB 345.0 OPEL GM 1940766 VOLVO 1161529-1 VW TL 521.46

CONTENT PN CODE

250ML	_
500ML	_
1L	8308505
4L	_
5L	_
20L	8313646
60L	8313844
205L	8313943
1000L	8314049
BULK	_



PRODUCTCODE 5078

LDS

Full synthetic hydraulic fluid for modern vehicles, e.g. Citroën. For extreme ambient temperatures and full performance from -40 °C to over 130 °C system temperature. Not compatible with LHM.

FEATURES

Complete system protection. Excellent temperature properties.

SPECIFICATION LEVEL

DIN 51524 T3 ISO 7308 PSA S71 2710

CONTENT PN CODE

250ML	_
500ML	_
1L	8300226
4L	_
5L	_
20L	8312687
60L	8312885
205L	8312984
1000L	8313080
BULK	_



ANTI-FREEZE LONGLIFE G13

An ethylene glycol/glycerine based antifreeze.It is nitrite, amine, phosphate and borate free and contains silicates. The Hybrid Organic Acid inhibitor (HOAT) offers permanent system protection.

FEATURES

Superior cold temperature performance. Outstanding corrosion protection. Excellent heat transfer and dispersion.

SPECIFICATION LEVEL

ASTM D3306 VW TL 774-J

CONTENT PN CODE

250ML	_
500ML	_
1L	8323584
4L	8323782
5L	_
20L	8323980
60L	8324086
205L	8324185
1000L	_
BULK	_



COOLANT -36°C LONGLIFE G13

An ethylene glycol/glycerine based coolant. It is nitrite, amine, phosphate and borate free and contains silicates. The Hybrid Organic Acid inhibitor (HOAT) offers permanent system protection.

FEATURES

Outstanding system protection. Extended service life.

SPECIFICATION LEVEL

ASTM D3306 VW TL 774-I

CONTENT PN CODE

250ML	_
500ML	_
1L	8327483
4L	8327582
5L	_
20L	8327681
60L	8327780
205L	8327889
1000L	_
BULK	_

PRODUCTCODE 50102

ANTI-FREEZE LONGLIFE G12+

An ethylene glycol based antifreeze. It is nitrite, amine, phosphate, borate and silicate free. It contains Organic Acid inhibitor Technology (OAT) offering permanent cooling system protection.

FEATURES

Superior cold temperature performance. Outstanding corrosion protection. Excellent heat transfer and dispersion.

SPECIFICATION LEVEL

ASTM D3306 ASTM D4985 MAN 324 SNF MB 325.3 SAE J1034 VW TL 774-F

CONTENT PN CODE

250ML	_
500ML	_
1L	8315985
4L	8316081
5L	_
20L	8311727
50L	8311826
205L	8310928
1000L	_
BULK	_

PRODUCTCODE 50001

COOLANT-36°C LONGLIFE G12+

An ethylene glycol based coolant.It is nitrite, amine, phosphate, borate and silicate free. It contains Organic Acid inhibitor (OAT) offering permanent cooling system protection.

FEATURES

Superior cold temperature performance. Outstanding corrosion protection. Excellent heat transfer and dispersion.

SPECIFICATION LEVEL

ASTM D3306 ASTM D4985 JD JDM H5 MAN 324 SNF MB 325.3 SAE J1034

CONTENT PN CODE

250ML	_
500ML	_
1L	8325885
4L	8325984
5L	_
20L	8326080
60L	8326189
205L	8326288
1000L	_
BULK	_





ANTI-FREEZE STANDARD G11

An ethylene glycol based antifreeze.It is nitrite, amine and phosphate free and includes borate and silicate. It contains Inorganic Acid inhibitor (IAT) offering permanent cooling system protection.

FEATURES

Very good low/high temperature performance. Adequate corrosion protection.

SPECIFICATION LEVEL

ASTM D3306 ASTM D4985 MAN 324 NF MB 325.0 SAE I1034 VW TL 774-C

CONTENT PN CODE

250ML	_
500ML	_
1L	8325083
4L	8325182
5L	_
20L	8325281
60L	8325380
205L	8325489
1000L	_
BULK	_



PRODUCTCODE 50100

COOLANT -36°C STANDARD G11

An ethylene glycol based coolant. It is nitrite, amine and phosphate free and includes borate and silicate.It contains Inorganic Acid inhibitor (IAT) offering permanent cooling system protection.

FEATURES

Very good low/high temperature performance. Adequate corrosion protection.

WINDSCREEN CONCENTRATE

SPECIFICATION LEVEL

ASTM D3306 ASTM D4985 GM B 0400240 MAN 324 NF MB 325.0 SAE J1034 VW TL 774-C

CONTENT PN CODE

250ML	_
500ML	_
1L	8326684
4L	8326783
5L	_
20L	8326882
60L	8326981
205L	8327087
1000L	_
BULK	_



An undiluted powerful windscreen washer antifreeze concentrate that can be used during the whole year with frost protection at your choice once diluted with water.

FEATURES

Efficient cleaning. Protects against freezing Nice odour

SPECIFICATION LEVEL

CONTENT	PN CODE
250ML	8322389
500ML	_
1L	8322785
4L	8322983
5L	_
20L	8323188
60L	_
205L	8323386
1000L	_
BULK	_

PRODUCTCODE 50200

WINDSCREEN -22°C **READY TO USE**

An undiluted powerful windscreen washer antifreeze concentrate that can be used during the whole year with frost protection at your choice once diluted with water.

FEATURES

Nice odour. Efficient cleaning. Protects against freezing.

SPECIFICATION LEVEL

250ML 500ML 8324383 1L 4L 8324482 5L 201 8324789 60L 205L 1000L BULK

CONTENT PN CODE



WINDSCREEN WASHER SUMMER READY TO USE SP

SPECIFICATION LEVEL

A powerful windscreen washer ready to use that can be used whith outside temperatures not below 0 °C. Special formula with anti-insect action, which is indispensable in summer period.

FEATURES

Efficient cleaning. Nice odour.

PRODUCTCODE 50220

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	8324888
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_





SPECIFICATION LEVEL

//

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BI II K	_

FEATURES

PRODUCTCODE 55571



PRODUCTCODE 70310

GASOLINE TREATMENT

Cleans the complete fuel system including valves, dirty carburettors and clogged injectors. Restores power and performance.

FEATURES

Superior cleaning of the fuel system. Gasoline consumption reduction. Combustion improvement.

SPECIFICATION LEVEL

//

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

LEAD SUBSTITUTE

Protects valves and valve seats and reduces loss of compression of engines which require leaded fuel. Eliminates valve sticking, reduces maintenance cost and increases engine lifetime.

FEATURES

Reduces wear and prolonges engine life.

PRODUCTCODE 70301

SPECIFICATION LEVEL

CONTENT	PN CODE
250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

DIESEL TREATMENT

Cleans the complete fuel system, increases cetane number and restores power and performance. Improves combustion and reduces fuel consumption. Lubricates the diesel pump in case of low sulphur fuel.

FEATURES

Superior cleaning action. Combustion improvement. Fuel consumption reduction.

SPECIFICATION LEVEL

7/

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8330735
60L	8330834
205L	8330933
1000L	_
BULK	_





DIESEL PARTICULATE FILTER CLEANER

This product is an organo-metallic diesel fuel additive to be used as a catalyst for the regeneration of diesel particulate filters.

FEATURES

Regenerates the DPF and extends its life. Prevents performance loss. Optimizes combustion.

SPECIFICATION LEVEL

7/

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

LPG TREATMENT

This product has been developed to clean and protect valves, valve seats and clogged injectors. It protects and stabilizes fuel during prolonged storage. Prevents rust and keeps fuel system clean.

FEATURES

Superior cleaning of the fuel system.

PRODUCTCODE 70304

SPECIFICATION LEVEL

CONTENT	PN CODE
250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

PRODUCTCODE 70313

ENGINE FLUSH

Completely cleans the engine interior by eliminating sludge, gum, rust and varnish. Removes carbon deposits, soot, water and unburnt fuel. Reduces fuel consumption and exhaust emissions.

FEATURES

Complete removal of impurities in the engine. Fuel consumption reduction. Exhaust emission reduction.

SPECIFICATION LEVEL

7 /

CONTENT PN CODE 250ML —

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

OIL LEAK STOP

This product prevents and stops oil leakage through the seals. It makes seals swell back to their original size and regain pliability.

FEATURES

Reduction of oil leakage. Improving the viscosity of the motor oil. Enhancing motor compression.

SPECIFICATION LEVEL

//

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
50L	_
205L	_
1000L	_
BULK	_





RADIATOR CLEANER

This product has been developed to clean the entire cooling system and to improve the heat transfer from the engine to the cooling system.

FEATURES

Complete removal of all deposits. Removing sludge, rust and scale. Preventing overheating.

SPECIFICATION LEVEL

7.7

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_



PRODUCTCODE 70316

RADIATOR SEALER & CONDITIONER

This product seals and permanently prevents hair cracks and leakages in the radiator, the water pump, the cylinder head gasket and the engine block.

FEATURES

Complete cooling system protection. Protecting the entire cooling system. Lubricating the water pump.

SPECIFICATION LEVEL

//

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

COLDCLEANER



This is a solvent and cleaning product, based on an aliphatic solvent, emulsifiers and tensio-actives. It is emulsifiable with water and suitable for the removal of oily, greasy and asphalt pollutions.

FEATURES

Efficient removal of oily contaminants.

SPECIFICATION LEVEL

ISO 6743/10

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307096
60L	8307294
205L	8307393
1000L	8307492
BULK	_



RACING 4T 5W50 ESTER

This is a full synthetic oil for 4-stroke engines, used in severe circumstances. It offers an exceptional lubricating power, reduces friction and wear and extends the life of your motorcycle.

FEATURES

Outstanding engine cleanliness and durability. Superior protection. Very high stability.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8305313
4L	8305412
5L	_
20L	8318269
60L	8318467
205L	8318566
1000L	8318665
BULK	_



RACING 4T 15W50 ESTER

This is a full synthetic oil for 4-stroke engines, designed for competition (circuit, cross, enduro, quads). It reduces friction and wear and extends the performance and lifetime of your motorcycle.

FEATURES

Outstanding engine cleanliness and durability. Superior protection. Very high stability.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8305115
4L	8305214
5L	_
20L	8317668
50L	8317866
205L	8317965
1000L	8318061
BULK	_



RACING 4T 20W50

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is for 4-stroke engines for normal and intensive use.

FEATURES

Engine protection and cleanliness. Anti-wear and oxidation stability.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8307119
4L	8307218
5L	_
20L	8315473
50L	8315671
205L	8315770
1000L	8315879
BULK	_

PRODUCTCODE 29447

CHRONO 4T 10W30

Full synthetic lubricant for 4-stroke engines. Based on an enforced formula with extreme pressure additives avoiding slipping of the wet clutches. Optimum protection and longer lifetime of the engine.

FEATURES

Outstanding engine cleanliness and durability. Superior protection.
Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8335419
4L	8335617
5L	_
20L	8336010
50L	8336119
205L	8336218
1000L	8335815
BULK	_





CHRONO 4T 10W40

Semi synthetic oil for 4-stroke engines for normal and intensive use. Enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the clutches.

FEATURES

Outstanding engine cleanliness and durability. Superior protection.
Superior viscosity stability.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8305719
4L	8305818
5L	_
20L	8319464
60L	8319662
205L	8319761
1000L	8319860
BULK	_



CHRONO 4T 10W50

Semi synthetic oil for 4-stroke engines for normal and intensive use. Enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the clutches.

FEATURES

Outstanding engine cleanliness and durability. Superior protection. Superior viscosity stability.

SPECIFICATION LEVEL

API SL JASO MA2 JASO MA

CONTENT PN CODE

250ML	_
500ML	_
1L	8305511
4L	8305610
5L	_
20L	8318863
60L	8319068
205L	8319167
1000L	8319266
BULK	_

PRODUCTCODE 29184

CHRONO 4T 10W60

Semi synthetic oil for 4-stroke engines for demanding circumstances like racing or hot climates. Enhanced formula with extreme pressure additives for gearboxes.

FEATURES

Outstanding engine cleanliness and durability. Superior protection of critical parts. Superior viscosity stability.

SPECIFICATION LEVEL

API SL JASO MA IASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8306419
4L	8306518
5L	_
20L	8311871
60L	8312076
205L	8312175
1000L	8312274
BULK	_

PRODUCTCODE 29189

CHRONO 4T 15W50

Semi synthetic oil for 4-stroke engines for normal and intensive use. Enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the clutches.

FEATURES

Outstanding engine cleanliness and durability. Superior protection. Superior viscosity stability.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8305917
4L	8306013
5L	_
20L	8310072
60L	8310270
205L	8310379
1000L	8310478
BULK	_

PRODUCTCODE 29186

51



V TWIN 4T 20W50

This high quality mineral motorcycle oil has been exclusively developed and tested for V-Twin engines (e.g. Harley Davidson).

SPECIFICATION LEVEL

API SG/CD JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8304910
4L	8305016
5L	_
20L	8317064
60L	8317262
205L	8317361
1000L	8317460
RI II K	

Ac

FEATURES

Excellent engine performance. Adequate protection of systems.

PRODUCTCODE 29147

PRO SCOOTER 4T 5W40

This is a full synthetic oil for 4-stroke engines, used in severe circumstances. It offers an exceptional lubricating power, reduces friction and wear and extends the life of your motorcycle.

FEATURES

Outstanding engine cleanliness and durability. Superior protection. Very high temperatur stability.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8306112
4L	8306211
5L	_
20L	8310676
60L	8310874
205L	8310973
1000L	8311079
BULK	_

PRODUCTCODE 29187

FUN 4T 15W40

High quality multigrade engine oil for daily use in small 4-stroke engines. It is adapted for integrated gear boxes and is suitable for smaller 4-stroke engines for normal use.

FEATURES

Excellent engine performance. Adequate protection of systems.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8306310
4L	_
5L	_
20L	8311277
50L	8311475
205L	8311574
1000L	8311673
BULK	_

PRODUCTCODE 29188

FUN 4T 20W40

Mineral 4-stroke oil ensuring your engine to deliver high power and torque, improving control and comfort. It provides advanced control with smoother gear changes of the integrated gear box.

FEATURES

Excellent engine performance.
Adequate protection of systems;

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8330421
4L	_
5L	_
20L	8330827
50L	8330926
205L	8331022
1000L	8330629
RIII K	_









RACING

Full synthetic high quality 2-stroke motor oil for competition engines with lubrication by mixing. High lubrication capacity and reduced wear. May also be used with high octane fuel.

FEATURES

Outstanding engine cleanliness and durability. Superior protection of critical parts.

SPECIFICATION LEVEL

API TC ISO L-EGB JASO FB

CONTENT PN CODE

250ML	_
500ML	_
1L	8306617
4L	_
5L	_
20L	8312472
60L	8312670
205L	8312779
1000L	8312878
BULK	_

PRODUCTCODE 29193

CHRONO

Full synthetic 2-stroke engine oil with smoke-reducing action. Used in mixed lubrication or with oil injection. This oil reduces friction and wear and is specifically suited for fast performance.

FEATURES

Outstanding engine cleanliness and durability. Excellent smoke reduction. Adequate corrosion protection.

SPECIFICATION LEVEL

API TC ISO L-EGD JASO FC JASO FD

CONTENT PN CODE 250MI

ZJUIVIL	
500ML	_
1L	8306716
4L	_
5L	_
20L	8313073
60L	8313271
205L	8313370
1000L	8313479
BULK	_

PRODUCTCODE 29195

SCOOTER

This semi synthetic oil is intended for 2-stroke gasoline engines for start-stop circumstances in city traffic. Optimum protection against wear. Reduced formation of smoke.

FEATURES

Excellent engine performance. Excellent smoke reduction. Adequate corrosion protection.

SPECIFICATION LEVEL

API TC ISO L-EGD IASO FC JASO FD

CONTENT PN CODE

250ML	_
500ML	_
1L	8306815
4L	_
5L	_
20L	8313677
60L	8313875
205L	8313974
1000L	8314070
BULK	_

PRODUCTCODE 29198

FUN

This oil is suitable for all air cooled 2-stroke gasoline engines. Can be used in mixed lubrication and with oil injection. It offers protection of the pistons and rings against overheating and deposits.

FEATURES

Excellent engine performance. Adequate corrosion protection.

SPECIFICATION LEVEL

API TC

CONTENT PN CODE

250ML	_
500ML	_
1L	8302206
4L	_
5L	_
20L	8304842
60L	8305047
205L	8305146
1000L	8305245
BULK	_

PRODUCTCODE 1918

53



SNOW SCOOTER 4T 0W40 ESTER

A full synthetic ester-based engine oil for 4-stroke snowmobiles. It assures maximum power output, reducing wear and extending the life of the engine.

FEATURES

Performance in keeping the engine clean. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

API SL JASO MA JASO MA2

CONTENT PN CODE

250ML	_
500ML	_
1L	8317125
4L	8317224
5L	_
20L	8317323
60L	8317422
205L	8317521
1000L	8317620
BULK	_



SNOW SCOOTER 2T TC-W3 EXTRA

A prediluted semi synthetic 2 stroke motor oil for snowscooters. The ester components ensure a strong lubricating film and an excellent protection at high operating temperatures and heavy loading.

FEATURES

Outstanding engine cleanliness and durability. Excellent smoke reduction. Adequate corrosion protection.

SPECIFICATION LEVEL

API TC JASO FC NMMA TC-W3

CONTENT PN CODE

250ML	_
500ML	_
1L	8316227
4L	8316326
5L	_
20L	8316425
60L	8316524
205L	8316623
1000L	8316722
BULK	_



SNOW SCOOTER 2T TC-W3

A mineral 2 stroke motor oil, developed for use in snowscooters. Its ashless composition prevents the formation of deposit, pre-ignition and spark plug fouling. High protection against rust.

FEATURES

Outstanding engine cleanliness and durability.
Adequate corrosion protection.

SPECIFICATION LEVEL

NMMA TC-W3

CONTENT PN CODE

250ML	_
500ML	_
1L	8318290
¥L	8318399
5L	_
20L	8318498
50L	8318597
205L	_
1000L	8318795
BULK	_

PRODUCTCODE 1917

MOTOGEAR 75W90 GL 5

Semi synthetic transmission oil with exceptionally high viscosity index. It exhibits excellent fluidity at low temperatures and ensures extended life of the oil and gears.

FEATURES

Smooth shift performance. Long transmission life. Proven resistance to oil degradation.

SPECIFICATION LEVEL

API GL-5

CONTENT PN CODE

250ML	_
500ML	_
1L	8306914
4L	_
5L	_
20L	8314278
50L	8314476
205L	8314575
1000L	8314674
BULK	_









MOTOGEAR 80W90 GL 5

This is an extreme pressure lubricant for gear boxes, specifically formulated to satisfy the most demanding service conditions: high speed, shockloads, and high torque at low speeds.

FEATURES

Easy gear shifting. Long transmission life.

PRODUCTCODE 29308

SPECIFICATION LEVEL

API GL-5

CONTENT PN CODE

250ML	_
500ML	_
1L	8307010
4L	_
5L	_
20L	8314872
60L	8315077
205L	8315176
1000L	8315275
BULK	_



TRANSLUBE 10W30 80W

Specific lubricant for gearboxes of motorcycles with 2-stroke engine with integrated clutch. It ensures easy gear shifting and controls the slipping characteristics of the clutch for smooth driving.

FEATURES

Good EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

API GL-3

CONTENT PN CODE

250ML	_
500ML	_
1L	8302800
4L	_
5L	_
20L	8306648
60L	8306846
205L	8306945
1000L	8307041
BULK	_

PRODUCTCODE 2001

FORK OIL 5W

This fork oil provides optimal dampening control over a wide temperature range. Its excellent anti-corrosion, low foaming, and anti-wear properties will contribute to long service life.

FEATURES

Superior viscosity stability. Excellent ant-foam properties.

SPECIFICATION LEVEL

DIN 51524 Part 3

CONTENT PN CODE

250ML	_
500ML	8306600
1L	_
4L	_
5L	_
20L	8303494
60L	8303692
205L	8303791
1000L	8303890
BULK	_

PRODUCTCODE 4655

FORK OIL

This fork oil will provide optimal dampening control over a wide temperature range. Its excellent anti-corrosion, low foaming, and anti-wear properties will contribute to long service life.


FEATURES

Superior viscosity stability. excellent anti-foam properties.

SPECIFICATION LEVEL

DIN 51524 Part 3

CONTENT PN CODE 250ML —





55



FORK OIL 15W

This fork oil provides optimal dampening control over a wide temperature range. Its excellent anti-corrosion, low foaming, and anti-wear properties will contribute to long service life.

FEATURES

Superior viscosity stability. Excellent anti-foam properties.

PRODUCTCODE 4657

SPECIFICATION LEVEL

DIN 51524 Part 3

COM	IFNI	ЫN	CODE

_
8306808
_
_
_
8304699
8304897
8304996
8305092
_

FORK OIL

This fork oil provides optimal dampening control over a wide temperature range. Its excellent anti-corrosion, low foaming, and anti-wear properties will contribute to long service life.

FEATURES

Superior viscosity stability. Excellent anti-foam properties.

SPECIFICATION LEVEL

DIN 51524 Part 3

CONTENT PN CODE

250ML	_
500ML	8306907
1L	_
4L	_
5L	_
20L	8305290
60L	8305498
205L	8305597
1000L	8305696
BULK	_

PRODUCTCODE 4658

CHAIN LUBE



High quality product based on mineral oil, solvents and a dye. It is a sticky and water repellent lubricant with great penetrating capacity. A thin film protects the chain against wear and rust. The product penetrates and lubricates and is completely harmless to O-rings.

FEATURES

Strong adhesive power.
Adequate protection of systems.

SPECIFICATION LEVEL

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	_	
60L	_	
205L	_	
1000L	_	
BULK	_	

PRODUCTCODE 55504

BRAKE CLEANER



This product removes all stains from drum and disc brakes, as well as oil, tar and grease from linings, shoes, cylinders.

FEATURES

Excellent cleaning capacities.
Efficient protection against corrosion.

SPECIFICATION LEVEL

CONTENT PN CODE

CONTLINE	FIN CODE
250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_







SILICONE CLEAN

This product polishes and revives the colours of plastic and varnish: fairing, seat, dashboard, wheels, mudguards.

FEATURES

Excellent polishing and shine.

PRODUCTCODE 55544

SPECIFICATION LEVEL

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

MULTISPRAY



This is a high-quality lubricant based on mineral oils and PTFE. Resistant to seawater and applicable in a broad temperature range: -50°C and 250°C.

FEATURES

Adequate protection of systems. Excellent lubricating capacities.

SPECIFICATION LEVEL

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_



OUTBOARD 4T 10W30

This is a semi synthetic 4-stroke motor oil, which meets the requirements of NMMA FC-W. It contains molybdenum/zinc technology anti-wear package and provides strong protection against corrosion.

FEATURES

Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

API SJ API SL NMMA FC-W

CONTENT PN CODE

250ML	_
500ML	_
1L	8302305
4L	8302404
5L	_
20L	8305443
60L	8305641
205L	8305740
1000L	8305849
BULK	_

PRODUCTCODE 1925

IN-OUTBOARD 4T 25W40

This is a semi-synthetic 4-stroke motor oil, which meets the requirements of NMMA FC-W. It contains molybdenum/zinc technology anti-wear package and provides strong protection against corrosion.

FEATURES

Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

API SJ API SL NMMA FC-W

CONTENT PN CODE

250ML	_
500ML	_
1L	8302503
4L	8302602
5L	_
20L	8306044
50L	8306242
205L	8306341
1000L	8306440
BULK	_

PRODUCTCODE 1956

OUTBOARD 2T TC-W3

This is an oil for water-cooled 2-stroke outboard engines meeting the NMMA-TC-W3. Its ashless composition prevents the formation of deposits, pre-ignition and spark plug fouling.

FEATURES

Outstanding engine cleanliness and durability.

Adequate corrosion protection.

SPECIFICATION LEVEL

NMMA TC-W3

CONTENT PN CODE

250ML	_
500ML	_
1L	8302008
4L	8316029
5L	_
20L	8303647
50L	8303845
205L	8303944
1000L	8304040
BULK	_

PRODUCTCODE 1912

UNIVERSAL 2T BIO

Full synthetic oil for water-cooled 2-stroke gasoline engines. Can also be used for air-cooled engines. Biodegradable, universally applicable and easily miscible with gasoline.

FEATURES

Outstanding engine cleanliness and durability.
Quick biological decomposition.

SPECIFICATION LEVEL

API TC+ CEC L-33-T-82 NMMA TC-W3

CONTENT PN CODE

250ML	_
500ML	_
1L	8302107
4L	_
5L	_
20L	8304248
50L	8304446
205L	8304545
1000L	8304644
RHK	_









S.T.O.U. 10W30

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

FEATURES

Excellent fluidity at low temperature. Proven protection of critical parts.

SPECIFICATION LEVEL

ALLISON C4 (Agriculture applic.) API CG-4 API GL-4 FORD ESN-M2C-159B/C JD J27 MF M 1145

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8306433
60L	8306631
205L	8306730
1000L	8306839
BULK	_



S.T.O.U. 10W40

This is a semi synthetic lubricant based on carefully selected highly refined base oils for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

FEATURES

Proven protection of critical parts. Excellent fluidity at low temperature.

SPECIFICATION LEVEL

ALLISON C4 (Agriculture applic.) API GL-4 API CG-4 FORD ESN-M2C-159B/C JD J27 MF Approval M 1145

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307034
60L	8307232
205L	8307331
1000L	8307430
BULK	_



S.T.O.U. 15W30

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

FEATURES

Proven protection of critical parts.

SPECIFICATION LEVEL

ALLISON C4 (Agriculture applic.) API CG-4 API GL-4 FORD ESN-M2C-159B/C JD J27 MF M 1145

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307638
60L	8307836
205L	8307935
1000L	8308031
BULK	_



S.T.O.U. 15W40

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

FEATURES

Proven protection of critical parts.

PRODUCTCODE 1436

SPECIFICATION LEVEL

ALLISON C4 (Agriculture applic.)
API CG-4
API GL-4
FORD ESN-M2C-159B/C
JD J27
MF M 1145

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8308239
60L	8308437
205L	8308536
1000L	8308635
BULK	_



S.T.O.U. 20W40

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

FEATURES

Proven protection of critical parts.

PRODUCTCODE 1446

SPECIFICATION LEVEL

ALLISON C4 ALLISON C4 (Agriculture applic.) API CG-4 API GL-4 FORD ESN-M2C-159B/C JD J27 MF M 1145

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8308833	
60L	8309038	
205L	8309137	
1000L	8309236	
BI II K	_	

TRACTOFLUID 50



Full synthetic oil for outstanding performance of wet brakes in a wide range of temperatures under all operating conditions. It protects against wear and reduce friction, and also prevent brake noise.

FEATURES

Reliable protection of all parts.

PRODUCTCODE 3119

SPECIFICATION LEVEL

API GL-4 API GL-4 FORD ESN-M2C134 D MF M 1145 VOLVO 97304 VOLVO WB-102

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8323119
60L	8324772
205L	8324475
1000L	8324697
RIII K	_

TRACTOFLUID 100



Special oil for automatic transmissions, hydraulic systems and brakes of tractors, forklifts and off-road equipment. This Universal Tractor Transmission Oil (UTTO) should never be used for the engine.

FEATURES

Reliable protection of all parts.

SPECIFICATION LEVEL

API GL-4 CASE IH HY-TRAN B6 CASE IH HY-TRAN PLUS FORD ESN-M2C-41 A/B MF M 1110 MF M 1141

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8306464
60L	8306662
205L	8306761
1000L	8306860
BULK	_

PRODUCTCODE 3120

TRACTOFLUID 170



Special oil for automatic transmissions, hydraulic systems and brakes of tractors, forklifts and off-road equipment. This Universal Tractor Transmission Oil (UTTO) should never be used for the engine.

FEATURES

Reliable protection of all parts.

SPECIFICATION LEVEL

ALLISON C3/C4 API GL 4 FORD ESN-M2C-134 C/D FORD ESN-M2C-86 C JD J20 C/D MF M 1143

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307065
60L	8307263
205L	8307362
1000L	8307461
BULK	_







TRACTOFLUID 170 BM

Special oil intended for automatic transmissions, hydraulic systems, wet brakes, convertors for tractors, forklifts and different off-highway equipment.

FEATURES

Superior protection of critical parts. Excellent fluidity at low temperature.

SPECIFICATION LEVEL


ALLISON C4 API GL 4 FORD ESN-M2C-134 C/D JD J20 C/D MF M 1145 VOLVO WB-101

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8328664
20L	8312267
60L	8312465
205L	8312564
1000L	8312663
BI II K	_

PRODUCTCODE 23121

TRACTOFLUID 400



FEATURES

Reliable protection of all parts.

SPECIFICATION LEVEL

ALLISON C3/C4 API GL 4 CASE MS1205 CASE MS1206 FORD ESN-M2C-86 A/B MF M 1135

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307669
60L	8307867
205L	8307966
1000L	8308062
BULK	_

PRODUCTCODE 3122

TRACTOFLUID 500



This is a lubricant, specifically formulated to meet the requirements of the Caterpillar transmissions, final drives and wet brakes (Cat TDTO).

FEATURES

Good fluidity at low temperature. Proven protection of critical parts.

SPECIFICATION LEVEL

ALLISON C4 CATERPILLAR TO-4 ISO 100 KOMATSU KES 07.868.1

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8308260
60L	8308468
205L	8308567
1000L	8308666
BULK	_

PRODUCTCODE 3123

TRACTOFLUID 600



This is a lubricant, which is specifically formulated to satisfy the requirements of Caterpillar for use in transmissions, final drives and wet brakes (Cat TDTO).

FEATURES

Good fluidity at low temperature. Proven protection of critical parts.

SPECIFICATION LEVEL

ALLISON C4 CATERPILLAR TO-4 ISO 220 KOMATSU KES 07.868.1 SAE 50

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8317880
60L	8318085
205L	8318184
1000L	8318283
BULK	_



SUPER CPO 10W40

Semi synthetic oil for use in public works. It meets the specifications of most manufacturers, both in terms of engine and gear oils. Its high viscosity index allows the use in all weather conditions.

FEATURES

Outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

API CG-4 API GL 5 (Low speed/high torque) EATON VICKERS I-280-S FORD ESN-M2C-159B/C JD J27 MF M 1145

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8300646
60L	8300844
205L	8300943
1000L	8301049
BULK	_

4T Is a lo

AGRIFLOW 4T 10W30

Is a low viscosity engine oil for gasoline or diesel engines. It combines a good fluidity at low temperature with a low ash content, while maintaining excellent detergent and dispersant properties.

FEATURES

Good engine protection and cleanliness. Adequate viscosity stability.

SPECIFICATION LEVEL

ACEA A2 ACEA B2 API SJ/CF JASO MA

CONTENT PN CODE

250ML	_
500ML	_
1L	8309106
4L	_
5L	_
20L	8318443
60L	8318641
205L	8318740
1000L	8318849
BULK	_

PRODUCTCODE 13125

AGRIFLOW 4T 15W40

This engine oil is specifically adapted for the lubrication of modern 4-stroke gasoline engines. The special composition ensures excellent protection against dirt and deposits.

FEATURES

Performance in keeping the engine clean.

SPECIFICATION LEVEL

ACEA E2-level ACEA A3/B4-98 API CF API CF-4 API SJ

CONTENT PN CODE

250ML	_
500ML	_
1L	8301308
4L	_
5L	_
20L	8305832
50L	8306037
205L	8306136
1000L	8306235
BULK	_

PRODUCTCODE 1406

AGRIFLOW 4T SAE 30 SI

This is an engine oil, specifically designed for the lubrication of modern 4-stroke gasoline engines. The special composition ensures excellent protection against dirt and deposits.

FEATURES

Engine protection and cleanliness.

PRODUCTCODE 1503

SPECIFICATION LEVEL

API SJ/CD JASO MA

CONTENT	PN CODE
250ML	_
500ML	_
1L	8301407
4L	_
5L	8301506
20L	8309434
60L	8309632
205L	8309731
1000L	8309830
DLILIZ	







SYNTH 2T

Full synthetic lubricant for air cooled 2-stroke gasoline engines, with mixed or separate lubrication. It assures a remarkable cleanliness of the engine, and has high thermal stability.

FEATURES

Outstanding engine cleanliness and durability. Adequate corrosion protection. Excellent smoke reduction.

SPECIFICATION LEVEL

APITC ISO L-EGD JASO FC JASO FD

CONTENT PN CODE

250ML	_
500ML	_
1L	8301704
4L	_
5L	_
20L	8301841
60L	8302046
205L	8302145
1000L	8302244
BULK	_

PRODUCTCODE 1905

SEMI-SYNT

Semi synthetic prediluted oil for the lubrication of 2-stroke gasoline engines with high specific power. It combines high lubricity and thermal stability. Easily miscible with gasoline.

FEATURES

Excellent engine performance. Adequate corrosion protection. Smoke reduction.

SPECIFICATION LEVEL

APITC ISO L-EGB JASO FB

CONTENT PN CODE

250ML	_
500ML	_
1L	8301803
4L	_
5L	_
20L	8302442
60L	8302640
205L	8302749
1000L	8302848
BULK	_

PRODUCTCODE 1908

UNIVERSAL

7T

Oil for air-cooled 2-stroke gasoline engines. Suitable for machines where the reservoir is filled with a mixture of gasoline and oil, and for those with separate reservoirs.

FEATURES

Excellent engine performance. Adequate corrosion protection.

SPECIFICATION LEVEL

APLTC

CONTENT PN CODE

5L — 20L 8301247 60L 8301445 205L 8301544 1000L — BULK —

PRODUCTCODE 1900

AGRIFLOW 2T



A semi synthetic lubricant with a high lubricating power, a minimum of deposits and a very high thermal stability. Prediluted for ease of use. Reduces exhaust smoke formation.

FEATURES

Excellent engine performance. Excellent smoke reduction. Adequate corrosion protection.

SPECIFICATION LEVEL

API TC ISO L-EGD JASO FC JASO FD

CONTENT PN CODE

250ML	_
500ML	_
1L	8327872
4L	_
5L	_
20L	8328176
60L	8328275
205L	8328374
1000L	8328077
BULK	_



AGRIFLOW CHAIN SAW

This is a strongly adhesive oil based on mineral oils and an adhesion improver. It was specifically developed for the lubrication of chainsaws, where high demands are made. Warning: never use in the engine.

FEATURES

Strong adhesive power.

PRODUCTCODE 29081

SPECIFICATION LEVEL

ISO 6743/1

CONTENT PN CODE

250ML	_
500ML	_
1L	8304712
4L	_
5L	8304811
20L	8316463
60L	8316661
205L	8316760
1000L	8316869
BULK	_



AGRIFLOW BIOCHAIN

This is a biodegradable oil, based on vegetable oils and toxicologically neutral components. It has an exceptional viscosity/temperature relation and strong adhesive power for this type of product.

FEATURES

Vegetable oil, quick decomposition. Strong adhesive power.

SPECIFICATION LEVEL

CEC L-33-T-82 ISO 68

CONTENT PN CODE

250ML	_
500ML	_
IL	8308703
+L	_
5L	8308802
20L	8315442
50L	8315640
205L	8315749
1000L	8315848
RI II K	_





SPECIFICATION LEVEL

DIN 51524 T3 HVLPD ISO 6743-4 CLASS L-HV HV-LP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

FEATURES

PRODUCTCODE 4426



PRODUCTCODE 4000

AROW ISO 5

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8308864	
60L	8309069	
205L	8309168	
1000L	8309267	
BULK	_	

AROW ISO 10

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8309465
60L	8309663
205L	8309762
1000L	8309861
BULK	_

PRODUCTCODE 4001

AROW ISO 15

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8300073
60L	8300271
205L	8300370
1000L	8300479
BULK	_

PRODUCTCODE 4002

65



AROW ISO 22

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8300677
60L	8300875
205L	8300974
1000L	8301070
BULK	_



PRODUCTCODE 4005

AROW ISO 32

A mineral oil, specificaly designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8320682
20L	8301278
60L	8301476
205L	8301575
1000L	8301674
BULK	_



PRODUCTCODE 4006

AROW ISO 46

A mineral oil specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	8306105
4L	_
5L	8306204
20L	8301872
60L	8302077
205L	8302176
1000L	8302275
BULK	_

AROW ISO 68

A mineral oil specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	8328367
20L	8302473
60L	8302671
205L	8302770
1000L	8302879
BULK	_





AROW ISO 100

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8303074
60L	8303272
205L	8303371
1000L	8303470
BULK	_



PRODUCTCODE 4009

AROW ISO 150

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8303678
60L	8303876
205L	8303975
1000L	8304071
BULK	_



A mineral oil, specifially designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8304279
60L	8304477
205L	8304576
1000L	8304675
BULK	_

PRODUCTCODE 4010

AROW ISO 320

A mineral oil, specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anticorrosion and anti-foam additives.

FEATURES

Superior protection. Excellent anti-foam properties. Adequate viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DENISON HF-2 DIN 51524 Part 2 EATON VICKERS I-286-S ISO 11158, HM ISO 6743-4, HM

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8304873
60L	8305078
205L	8305177
1000L	8305276
BULK	_



67



AROW SAE 10W

Detergent hydraulic oil significantly reducing, due to its dispersant properties, deposits and sludge formation. Its high zinc content ensures excellent antiwear and anti-oxidation characteristics.

FEATURES

Superior protection. Excellent anti-foam properties.

SPECIFICATION LEVEL

ALLISON C3 API CD/SF API CE

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8315398
60L	8315497
205L	8315596
1000L	8315695
BULK	_



AROW HV

A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean.

FEATURES

Superior protection. Excellent anti-foam properties. Superior viscosity stability.

SPECIFICATION LEVEL

AFNOR 48-603 HV DENISON HF-2 DIN 51524 Part 3 EATON VICKERS I-286-S ISO 11158, HV ISO 6743-4, HV

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8303883
60L	8304088
205L	8304187
1000L	8304286
BUI K	_

PRODUCTCODE 4403

AROW HV ISO 22

A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean.

FEATURES

Superior protection. Excellent anti-foam properties. Superior viscosity stability.

SPECIFICATION LEVEL

AFNOR 48-603 HV DENISON HF-2 DIN 51524 Part 3 EATON VICKERS I-286-S ISO 11158, HV ISO 6743-4, HV

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8304484
60L	8304682
205L	8304781
1000L	8304880
BULK	_

PRODUCTCODE 4404

AROW HV ISO 32

A high viscosity index paraffinic oil, based on selected ingredients, especially intended for use in hydraulic circuits. Superior performance in keeping the system clean.

FEATURES

Superior protection. Excellent anti-foam properties. Superior viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HV DENISON HF-2 DIN 51524 Part 3 EATON VICKERS I-286-S ISO 11158, HV ISO 6743-4, HV

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8305085
60L	8305283
205L	8305382
1000L	8305481
BULK	_





AROW HV ISO 46

A high viscosity index paraffinic oil for hydraulic circuits. Superior performance in keeping the system clean. It has good filterability, water separation, and quick air release characteristics.

FEATURES

Superior protection. Excellent anti-foam properties. Superior viscosity stability.

SPECIFICATION LEVEL

AFNOR 48-603 HV DENISON HF-2 DIN 51524 Part 3 EATON VICKERS I-286-S ISO 11158, HV ISO 6743-4, HV

CONTENT PN CODE

250ML	_
500ML	_
1L	8306303
4L	_
5L	8306402
20L	8305689
60L	8305887
205L	8305986
1000L	8306082
BULK	_



PRODUCTCODE 4407

AROW HV

A high viscosity index paraffinic oil for hydraulic circuits. Superior performance in keeping the system clean. It has good filterability, water separation, and quick air release characteristics.

FEATURES

Superior protection. Excellent anti-foam properties. Superior viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HV DENISON HF-2 DIN 51524 Part 3 EATON VICKERS I-286-S ISO 11158, HV ISO 6743-4, HV

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8306280
60L	8306488
205L	8306587
1000L	8306686
BULK	_

AROW HV ISO 100

A high viscosity index paraffinic oil for hydraulic circuits. Superior performance in keeping the system clean. It has good filterability, water separation, and quick air release characteristics.

FEATURES

Superior protection. Excellent anti-foam properties. Superior viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HV DENISON HF-2 DIN 51524 Part 3 EATON VICKERS I-286-S ISO 11158, HV ISO 6743-4, HV

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8306884
60L	8307089
205L	8307188
1000L	8307287
BULK	_



AROW XHV ISO 32

This is an oil of paraffinic nature with a high viscosity index, which is specially designed to be used in hydraulic circuits.


FEATURES

Superior protection. Excellent anti-foam properties. Superior viscosity stability.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HV DENISON HF-2 DIN 51524 Part 3 EATON VICKERS I-286-S ISO 11158, HV ISO 6743-4, HV

CONTENT PN CODE



PRODUCTCODE 24405

69



AROWEP ISO 46

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8305474	
60L	8305672	
205L	8305771	
1000L	8305870	
BULK	_	



AROWEP ISO 68

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8306075
60L	8306273
205L	8306372
1000L	8306471
BULK	_

PRODUCTCODE 4107

AROWEP ISO 100

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties.

Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP ISO 100

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8306679
50L	8306877
205L	8306976
1000L	8307072
BULK	_

PRODUCTCODE 4108

AROWEP ISO 150

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN \$1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307270
60L	8307478
205L	8307577
1000L	8307676
BULK	_





AROWEP ISO 220

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307874
60L	8308079
205L	8308178
1000L	8308277
BULK	_



AROWEP ISO 320 This is an extreme

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8308475
60L	8308673
205L	8308772
1000L	8308871
BULK	_

PRODUCTCODE 4111

AROWEP ISO 460

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8309076
60L	8309274
205L	8309373
1000L	8309472
BULK	_

PRODUCTCODE 4112

AROWEP ISO 680

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8309670
60L	8309878
205L	8309977
1000L	8300080
BULK	_



AROWEP ISO 1000

This is an extreme pressure oil for industrial gears. It contains high pressure additives based on sulfur and phosphorus compounds which significantly reduce friction and prevent wear.

FEATURES

Superior EP properties. Adequate protection of systems.

SPECIFICATION LEVEL

AGMA 9005-E02 AISE 224 DAVID BROWN S1.53.101E DIN 51517 CLP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8300288
60L	8300486
205L	8300585
1000L	8300684
BULK	_



ARIO ISO 32

This is a compressor oil made of highly refined base oils and additives which prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROP-oxidation test.

FEATURES

Superior protection.

Adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51506 VDL PNEUROP DIN 51.352

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8300882
50L	8301087
205L	8301186
1000L	8301285
BULK	_

PRODUCTCODE 4206

ARIO ISO 46

This is a compressor oil made of highly refined base oils and additives which prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROP-oxidation test.

FEATURES

Superior protection.
Adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51506 VDL PNEUROP DIN 51.352

CONTENT PN CODE

250ML	_
500ML	_
1L	8339615
4L	_
5L	_
20L	8303289
50L	8303487
205L	8303586
1000L	8303685
BULK	_

PRODUCTCODE 4210

ARIO ISO 68

This is a compressor oil made of highly refined base oils and additives to prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROP-oxidation test.

FEATURES

Superior protection. Adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51506 VDL PNEUROP DIN 51.352

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8301483
60L	8301681
205L	8301780
1000L	8301889
BI II K	







ARIO ISO 100

This is a compressor oil made of highly refined base oils and additives which prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROP-oxidation test

FEATURES

Superior protection. Adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51506 VDL PNEUROP DIN 51.352

CONTENT PN CODE

250ML	_
500ML	_
1L	8339813
4L	_
5L	_
20L	8302084
60L	8302282
205L	8302381
1000L	8302480
BULK	_



ARIO ISO 150

This is a compressor oil made of highly refined base oils and additives to prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROPoxidation test.

FEATURES

Superior protection. Adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51506 VDL PNEUROP DIN 51.352

CONTENT	PN CODE
---------	---------

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8302688
60L	8302886
205L	8302985
1000L	8303081
BULK	_

PRODUCTCODE 4209

AIR TOOL **LUBRICANT ISO 22**

This oil is used for the lubrication of pneumatic tools. It contains additives to improve adhesion and anti-rust, and an emulsifier to absorb moisture. It also contains anti-wear and extreme-pressure additives.

FEATURES

Good EP properties. Adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51502 D ISO 6743-11 CLASS LP

CONTENT PN CODE

250ML	_
500ML	_
1L	8306501
4L	_
5L	_
20L	8308086
60L	8308284
205L	8308383
1000L	8308482
BULK	_

PRODUCTCODE 4522

AIR TOOL **LUBRICANT ISO 32**

This oil is used for the lubrication of pneumatic tools. It contains additives to improve adhesion and anti-rust, and an emulsifier to absorb moisture. It contains anti-wear and extreme-pressure additives.


FEATURES

Good EP properties.

SPECIFICATION LEVEL

DIN 51502 D ISO 6743-11 CLASS LP

CONTENT PN CODE





PRODUCTCODE 4523

Adequate anti-foam performance.



AIR TOOL LUBRICANT ISO 46

This oil is used for the lubrication of pneumatic tools. It contains additives to improve adhesion and anti-rust, and an emulsifier to absorb moisture. It contains anti-wear and extreme-pressure additives.

FEATURES

Good EP properties. Adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51502 D ISO 6743-11 CLASS LP

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8307485
60L	8307683
205L	8307782
1000L	8307881
BULK	_



WAY LUBRICANT ISO 32

This oil is used for the lubrication of machine tool slideways. By the use of special additives, the adhesive and lubricity properties are increased and shocks (so-called stick-slip) are avoided.

FEATURES

Good stick-slip test results. Mild EP properties.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM CINCINNATI MILACRON P-53 DIN 51502 CGLP DIN 51524 Part 2

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8309885
60L	8300097
205L	8300196
1000L	8300295
BULK	_

PRODUCTCODE 4530

WAY LUBRICANT ISO 68

This oil is used for the lubrication of machine tool slideways. Due to special additives, the adhesive and lubricity properties are increased and shocks (so-called stick-slip) are avoided.

FEATURES

Good stick-slip test results. Mild EP properties.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM CINCINNATI MILACRON P-47 DIN 51502 CGLP DIN 51524 Part 2

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8300493
60L	8300691
205L	8300790
1000L	8300899
BULK	_

PRODUCTCODE 4531

WAY LUBRICANT ISO 100

This oil is particularly used for the lubrication of machine tool slideways. By the use of special additives, the adhesive and lubricity properties are increased and shocks (so-called stick-slip) are avoided.

FEATURES

Good stick-slip test results. Mild EP properties.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DIN 51502 CGLP DIN 51524 Part 2

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8301698	
60L	8301896	
205L	8301995	
1000L	8302091	
RI II K	_	









WAY LUBRICANT ISO 150

This oil is particularly used for the lubrication of machine tool slideways. By the use of special additives, the adhesive and lubricity properties are increased and shocks (so-called stick-slip) are avoided.

FEATURES

Good stick-slip test-results. Mild EP properties.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM DIN 51502 CGLP DIN 51524 Part 2

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8302299
60L	8302497
205L	8302596
1000L	8302695
BULK	_



PRODUCTCODE 4532

WAY LUBRICANT ISO 220

This oil is particularly used for the lubrication of machine tool slideways. By the use of special additives, the adhesive and lubricity properties are increased and shocks (so-called stick-slip) are avoided.

FEATURES

Good stick-slip test results. Mild EP properties.

SPECIFICATION LEVEL

AFNOR NF E 48-603 HM CINCINNATI MILACRON P-50 DIN 51502 CGLP DIN 51524 Part 2

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	8301094	
60L	8301292	
205L	8301391	
1000L	8301490	
BULK	_	

FLUSHING OIL

flushing and cleaning properties.



FEATURES

Very good detergent and dispersant characteristics.

This is a low viscosity mineral oil with good

SPECIFICATION LEVEL

ISO 6743/10

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8309281
60L	8309489
205L	8309588
1000L	8309687
BULK	_

PRODUCTCODE 4524

CUTTING OIL S 1

This is a neat cutting oil for difficult

machining operations on steel and non ferro metals. It contains "extreme pressure" additives and is suitable for drilling, tapping



and milling.

FEATURES

Superior EP properties. Adequate corrosion protection.

SPECIFICATION LEVEL

ISO 32 ISO 6743/7

CON	TENT	DN	cone
COM	ILIMI	PIV	CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8302893
60L	8303098
205L	8303197
1000L	8303296
BULK	_

PRODUCTCODE 4619

75



HEAT TRANSFER OIL ISO 32

This is a heat transfer oil based on a specifically refined mineral oil with exceptional oxidation stability and very high resistance to thermal decomposition.

FEATURES

Superior viscosity stability. Adequate protection of systems.

SPECIFICATION LEVEL

ISO 32

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	8311840
60L	8312045
205L	8312144
1000L	8312243
BULK	_

BIO HYDRAULIC FLUID 2268

This is a biologically degradable hydraulic oil based on carefully refined vegetable oils and an adapted additive package. It corresponds to ISO VG 32, 46 and 68.

FEATURES

Very high stability. Adequate protection of systems.

SPECIFICATION LEVEL

DIN 51524 Part 3 ISO 6743-4, HETG

CONTENT PN CODE

250ML	_
500ML	_
IL	_
+L	_
5L	_
20L	8314841
50L	8315046
205L	8315145
1000L	8315244
BULK	_







LITHIUM COMPLEX EP 2

Lithium-Complex grease with "Extreme Pressure" additives without lead, especially developed for the lubrication of roller bearings of vehicles.

FEATURES

Extreme pressure properties. Anti-wear and oxidation stability. Excellent high temperature properties.

SPECIFICATION LEVEL

DIN 51502 DIN KP2.5N-30 ISO L-XC(F)DIB2.5 ISO 12924

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	_	
60L	_	
205L	_	
1000L	_	
BULK	_	



PRODUCTCODE 9126

LITHIUM GREASE EP 1

This is a grease with high-pressure properties, for heavily loaded applications in general. This grease has a good oxidation stability and anti-wear properties. It insures long-lasting lubrication.

FEATURES

Good mechanical stability. Good corrosion protection. High load carrying capacity.

SPECIFICATION LEVEL

DIN 51502 DIN KP1K-30 ISO 6743 ISO L-XCCFB1

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_

CONTENT PN CODE



LITHIUM GREASE EP 2

This is a lithium thickened lubricating grease. it contains antioxidants, corrosion inhibitors and EP/AW additives. it is a typical multipurpose EP grease that can be used in various applications.

FEATURES

High load carrying capacity. Good corrosion protection. Wide range of applications.

SPECIFICATION LEVEL

DIN 51502 DIN KP2K-30 ISO 6743 ISO L-XCCIB2

CONTENT PN CODE

BULK

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

PRODUCTCODE 9130

LITHIUM GREASE EP 3

This is a grease with high-pressure properties, for heavily loaded applications. This grease has a good oxidation stability and anti-wear properties. It can insure long-lasting lubrication.

FEATURES

Works under very heavy load. Good corrosion protection. Good mechanical stability.

SPECIFICATION LEVEL

DIN 51502 DIN KP3K-30 ISO 6743 ISO L-XCCFB3

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	_	
60L	_	
205L	_	
1000L	_	
BULK	_	



MULTIPURPOSE GREASE 2

Lubricating grease for general applications. It is water resistant and has good temperature properties. It stays pumpable at low temperatures making it suitable for bearing lubrication.

FEATURES

For industrial and automotive applications. Good mechanical stability. Good corrosion protection.

SPECIFICATION LEVEL

DIN 51502 DIN K2K-30 ISO 6743 ISO L-XCCEA2

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

MULTIPURPOSE GREASE 3

Lubricating grease for general applications. It has good oxidation stability and corrosion protection. It provides temperature protection within a certain range and can be used in wet environment.

FEATURES

Good mechanical stability. Good corrosion protection Suitable also in wet environment.

SPECIFICATION LEVEL

DIN 51502 DIN K3K-30 ISO 6743 ISO L-XCCFA3

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
50L	_
205L	_
1000L	_
BULK	_

PRODUCTCODE 9103

ALL-PURPOSE EP NR. 0

This is a lithium thickened grease. It has antioxidants, corrosion inhibitors and EP/AW additives. It is a high quality multipurpose grease that is used in industrial and automotive applications.

FEATURES

Easy to pump at low temperature. Good mechanical stability. High load carrying capacity.

SPECIFICATION LEVEL

DIN 51502 DIN KP0K-30 ISO 6743 ISO L-XCCFB0

CONTENT PN CODE

250ML	_
500ML	_
1L	_
¥L	_
5L	_
20L	_
50L	_
205L	_
1000L	_
BULK	_

PRODUCTCODE 9182

ALL-PURPOSE EP NR. 00

This is a lithium thickened grease. It contains antioxidants, corrosion inhibitors and EP/AW additives. It's a multipurpose EP grease which can be used in various applications.

FEATURES

Easy to pump at low temperature. Good mechanical stability. Good corrosion protection

SPECIFICATION LEVEL

DIN 51502 DIN KP00K-30 ISO 6743 ISO L-XCCHB00

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_







CALCIUM LITHIUM EP2 HEAVY

This is a lithium calcium thickened grease. It contains antioxidants, corrosion inhibitors and EP/AW additives.

FEATURES

Excellent water resistance. Extreme load carrying capacity. Endures shock loads.

SPECIFICATION LEVEL

DIN 51502 DIN KP2K-20 ISO 6743 ISO L-XBCIB2

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_

LITHIUM CALCIUM EP2 GREEN

This lithium-calcium grease is characterized by improved water resistance and rust protection. Also suitable for the lubrication of heavily loaded bearings running at medium speed.

FEATURES

Good water resistance. Very good corrosion protection. Good resistance to shock loads.

SPECIFICATION LEVEL

DIN 51502 DIN KP2K-30 ISO 12924 ISO L-XC(F)CIB2

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	_	
60L	_	
205L	_	
1000L	_	
BULK	_	

CONTENT PN CODE

PRODUCTCODE 9184

LITHIUM GREASE EPA

This a lithium thickened grease with antioxidants, corrosion inhibitors and EP/AW additives. It is a multipurpose "moly" grease which can be used in various applications.

FEATURES

Extreme pressure properties. Anti-wear and oxidation stability. High load carrying capacity.

SPECIFICATION LEVEL

DIN 51350:4 DIN KPF2K-30 ISO 6743 ISO L-XCCEB2

CONTENT PN CODE

250ML	_	
500ML	_	
1L	_	
4L	_	
5L	_	
20L	_	
60L	_	
205L	_	
1000L	_	
BULK	_	

PRODUCTCODE 9140

MULTI MOLY GREASE 2

This is a multipurpose grease, containing molybdenum disulphide (MoS2) that contributes to its extreme pressure and anti-wear characteristics, even at the heaviest loads and the most violent shocks.

FEATURES

High load carrying capacity. Good corrosion protection. For heavily loaded slow moving bearings.

SPECIFICATION LEVEL

DIN 51502 DIN KPF2K-30 ISO 6743 ISO L-XCCIB2

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_



HIGH TEMPERATURE GREASE 2

This grease is based on high viscosity mineral base oils with high flash point. Bentone is used as inorganic thickener that makes the product suitable for a wide range of temperatures.

FEATURES

Superior protection against oxidation.
Outstanding high temperature properties.
Wide range of applications.

SPECIFICATION LEVEL

DIN 51502 DIN KP2N-30 ISO 6743 ISO L-XCDAB2

CONTENT PN CODE

250ML	_
500ML	_
1L	_
4L	_
5L	_
20L	_
60L	_
205L	_
1000L	_
BULK	_







WOLF OIL CORPORATION NV

Georges Gilliotstraat 52 2620 Hemiksem Belgium Phone +32 (0) 3 870 00 00 Fax +32 (0) 3 870 00 99 Email info@wolfoil.com

www.wolflubes.com

