

TEST REPORT: 7191160659-CHM17-TSL

Date: 20 APR 2017

Tel: +65 68851312 Fax: +65 67784301

Client's Ref: 221411740

Email: zhou.xiao@tuv-sud-psb.sg

Note: This report is issued subject to the Testing and Certification Regulations of the TÜV SÜD Group and the General Terms and Conditions of Business of TÜV SÜD PSB Pte Ltd. In addition, this report is governed by the terms set out within this report.



PSB Singapore

Choose certainty.
Add value.

SUBJECT

Evaluation of Toxic Fumes Generated From Material Sample During Burning

CLIENT

Superlon Worldwide Sdn Bhd
Lot 2736, Jalan Raja Nong, Klang
41200 Selangor Darul Ehsan
Selangor

Attn : Ms Joanna

SAMPLE SUBMISSION DATE

30 Mar 2017

DESCRIPTION OF SAMPLE

One piece of material sample labelled as follows was received.

Sample Information		Figure of Sample
Brand & Model Reference	Superlon	
Generic Product Name	Insulation Material	
Product Composition	Nitrile Butadiene Rubber	
Nominal Mass per Unit Area (kg/m ²)	65	
Nominal Thickness (mm)	6	

DATE OF ANALYSIS

03 Apr 2017 – 18 Apr 2017



Laboratory:
TÜV SÜD PSB Pte. Ltd.
No.1 Science Park Drive
Singapore 118221

Phone : +65-6885 1333
Fax : +65-6776 8670
E-mail: enquiries@tuv-sud-psb.sg
www.tuv-sud-psb.sg
Co. Reg : 199002667R

Regional Head Office:
TÜV SÜD Asia Pacific Pte. Ltd.
1 Science Park Drive, #02-01
Singapore 118221
TUV®



METHOD OF TEST

Analysis of Pyrolysis and Combustion Gases Generated From the Sample

The test was conducted according to BS 6853:1999 Annex B, B.1 Mass Based Test Method - NF X 70-100 (2006) Method:

1.1 Sample Preparation of Test Specimen

The sample was conditioned at 23°C and 50% Relative Humidity for 48 hours and tested as whole for the following tests.

1.2 Generation of Pyrolysis and Combustion Gases

Approximately 1.0g of the sample was then used for the test in a stream of air at the air flow rate of 120L/hr at 400°C for 20 minutes in a tube furnace. A further 20 minutes was used to air-flush the apparatus once residue sample was removed from tube furnace.

Toxic fumes collected during the burning were analysed by the following methods:

- a) Carbon Monoxide and Carbon Dioxide : Directly determined by Testo 300 XL-I Flue Gas Analyser
- b) Hydrogen Cyanide : By Pyridine – Pyrazalone Method
- c) Others ions: By Ion Chromatography



RESULTS

Table 1: The Toxic Fumes Results For "Superlon Insulation Material" Sample

Toxic Fumes Generated	"Superlon Insulation Material" (mg/m ³ of Fire Effluents)	IDLH Values Limits ^a (mg/m ³)
1. Carbon Dioxide, Average (Carbon Dioxide, maximum)	<200 <200	73000 -
2. Carbon Monoxide, Average (Carbon Monoxide, maximum)	<200 <200	1400 -
3. Hydrogen Fluoride, HF	<5	25
4. Hydrogen Chloride, HCl	<5	76
5. Hydrogen Bromide, HBr	<5	101
6. Sulfur Dioxide, SO ₂ ^b	<5	270
7. Nitrogen Dioxide, NO ₂ ^c	<5	38
8. Hydrogen Cyanide, HCN	<5	56

^a The values in Table 1 are the IDLH values of the listed gases (the concentration of the gas in the atmosphere which for an exposure time of 30mins is immediately Dangerous to Life or Health) given in the NIOSH Guide [1].

^b Sulfur Dioxide includes Sulfur trioxide expressed as sulfur dioxide

^c Nitrogen dioxide includes nitric oxide expressed as nitrogen dioxide

1. The above results from the analysis of the toxic fumes generated from the specimen were found to be below the IDLH Value of listed gases.
2. The weighted summation index, R, is less than 0.3.

Remarks

The weighted summation index R for the sample tested was found to be within the requirement of 1.0 max when tested and assessed according to NF X 70-100 with R calculated in accordance with Annex B of BS 6853:1999.

MS TAN SER LING
TECHNICAL EXECUTIVE

DR XIAO ZHOU
PRODUCT MANAGER
MICROCONTAMINATION DIAGNOSIS
CHEMICAL & MATERIALS