



CAROLINA



CAROLINA BREWTECH LLC

STANDARD FEATURES:

- Butterfly valves, sample valve, PVRV, pressure gauge, thermometer
- Inner shell 304 stainless steel, thickness 3mm
- Outer shell 304 stainless steel, thickness 2mm
- Interior & exterior sanitary polished
- Fully pickled and passivated
- 60° cone bottom
- Rotary racking arm
- CIP assembly
- Blow off arm
- Top/side man way
- Carb stone assembly
- Dual zone dimple glycol jackets
- RTD sensor port
- 3" insulation
- Necessary fittings and valves
- Work pressure: 30Psi
- Tested pressure: 60Psi

Fermentation tank

Size	D	H	Full Volume
3BBL	960mm [37.80in]	≈ 2020mm [79.52in]	3.92BBL
5BBL	1060mm [41.73in]	≈ 2100mm [82.67in]	6.21BBL
7BBL	1110mm [43.70in]	≈ 2515mm [99.01in]	8.55BBL
10BBL	1260mm [49.01in]	≈ 2550mm [100.39in]	12.10BBL
15BBL	1410mm [55.51in]	≈ 2900mm [114.17in]	18.39BBL
20BBL	1610mm [63.39in]	≈ 3270mm [128.74in]	25.92BBL
30BBL	1860mm [73.22in]	≈ 3505mm [137.99in]	37.68BBL



Tel: (410) 971-8326



Email: sales@carolinabeers.com



Address: Unit 505, Curtis Business Ctr 3 - 709 East Ordinance Road, Baltimore, MD 21226

<https://www.carolinamicrobrewing.com>