



CAROLINA

CAROLINA BREWTECH LLC

STANDARD FEATURES:

- Butterfly valves, Sample valve, PVRV, Pressure gauge, Thermowell, Thermometer
- Dry hopping port of top
- 4 stainless steel legs with stainless leveling footpads
- Inner shell: 304 stainless steel, thickness 0.12"
- Outer shell: 304 stainless steel, thickness 0.08" (Exterior brushed)
- Interior and exterior finish polished to a sanitary finish
- Interior finish pickled and passivated
- Fully welded exterior shell
- 60 degree cone bottom
- Rotating beer outlet port
- Side manway
- Dual zone dimple cooling jackets (3 or more on larger tanks)
- 3" Polyurethane insulation
- CIP arm and rotary spray ball
- Sanitary tri-clamp connections



Fermentation tank - 1

Size	D	H	Full Volume
5BBL	1060mm [41.73in]	2096mm [82.52in]	6.26BBL [735L]
7BBL	1110mm [43.70in]	2516mm [99.06in]	8.52BBL [1000L]
10BBL	1260mm [49.01in]	2552mm [100.47in]	12.10BBL [1420L]
15BBL	1460mm [57.48in]	3087mm [121.54in]	20.19BBL [2370L]
20BBL	1610mm [63.39in]	3267mm [128.62in]	25.98BBL [3050L]
500L	1060mm [41.73in]	1946mm [76.61in]	5.41BBL [635L]
1000L	1210mm [47.64in]	2573mm [101.30in]	10.73BBL [1260L]
2000L	1510mm [59.45in]	3146mm [123.86in]	21.89BBL [2570L]