



CAROLINA



CAROLINA BREWTECH LLC

STANDARD FEATURES:

- Butterfly valves, sample valve, PVRV, pressure gauge, thermometer
- Inner shell 304 stainless steel, thickness 3mm
- Outer shell 304 stainless steel, thickness 2mm
- Interior & exterior sanitary polished
- Fully pickled and passivated
- 60° cone bottom
- Rotary racking arm
- CIP assembly
- Top/side man way
- Carb stone assembly
- Dual zone dimple glycol jackets
- RTD sensor port
- 3" insulation
- Necessary fittings and valves
- Work pressure: 30Psi
- Tested pressure: 60Psi

Fermentation tank

Size	D	H	Full Volume
2BBL	860mm [33.86in]	≈ 1820mm [71.65in]	2.56BBL
3BBL	960mm [37.80in]	≈ 2530mm [99.61in]	3.92BBL
5BBL	1060mm [41.73in]	2100mm [82.67in]	6.26BBL
7BBL	1110mm [43.70in]	2515mm [99.01in]	8.52BBL
10BBL	1260mm [49.01in]	2550mm [100.39in]	12.10BBL
15BBL	1460mm [57.48in]	2940mm [115.74in]	20.19BBL
20BBL	1610mm [63.39in]	3270mm [128.74in]	25.98BBL

<https://www.carolinamicrobrewing.com>

Tel: (410) 971-8326

Email: sales@carolinabeers.com

Address: Unit 505, Curtis Business Ctr 3 - 709 East Ordinance Road, Baltimore, MD 21226