




## DIMENSIONS



## ACCESSORIES



HIGH CHROMATIC LED



BEAM MIXER DIFFUSER



DRIVER OPTIONS

## PRODUCT

Name	TOP MINI W/O EQ. 20° 3000K WT
Reference	A2960011WT
Color	Textured white
Category	SURFACE & SUSPENDED

## LIGHTING INFORMATION

Light source	LED
Gross luminous flux	500 / 640 Lm
Power	4,5 / 6,5 W
Colour temperature	3000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	20°
Unified Glare Rating	UGR<19
Lighting efficiency	92%
Efficacy	111 Lm/W
Current intensity	500 / 700 mA
Dimming	No Dim - Other DIM, please consult
Driver	Excl.
Electrical insulation class	III
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A++
LED lifespan	L80B10 (Tj=85°C) >60.000h

## OTHER DATA

Ingress Protection	IP20
Weight	58 g.
Packaged weight	85 g.
Packaging dimensions	136 × 68 × 51 mm.
Materials	Aluminium / Polycarbonate



Top is a miniaturized surface-mounted ceiling luminaire. Its compact design makes Top an ideal solution for installation in ceiling cavities and for projects where a discrete presence of the luminaire in the scene is desired. Formally Top presents itself as a design of pure lines and architectural aesthetics. In terms of lighting, Top offers a conical distribution with three available beam angles (flood, medium and spot). Its installation is extremely easy and safe, fixing it to the ceiling by means of a bayonet system that does not require the use of any tools.



Vivid Model Colour Temperature	2700K	3000K	3500K	4000K	Light Pink
📖 Reading			•	•	
🥬 Fruits & Vegetables		•	•		
🍞 Bakery	•				
👤 Retail		•	•		
💄 Cosmetics			•	•	
🍖 Meat					•
🐟 Fish				•	
🐠 Seafood				•	•

For some of its products, Arkoslight offers the possibility to provide them with a special LED, designed to create an illumination focused on visually promoting goods or products for commercial purposes.

It is a high chromaticity LED, capable of identifying the colour shades that produce a positive psychological perception of the illuminated object.


This special LED lighting source offers a much more attractive and intense colour range than a conventional LED, besides being much wider. Technically, this is possible thanks to a special LED setting that includes a « special saturation parameter », capable of highlighting the objects colours and materials in such a way that they seem more attractive within the visible light spectrum. To achieve this performance, in each case, the appropriate diode and specific phosphor coating are carefully selected.







	PRODUCT
Model	TOP Beam Mixer Diffuser
Reference	08050100
Category	Accessories

NOT SOLD SEPARATELY.

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening. The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.



DRIVER OPTIONS  
[1 to 4 TOP mini]\*

	W	mA	K	Lm
0434-00-42	4,5 W	500	2700K	480
			3000K	500
			4000K	515
0434-00-43	4,5 W	500	2700K	480
			3000K	500
			4000K	515
 PUSH / 1-10V	4,5 W	500	2700K	480
			3000K	500
			4000K	515
 DALI	4,5 W	500	2700K	480
			3000K	500
			4000K	515
0434-00-40	6,5 W	700	2700K	610
			3000K	640
			4000K	655
0434-00-45	6,5 W	700	2700K	610
			3000K	640
			4000K	655
 PUSH / 1-10V	6,5 W	700	2700K	610
			3000K	640
			4000K	655
 DALI	6,5 W	700	2700K	610
			3000K	640
			4000K	655

DRIVER MUST BE PLACED ON REMOTE