

## WALKIE STRADDLE STACKER EB16EA



## WALKIE STRADDLE STACKER



## EB16EA

Superior quality, maneuverable, compact, and durable for all your material handling applications. Ideal for small aisles and areas.

WEIGHT CAPACITY: 4400 lbs. @ 24" load center

**LIFT HEIGHT:** 216" (18 ft.)

**FORK LENGTH: 45.28"** 

**ADJUSTABLE OUTRIGGERS: 38.06-51.81"** 

**ADJUSTABLE FORKS: 9.8-31.5"** 

MAST HEIGHT: 98.03"

TURNING RADIUS: 69.09"

BATTERY / CHARGER: 24V/210Ah, 24-volt

deep cycle maintenance-free batteries with external direct connect 110A 110VAC plug-in automatic

24V/30A charger (both Included)

SPEED TRAVEL: 3.3 mph empty; 3.0 mph loaded

**LIFTING SPEED:** 5.35 ips empty; 3.6 ips loaded

LOWERING SPEED: 3.85 ips empty; 4.4 ips loaded

**DRIVE WHEELS:** 9" x 3" polyurethane

**STABILITY:** 4" x 2" polyurethane

**LOAD WHEELS:** (2) 4" x 3" polyurethane per outrigger

HYDRAULICS LIFTING MOTOR: 24V 3000-Watt lifting motor with hardened chrome moly steel for durability.

DRIVE MOTOR: 24V AC ZF 3000Watt drive motor for efficiency and high torque. EPS (Electric Power Steering)

**AC CONTROLLER:** 24V CURTIS Instrument provides performance through entire range of speed; Constant travel speed regardless of load; Battery discharge indicator combination gauge.

**BRAKES:** Electro-magnetic braking for secure stopping power; Electronic neutral braking for accurate control.

**OPERATOR CONTROLS:** Throttle, lifting, lowering, turtle mode and horn functions are in the ergonomic handle; Offset steering handle to provide better visibility; Belly button reverse safety feature allows the unit to stop and reverse to avoid collision or injury.

**CHASSIS AND MAST:** Robotic Welding; Heavy duty steel chassis with I-beam mast for durability; Telescoping mast includes a protective steel guard.



## Walkie Straddle Stacker





MODEL#	MAST	LIFT HEIGHT	MAX MAST HEIGHT	SERVICE WEIGHT
EB16EA	98.03"	216"	253.15"	3542

