

# LE4140 H1 QUINPLEX White Gear Lubricant

Lubrication Engineers NZ Ltd

Chemwatch Hazard Alert Code: 2

Chemwatch: 22-6148

Issue Date: 07/01/2015

Version No: 6.1.1.1

Print Date: 09/03/2018

Safety Data Sheet according to HSNO Regulations

S.GHS.NZL.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

Product name	LE4140 H1 QUINPLEX White Gear Lubricant
Synonyms	Not Available
Other means of identification	Not Available

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions. Lubricant.
--------------------------	---

### Details of the supplier of the safety data sheet

Registered company name	Lubrication Engineers NZ Ltd
Address	11F Piermark Drive North Harbour Industrial Estate Albany, Auckland New Zealand
Telephone	+64 09 415 9411
Fax	+64 09 4158411
Website	Not Available
Email	Not Available

### Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	+64 21 3385487
Other emergency telephone numbers	Not Available

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.**

#### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	1	1
Toxicity	1	1
Body Contact	2	2
Reactivity	1	1
Chronic	0	0

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

Classification <sup>[1]</sup>	Acute Toxicity (Oral) Category 5, Skin Corrosion/Irritation Category 3, Eye Irritation Category 2B
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

LE4140 H1 QUINPLEX White Gear Lubricant

<b>Determined by Chemwatch using GHS/HSNO criteria</b>	6.1E (oral), 6.3B, 6.4A (mild)
--	--------------------------------

**Label elements**

<b>Hazard pictogram(s)</b>	Not Applicable
----------------------------	----------------

<b>SIGNAL WORD</b>	<b>WARNING</b>
--------------------	----------------

**Hazard statement(s)**

<b>H303</b>	May be harmful if swallowed.
<b>H316</b>	Causes mild skin irritation.
<b>H320</b>	Causes eye irritation.

**Precautionary statement(s) Prevention**

<b>P264</b>	Wash all exposed external body areas thoroughly after handling.
-------------	---

**Precautionary statement(s) Response**

<b>P312</b>	Call a POISON CENTER or doctor/physician if you feel unwell.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P332+P313</b>	If skin irritation occurs: Get medical advice/attention.
<b>P337+P313</b>	If eye irritation persists: Get medical advice/attention.

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

Not Applicable

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

**Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
8042-47-5	NotSpec	<u>white mineral oil (petroleum)</u>
64742-46-7.	1-5	<u>distillates, petroleum, middle, hydrotreated</u>
140-88-5	NotSpec	<u>ethyl acrylate</u>
6683-19-8	NotSpec	<u>pentaerythritol tetrabutylhydroxyhydrocinnamate</u>
65-85-0	NotSpec	<u>benzoic acid</u>
103-11-7	NotSpec	<u>2-ethylhexyl acrylate</u>
	balance	Ingredients determined not to be hazardous

**SECTION 4 FIRST AID MEASURES**

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

**Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> </ul>

Continued...

	<ul style="list-style-type: none"> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- ▶ Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- ▶ In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- ▶ High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

**Do not** use a water jet to fight fire.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result</li> </ul>
-----------------------------	--

### Advice for firefighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) other pyrolysis products typical of burning organic material. May emit poisonous fumes.</p> <p><b>CARE:</b> Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.</p>

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<p>Slippery when spilt.</p> <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> </ul>
---------------------	--

<b>Major Spills</b>	<p>Slippery when spilt. Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> </ul>
---------------------	--

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> </ul>

### Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid strong acids, bases.</li> <li>▶ Avoid reaction with oxidising agents</li> </ul>



+            X            +            O            X            +            +

X — Must not be stored together

O — May be stored together with specific preventions

+ — May be stored together

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	white mineral oil (petroleum)	Oil mist, mineral	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	Not Available	(om) - Sampled by a method that does not collect vapour.
New Zealand Workplace Exposure Standards (WES)	distillates, petroleum, middle, hydrotreated	Oil mist, mineral	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	Not Available	(om) - Sampled by a method that does not collect vapour.
New Zealand Workplace Exposure Standards (WES)	ethyl acrylate	Ethyl acrylate	Not Available	Not Available	20 mg/m <sup>3</sup> / 5 ppm	(sen) - Sensitiser; (skin) - Skin absorption

#### EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethyl acrylate	Ethyl acrylate	Not Available	Not Available	Not Available
benzoic acid	Benzoic acid	15 mg/m <sup>3</sup>	170 mg/m <sup>3</sup>	830 mg/m <sup>3</sup>
2-ethylhexyl acrylate	Ethylhexyl acrylate, 2-; (Acrylic acid, 2-ethylhexyl ester)	15 ppm	120 ppm	150 ppm

Ingredient	Original IDLH	Revised IDLH
white mineral oil (petroleum)	2500 mg/m <sup>3</sup>	Not Available
distillates, petroleum, middle, hydrotreated	2500 mg/m <sup>3</sup>	Not Available
ethyl acrylate	300 ppm	Not Available

pentaerythritol tetrabutylhydroxyhydrocinnamate	Not Available	Not Available
benzoic acid	Not Available	Not Available
2-ethylhexyl acrylate	Not Available	Not Available

## Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p> <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C. apron.</li> <li>▶ Barrier cream.</li> </ul>
<b>Thermal hazards</b>	Not Available

## Recommended material(s)

### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

LE4140 H1 QUINPLEX White Gear Lubricant

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
PVA	C
TEFLON	C
VITON/NEOPRENE	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is

Continued...

LE4140 H1 QUINPLEX White Gear Lubricant

not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Appearance</b>	Transparent liquid with a hydrocarbon-like odour; not miscible with water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.89
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	6-8	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	440
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	198	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Immiscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	<1	<b>VOC g/L</b>	40

**SECTION 10 STABILITY AND REACTIVITY**

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

**SECTION 11 TOXICOLOGICAL INFORMATION**

**Information on toxicological effects**

<b>Inhaled</b>	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation hazard is increased at higher temperatures. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
<b>Ingestion</b>	Accidental ingestion of the material may be damaging to the health of the individual.
<b>Skin Contact</b>	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition
<b>Eye</b>	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

<b>Chronic</b>	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.
----------------	--

LE4140 H1 QUINPLEX White Gear Lubricant	TOXICITY	IRRITATION
		Not Available
white mineral oil (petroleum)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup> Oral (rat) LD50: >5000 mg/kg <sup>[1]</sup>	Not Available
distillates, petroleum, middle, hydrotreated	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup> Oral (rat) LD50: >5000 mg/kg <sup>[1]</sup>	Not Available
ethyl acrylate	TOXICITY	IRRITATION
	dermal (rat) LD50: 3049 mg/kg <sup>[1]</sup>	Eye (rabbit): 1204 ppm/7h
	Inhalation (rat) LC50: 1412.386626 mg/l/4hd <sup>[2]</sup> Oral (rat) LD50: 800 mg/kg <sup>[2]</sup>	Eye (rabbit): 45 mg - mild Skin (rabbit): 10 mg/24h - mild Skin (rabbit): 500 mg open - mild
pentaerythritol tetrabutylhydroxyhydrocinnamate	TOXICITY	IRRITATION
	dermal (rat) LD50: 3160 mg/kg <sup>[2]</sup> Oral (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: non-irritating ** Skin: non-irritating **
benzoic acid	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 2000 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg - SEVERE
	Oral (rat) LD50: 1700 mg/kg <sup>[2]</sup>	Skin (human): 22 mg/3d - moderate Skin (rabbit): 500 mg/24h - mild
2-ethylhexyl acrylate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: ~7522 mg/kg <sup>[1]</sup>	Eyes (rabbit) 500mg/24h mild
	Oral (rat) LD50: 5660 mg/kg <sup>[2]</sup>	Skin (rabbit) 10mg/24h - SEVERE Skin (rabbit) 20mg/24h mod. Skin (rabbit) 500mg mild

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

<b>WHITE MINERAL OIL (PETROLEUM)</b>	<p>The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives;</p> <p>The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:</p> <ul style="list-style-type: none"> <li>The adverse effects of these materials are associated with undesirable components, and</li> <li>The levels of the undesirable components are inversely related to the degree of processing;</li> <li>Distillate base oils receiving the same degree or extent of processing will have similar toxicities;</li> <li>The potential toxicity of residual base oils is independent of the degree of processing the oil receives.</li> <li>The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.</li> </ul> <p>Unrefined &amp; mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components.</p> <p>For highly and severely refined distillate base oils:</p> <p>In animal studies, the acute, oral, semilethal dose is &gt;5g/kg body weight and the semilethal dose by skin contact is &gt;2g/kg body weight. The semilethal concentration for inhalation is 2.18 to &gt;4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation.</p>
--------------------------------------	---

## LE4140 H1 QUINPLEX White Gear Lubricant

	<p>Testing for sensitisation has been negative.</p> <p>The substance is classified by IARC as Group 3:</p> <p><b>NOT</b> classifiable as to its carcinogenicity to humans.</p> <p>Evidence of carcinogenicity may be inadequate or limited in animal testing.</p> <p>Oral (rat) TCLo: 92000 mg/kg/92D-Cont. Generally the toxicity and irritation is of low order. White oils and highly/solvent refined oils have not shown the long term risk of skin cancer that follows persistent skin contamination with some other mineral oils, due in all probability to refining that produces low content of both polyaromatics (PAH) and benz-alpha-pyrenes (BaP)</p>
<b>ETHYL ACRYLATE</b>	<p>The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p><b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.</p> <p>Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. of Health &amp; Human Services 2002]</p>
<b>PENTAERYTHRITOL TETRABUTYLHYDROXYHYDROCINNAMATE</b>	<p>Data show that acute toxicity following oral and topical use of hindered phenols is low. They are not proven to cause mutations. However, long term use may affect the liver, thyroid, kidney and lymph nodes. Liver tumours have been reported.</p> <p>Non-sensitising in Guinea pig skin assay ** * CG ** Clariant</p>
<b>BENZOIC ACID</b>	<p>For benzoates: Benzyl alcohol, benzoic acid and its sodium and potassium salt have a common metabolic and excretion pathway. All but benzyl alcohol are considered to be unharmed and of low acute toxicity. They may cause slight irritation by oral, dermal or inhalation exposure except sodium benzoate which doesn't irritate the skin. Studies showed increased mortality, reduced weight gain, liver and kidney effects at higher doses, also, lesions of the brains, thymus and skeletal muscles may occur with benzyl alcohol. This is a member or analogue of a group of benzyl derivatives generally regarded as safe (GRAS), based partly on their self-limiting properties as flavouring substances in food. In humans and other animals, they are rapidly absorbed, broken down and excreted, with a wide safety margin. They also lack significant potential to cause genetic toxicity and mutations. The intake of benzyl derivatives as natural components of traditional foods is actually higher than the intake as intentionally added flavouring substances.</p> <p>Mutagenicity: Bacterial reverse mutation test (S. typhimurium): not mutagenic (OECD 471, EC B.13/14; Ames test) In vitro mammalian chromosome aberration (Chinese hamster fibroblasts): negative Reproductive toxicity: 4 generation study in rats: Oral NOAEL &gt;500 mg/kg bw/day STOT single exposure: In a repeated inhalation study benzoic acid appeared to be irritating to the respiratory tract at high doses * DSM SDS</p>
<b>2-ETHYLHEXYL ACRYLATE</b>	<p>The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.</p> <p>For 2-ethylhexyl acrylate: Animal testing shows that 2-ethylhexyl acrylate can cause skin sensitisation and damage sensation of smell, and that chronic exposure can increase the incidence of kidney inflammation. High doses may cause developmental effects. Testing has shown that 2-ethylhexyl acrylate may cause genetic damage and/or mutations. It has not been shown to cause tumours except at very high doses.</p> <p>Substance has been investigated as a tumourigen on mouse skin.</p>
<b>ETHYL ACRYLATE &amp; 2-ETHYLHEXYL ACRYLATE</b>	<p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.</p>
<b>ETHYL ACRYLATE &amp; BENZOIC ACID &amp; 2-ETHYLHEXYL ACRYLATE</b>	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.</p>
<b>ETHYL ACRYLATE &amp; 2-ETHYLHEXYL ACRYLATE</b>	<p>Where no "official" classification for acrylates and methacrylates exists, there have been cautious attempts to create classifications in the absence of contrary evidence. For example Monalkyl or monoarylestere of acrylic acids should be classified as R36/37/38 and R51/53 Monoalkyl or monoaryl estere of methacrylic acid should be classified as R36/37/38</p>
<b>ETHYL ACRYLATE &amp; BENZOIC ACID</b>	<p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p>
<b>ETHYL ACRYLATE &amp; 2-ETHYLHEXYL ACRYLATE</b>	<p>Based on the available oncogenicity data and without a better understanding of the carcinogenic mechanism the Health and Environmental Review Division (HERD), Office of Toxic Substances (OTS), of the US EPA previously concluded that all chemicals that contain the acrylate or methacrylate moiety (CH<sub>2</sub>=CHCOO or CH<sub>2</sub>=C(CH<sub>3</sub>)COO) should be considered to be a carcinogenic hazard unless shown</p>

	otherwise by adequate testing. This position has now been revised and acrylates and methacrylates are no longer <i>de facto</i> carcinogens.
<b>BENZOIC ACID &amp; 2-ETHYLHEXYL ACRYLATE</b>	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

<b>Acute Toxicity</b>	✓	<b>Carcinogenicity</b>	⊘
<b>Skin Irritation/Corrosion</b>	✓	<b>Reproductivity</b>	⊘
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	⊘
<b>Respiratory or Skin sensitisation</b>	⊘	<b>STOT - Repeated Exposure</b>	⊘
<b>Mutagenicity</b>	⊘	<b>Aspiration Hazard</b>	⊘

**Legend:** ✗ – Data available but does not fill the criteria for classification  
✓ – Data available to make classification  
⊘ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

### Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
<b>LE4140 H1 QUINPLEX White Gear Lubricant</b>	Not Available	Not Available	Not Available	Not Available	Not Available
<b>white mineral oil (petroleum)</b>	Not Available	Not Available	Not Available	Not Available	Not Available
<b>distillates, petroleum, middle, hydrotreated</b>	NOEC	48	Crustacea	=10mg/L	1
<b>ethyl acrylate</b>	LC50	96	Fish	1.1mg/L	2
	EC50	48	Crustacea	1.3mg/L	2
	EC50	72	Algae or other aquatic plants	1.71mg/L	2
	NOEC	504	Crustacea	0.136mg/L	2
<b>pentaerythritol tetrabutylhydroxyhydrocinnamate</b>	EC50	72	Algae or other aquatic plants	>100mg/L	1
<b>benzoic acid</b>	LC50	96	Fish	180mg/L	4
	EC50	48	Crustacea	860mg/L	4
	EC50	72	Algae or other aquatic plants	>33.1mg/L	2
	BCF	24	Algae or other aquatic plants	0.05mg/L	4
	NOEC	72	Algae or other aquatic plants	0.11mg/L	2
<b>2-ethylhexyl acrylate</b>	LC50	96	Fish	1.1mg/L	2
	EC50	48	Crustacea	1.3mg/L	2
	EC50	72	Algae or other aquatic plants	1.71mg/L	2
	NOEC	504	Crustacea	0.136mg/L	2

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

Continued...

**Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
ethyl acrylate	LOW (Half-life = 14 days)	LOW (Half-life = 0.95 days)
pentaerythritol tetrabutylhydroxyhydrocinnamate	HIGH	HIGH
benzoic acid	LOW	LOW
2-ethylhexyl acrylate	LOW	LOW

**Bioaccumulative potential**

Ingredient	Bioaccumulation
ethyl acrylate	LOW (LogKOW = 1.32)
pentaerythritol tetrabutylhydroxyhydrocinnamate	LOW (BCF = 2.3)
benzoic acid	LOW (LogKOW = 1.87)
2-ethylhexyl acrylate	LOW (BCF = 289.73)

**Mobility in soil**

Ingredient	Mobility
ethyl acrylate	LOW (KOC = 11.85)
benzoic acid	LOW (KOC = 14.49)
2-ethylhexyl acrylate	LOW (KOC = 429)

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Product / Packaging disposal</b>	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> <li>▶ Bury or incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
-------------------------------------	--

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture**

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002624	N.O.S. (Subsidiary Hazard) Group Standard 2006
HSR002535	Compressed Gas Mixtures (Subsidiary Hazard) Group Standard 2006
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2006
HSR002530	Cleaning Products (Subsidiary Hazard) Group Standard 2006
HSR002585	Fuel Additives (Subsidiary Hazard) Group Standard 2006
HSR002519	Aerosols (Subsidiary Hazard) Group Standard 2006
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2006
HSR002606	Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2006
HSR002644	Polymers (Subsidiary Hazard) Group Standard 2006
HSR002647	Reagent Kits Group Standard 2006
HSR002612	Metal Industry Products (Subsidiary Hazard) Group Standard 2006
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006
HSR002503	Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006
HSR002638	Photographic Chemicals (Subsidiary Hazard) Group Standard 2006
HSR002565	Embalming Products (Subsidiary Hazard) Group Standard 2006
HSR002578	Food Additives and Fragrance Materials (Subsidiary Hazard) Group Standard 2006
HSR002558	Dental Products (Subsidiary Hazard) Group Standard 2006
HSR002684	Water Treatment Chemicals (Subsidiary Hazard) Group Standard 2006
HSR002573	Fire Fighting Chemicals Group Standard 2006
HSR100425	Pharmaceutical Active Ingredients Group Standard 2010
HSR002600	Leather and Textile Products (Subsidiary Hazard) Group Standard 2006
HSR002605	Lubricants (Low Hazard) Group Standard 2006
HSR002571	Fertilisers (Subsidiary Hazard) Group Standard 2006
HSR002648	Refining Catalysts Group Standard 2006
HSR002653	Solvents (Subsidiary Hazard) Group Standard 2006
HSR002544	Construction Products (Subsidiary Hazard) Group Standard 2006
HSR002549	Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2006
HSR002552	Cosmetic Products Group Standard 2006
HSR100757	Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2012
HSR100758	Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2012
HSR100628	Straight-chained Lepidopteran Sex Pheromone Group Standard 2012
HSR100580	Tattoo and Permanent Makeup Substances Group Standard 2011

**WHITE MINERAL OIL (PETROLEUM)(8042-47-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Workplace Exposure Standards (WES)

New Zealand Inventory of Chemicals (NZIoC)

**DISTILLATES, PETROLEUM, MIDDLE, HYDROTREATED(64742-46-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Workplace Exposure Standards (WES)

New Zealand Inventory of Chemicals (NZIoC)

**ETHYL ACRYLATE(140-88-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Continued...

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### PENTAERYTHRITOL TETRABUTYLHYDROXYHYDROCINNAMATE(6683-19-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

#### BENZOIC ACID(65-85-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

#### 2-ETHYLHEXYL ACRYLATE(103-11-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

### Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

### Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

### Tracking Requirements

Not Applicable

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (benzoic acid; pentaerythritol tetrabutylhydroxyhydrocinnamate; 2-ethylhexyl acrylate; distillates, petroleum, middle, hydrotreated; ethyl acrylate; white mineral oil (petroleum))
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (distillates, petroleum, middle, hydrotreated; white mineral oil (petroleum))
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
<b>Legend:</b>	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## SECTION 16 OTHER INFORMATION

### Other information

### Ingredients with multiple cas numbers

Name	CAS No
pentaerythritol	6683-19-8, 5106-16-1, 12634-41-2, 60005-82-5, 67894-72-8, 68882-58-6, 70695-00-0, 98584-37-3, 103843-13-6,
tetrabutylhydroxyhydrocinnamate	127337-64-8, 137500-49-3, 145526-73-4, 154508-64-2

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.