

NOVOCLEAR 485 HTO

Rid your water of hardness & bad tastes and odor caused by chlorine, chloramines or organic matter

The unique two tank system keeps the two media beds separate and allows for more carbon contact improving chlorine, chloramines and organic removal.

Because the carbon may need to be replaced before the softening resin, the two tank system allows for replacement without having to change the resin bed unlike many traditional mixed bed systems. Same benefit as separate systems but with cost of only one control valve.



Features:

- ➔ Dedicated softening & carbon filtration tanks provide truly refined water
- ➔ NSF Certified control valve with electronic sensors, adjustable cycles & proven piston, seal & spacer design
- ➔ Reverse Flow regeneration preserves unused portion of softening bed from unnecessary exchange saving salt
- ➔ Precision brining calculates the exact amount of brine required to regenerate saving up to 30% more salt
- ➔ Backwash Frequency Preset for clean municipal water saves water by matching backwash to water quality need
- ➔ Soft Water brine tank refill keeps tank & injectors clean
- ➔ Automatic system refresh flushes stagnant water
- ➔ NSF Certified fibreglass pressure tank
- ➔ WQA Gold Seal Certified cation resin
- ➔ User-friendly backlit LCD display
- ➔ “No Touch” rotating information display
- ➔ Unique bypass with integrated turbine meter saves space, eliminates connections
- ➔ Time saving quick connect fittings on bypass, drain line, brine line & power cord
- ➔ Drain line o-ring. No need for Teflon
- ➔ Brine safety valve provides added overflow protection
- ➔ Plastic salt grid prevents bridging
- ➔ 48 hour self charging battery back-up
- ➔ Includes hose clamp & 10’ of drain tubing

Specifications	485HTO-100	485HTO-150	485HTO-200	485HTO-300
	15010484	15010485	15010486	15010487
Factory Settings				
Salt Used - Per Regeneration	6.0 lbs	9.0 lbs	12.0 lbs	18.0 lbs
Water Used - Regeneration	86.4 gal	148 gal	162.4 gal	224.8 gal
Hardness Removal - Grains	25,000	37,500	50,000	75,000
Tank #1 Carbon Quantity - Cubic Feet	1.0 ft	1.50 ft	2.0 ft	3.0 ft
Tank #2 Resin Quantity - Cubic Feet	1.0 ft	1.50 ft	2.0 ft	3.0 ft
Tank Size	9x48	10x54	12x52	14x65
Tank Jacket / Media Loaded	Yes	Yes	No	No
Brine Tank / Cabinet Size (Inches)	18.1 x 34.5	18.1 x 34.5	20.3 x 37.4	23.0 x 40.5
Salt Storage Capacity	240 lbs	240 lbs	350 lbs	420 lbs
Flow Rate @ 15 psi Pressure Drop	7.2 gpm	7.4 gpm	9.0 gpm	9.2 gpm
Flow Rate @ 25 psi Pressure Drop	10.0 gpm	10.1 gpm	11.9 gpm	12.1 gpm
Back Wash Flow Rate	2.4 gpm	3.5 gpm	4.0 gpm	5.0 gpm
Shipping Weight	154 lbs	171 lbs	214 lbs	232 lbs
Regeneration Type	Counter Current / Up Flow			
Plumbing Connections	¾" or 1"			
Resin Type	Aquifine 8% High Capacity Ion Exchange Resin			
Carbon Type	Canature Catalytic Carbon			
Electrical Requirements	Input 120V 60 Hz - Output 12V 650mA			
Water Temperature	Min 39 - Max. 100 degrees Fahrenheit			
Water Pressure	Min. 20 - Max. 125 psi			



7 Year Warranty Control Valve



Lifetime Warranty Pressure tank



WQA Tested & Certified to NSF/ANSI 44 for effective reduction of hardness as verified and substantiated by test data.