

LITHOFOUNT 555

Web Fountain Solution

Litho Fount 555 is Formulated with a robust wetting / lubricating package, stabilized pH and extra desensitizers to over come many of today issues caused by inconsistent materials. Lower solvency with increased lubrication helps assure reduced paper and ink breakdown, minimizing the build up of contaminants that can de-stabilize fountain solutions, causing print issues. Contains calcium deposit inhibitor to keep fount from weakening.

- Made with multiple, extra desensitizers
- Formulated to maintain quality with stability in print
- Contains lubricators to stabilize wetting & keep blankets cleaner
- Good dot fidelity with dense colors.
- Stable pH and conductivity
- Multiple, bio slime inhibitors
- Contains corrosion inhibitors to protect press parts

Direction For Use:

Recommended dosage range - 3 oz. to 5 oz. per gallon.
Conductivity per ounce 300 micromhos.
We recommend starting with 3.5 oz./gallon.
Once running, adjust dosage up or down as needed.



Recommended dosage range 2.5% to 4%.
Conductivity per 1% is 384 micromhos.
We recommend starting with 3%, adjusting dosage up or down as needed.

Specifications:

VOC content lb. / gallon	0.8
VOC content grams / liter	95.9
Flashpoint	200°F
Color	Colorless
CA. Compliant	Yes

Available In:

Product Code	Unit	Case Qty.
10555E	5 Gallons (18.9 ltr)	Each
10555G	55 Gallons (208 ltr)	Each
10555T	275 Gallons (1040 ltr)	Each



VOC COMPLIANT Air Quality Management District Compliant

