

# UNIVERSAL #1

## Fountain Solution for Polyester Plates

Universal #1 permits a stable ink/water balance to be achieved using both polyester and metal plates. This means cleaner and faster start-up, less ink breakdown and less ink build-up on metering roller or blankets.

Universal #1 keeps a good film of water on the plate background while ensuring good plate desensitization. When changing from Polyester to metal plates or visa versa, no changes are necessary. Use the same dosage and start the press.

- Inhibits excess water pick up in inks
- More salable sheets, faster start-up
- Inks print and stay dense
- Eliminates tinting / build-up of ink on metering rollers and blankets

### Direction For Use:

Recommended dosage range - 4oz. to 8 oz. per gallon.  
Conductivity per ounce is 175 micromhos.  
We recommend starting with 5 oz./gallon.  
Once running, adjust dosage up or down as needed.



Recommended dosage range 3% to 6%.  
Conductivity per 1% is 225 micromhos.  
We recommend starting with 4%, adjusting dosage up or down as needed.

### Specifications:

VOC content lb. / gallon	0.4
VOC content grams / liter	44
Flashpoint	120°F
Color	Colorless
CA. Compliant	Yes

### Available In:

Product Code	Unit	Case Qty.
10364D	1 Gallon (3.785 ltr)	4
10364E	5 Gallons (18.9 ltr)	Each
10364F	30 Gallons (113.6 ltr)	Each
10364G	55 Gallons (208 ltr)	Each
10364T	275 Gallons (1040 ltr)	Each

