

ALCOMI 3368 NEUTRAL TE

Meets FOGRA Specs for Heat-Set Applications

Alcomi 3368 Neutral TE provides consistency in water speeds. Low solvent content assures reduced paper coating and ink breakdown, which aids in minimizing the build up of contaminants that will ultimately destabilize fountain solution and cause inconsistent image reproduction. Alcomi 3368 Neutral TE is formulated with a robust wetting / lubricating package, stabilized pH and desensitizers to provide ideal plate conditions to facilitate sharp open screens and reverses. In addition, printing blankets will remain cleaner without attracting heavy build up.

- Quick plate clean ups on start-ups and start / stop
- Excellent plate protection / wetting during print runs
- Excellent protection for CtP plates
- Compatible with all Kodak plates
- Excellent dot fidelity with dense / bright colors
- 100 % IPA Free
- No requirement for special IPA Free rollers
- Fogra, Blue Angel and Nordic Swan compliant
- Easy installation and operating conditions
- Low paper waste on start-ups and stops / starts

Direction For Use:

If Dosing by Ounces:
Dosage range is 2.5 oz. to 5 oz. / gal of mixed fount solution
Recommended starting dosage is 2.5 oz. / gal
Conductivity per ounce is approximately 234

Specifications:

VOC content lb. / gallon	1.05
VOC content grams / liter	125
Flashpoint	None
Color	Colorless
CA. Compliant	Yes



Fogra, Blue Angel and Nordic Swan Compliant
No.30249



If Dosing by (%) Percentage:

Dosage range is 2% to 4% / gal of mixed fountain solution
Recommended starting dosage is 2%
Conductivity per 1% is approximately 300

Available In:

Product Code	Unit	Case Qty.
10650D	1 Gallon (3.785 ltr)	4
10650E	5 Gallons (18.9 ltr)	Each
10650G	55 Gallons (208 ltr)	Each
10650T	275 Gallons (1040 ltr)	Each



VOC COMPLIANT Air Quality Management District Compliant

