

ALCOMI 3368-K

High Speed Web Fountain Solution

Alcomi 3368-K provides consistency in water speeds. Low solvent content assures reduced paper coating and ink breakdown which aids in minimizing the build up of contaminants that will ultimately de-stabilize fountain solution and cause inconsistent image reproduction. Alcomi 3368-K is formulated with a robust wetting/lubricating package, stabilized pH and desensitizers to provide ideal plate conditions to facilitate sharp open screens and reverses. In addition, printing blankets will remain cleaner without attracting heavy build up.

- Web fount
- High speed fount / fast start-ups, minimize paper waste
- Contains corrosion inhibitors to protect press parts
- Good dot fidelity with dense colors
- Excellent protection for CtP plates
- Reduces fountain tank contamination
- Less buildup on blankets
- Creates a stable printing environment

Direction For Use:

Recommended dosage range - 3 oz. to 5 oz. per gallon.
Conductivity per ounce is 200 micromhos.
We recommend starting with 3.5 oz./gallon.
Once running, adjust dosage up or down as needed.



Recommended dosage range 2.5% to 4%.
Conductivity per 1% is 250 micromhos.
We recommend starting with 3%, adjusting dosage up or down as needed.

Specifications:

VOC content lb. / gallon	0.6
VOC content grams / liter	68
Flashpoint	>200°F
Color	Colorless
CA. Compliant	Yes

Available In:

Product Code	Unit	Case Qty.
10361E	5 Gallons (18.9 ltr)	Each
10361G	55 Gallons (208 ltr)	Each
10361T	275 Gallons (1040 ltr)	Each



VOC COMPLIANT Air Quality Management District Compliant

