

FLEXO WASH V

Flexographic Cleaner

For heavy duty cleaning of UV/Energy curable, solvent & water based inks. Where other washes are slow or fail, this dedicated UV cleaner will work. Removes ingrained pigments from cells and other needed areas. Can be diluted from 1 to 3 up to 1 to 6 parts water. This concentration allows you to choose the dilution rate that best fits your needs.

- Powerful cleaning
- Water miscible
- Suitable for use in Ultrasonic cleaning bath
- Low alkalinity is less aggressive on equipment and users

Directions For Use:

Begin at full strength to gauge performance; then dilute out at 1-3 parts water and gauge performance. Determine an ideal ratio (up to 1-6 parts water). MIX with water at a ratio of 1-3, and run the ultrasonic tank without heat. The Flexo Wash V formula was developed to provide best results at around 100°F.

Specifications:

VOC content lb. / gallon	7
VOC content grams / liter	839
Flashpoint	180° F
Color	Clear
CA. Compliant	No



Available In:

Product Code	Unit	Case Qty.
F10275C	Qt. (.946 ltr)	6
F10275D	1 Gallon (3.785 ltr)	4
F10275E	5 Gallons (18.9 ltr)	Each
F10275G	55 Gallons (208 ltr)	Each

