



Setup for Bluetooth start/stop logging switch.

There is an optional extra Bluetooth start/stop logging switch available for use with the HD2 (RLACS224). This can be purchased from our online store. This button is designed for in car use, with a range of around 2 m.

The device will automatically connect to the unit when turned on. The pairing of the Bluetooth logging switch uses the button's MAC code, its own unique identifier, which is individual to that particular switch. This ensures that in busy areas, there can be no confusion or accidental pairing to an incorrect unit.

In order to pair the Bluetooth start/stop logging switch with the HD2 unit, the correct setting must be firstly selected within VBOX Video Setup software.

1. Firstly, power up VBOX Video HD2.
2. Insert the SD card in to a computer and open VBOX Video Setup software.
3. Add a new scene or select a previously saved scene by selecting the 'File' button.
4. Select '**Settings**' and click on '**General**'.
5. Select '**Bluetooth**', ensure that '**Enable button**' is ticked.

A screenshot of the VBOX Video Setup software interface. At the top, there is a blue Bluetooth icon and the text 'Configure the bluetooth settings.' Below this is a grey header bar with the word 'Bluetooth'. The main content area contains the text: 'If using an external Bluetooth start/stop logging switch, this option will need to be enabled.' followed by a blue hyperlink: 'Further information on the operation of this switch can be found here: [VBOX Video HD2 - Bluetooth start / stop logging switch](#)'. Below the text is a checkbox labeled 'Enable button' which is checked and highlighted with a red rectangular box. At the bottom, there is a label 'Mark button mode' followed by a dropdown menu currently showing 'Event marker'.

6. Save to the SD card and remove.