

## Part Number: 1673A

50 Ohm Microwave, RG402, 19 AWG SPCCS, Unjacketed



### Product Description

50 Ohm, RG-402/U type, 19 AWG solid .036" silver-plated copper-covered steel conductor, TFE Teflon® insulation, copper-tin composite shield (100% coverage), unjacketed.

### Technical Specifications

#### Product Overview

|                      |                              |
|----------------------|------------------------------|
| Environmental Space: | Indoor (Not Riser or Plenum) |
|----------------------|------------------------------|

#### Physical Characteristics (Overall)

##### Conductor

| AWG | Stranding | Material                                   | Nominal Diameter | No. of Coax |
|-----|-----------|--|------------------|-------------|
| 19  | Solid     | SPCCS - Silver Plated Copper Covered Steel | 0.036 in         | 1           |

|                  |    |
|------------------|----|
| Conductor Count: | 1  |
| AWG Size:        | 19 |

##### Insulation

| Material                  | Material Trade Name | Nominal Diameter |
|---------------------------|---------------------|------------------|
| TFE - Tetrafluoroethylene | Teflon®             | 0.116 in         |

##### Outer Shield Material

| Type  | Layer | Material             | Coverage [%] |
|-------|-------|----------------------|--------------|
| Tape  | 1     | Copper Foil          | 100 %        |
| Braid | 2     | Tin-Filled Composite | 100 %        |

##### Outer Jacket Material

| Material   |
|------------|
| Unjacketed |

#### Electrical Characteristics

##### Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR | Outer Conductor DCR |
|-----------------------|--------------------------|---------------------|
| 20.5 Ohm/1000ft       | 4.5 Ohm/1000ft           | 4.5 Ohm/1000ft      |

##### Capacitance

| Nom. Capacitance Conductor to Shield |
|--------------------------------------|
| 29.5 pF/ft                           |

##### Inductance

| Nominal Inductance |
|--------------------|
| 0.07 µH/ft         |

##### Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 50 Ohm                           |

##### High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
|-----------------|---------------------|

|           |               |
|-----------|---------------|
| 500 MHz   | 8 dB/100ft    |
| 1000 MHz  | 12 dB/100ft   |
| 2000 MHz  | 18.1 dB/100ft |
| 3000 MHz  | 22.9 dB/100ft |
| 5000 MHz  | 31 dB/100ft   |
| 7000 MHz  | 37.8 dB/100ft |
| 10000 MHz | 46.6 dB/100ft |
| 15000 MHz | 59.1 dB/100ft |
| 18000 MHz | 65.8 dB/100ft |
| 20000 MHz | 70 dB/100ft   |

#### Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.46 ns/ft    | 69.5 %                                   |

#### High Freq

| Frequency [MHz] | Max. Insertion Loss (Attenuation) |
|-----------------|-----------------------------------|
| 500 MHz         | 9.5 dB/100ft                      |
| 1000 MHz        | 14.5 dB/100ft                     |
| 3000 MHz        | 26.5 dB/100ft                     |
| 5000 MHz        | 36 dB/100ft                       |
| 10000 MHz       | 54 dB/100ft                       |
| 20000 MHz       | 84 dB/100ft                       |

#### Power Rating

| Frequency [MHz] | Max. Power Rating [W] | Nominal Power Rating [W] |
|-----------------|-----------------------|--------------------------|
| 500 MHz         | 600 W                 | 600 W                    |
| 1,000 MHz       | 401 W                 | 401 W                    |
| 2,000 MHz       | 268 W                 | 268 W                    |
| 3,000 MHz       | 211 W                 | 211 W                    |
| 5,000 MHz       | 157 W                 | 157 W                    |
| 7,000 MHz       | 129 W                 | 129 W                    |
| 10,000 MHz      | 105 W                 | 105 W                    |
| 15,000 MHz      | 83 W                  | 83 W                     |
| 18,000 MHz      | 74 W                  | 74 W                     |
| 20,000 MHz      | 70 W                  | 70 W                     |

#### Voltage

| Non-UL Voltage Rating | UL Voltage Rating |
|-----------------------|-------------------|
| 1900V RMS             | 30V RMS           |

#### VSWR

| Element                   | Max. VSWR |
|---------------------------|-----------|
| Ramp Function, End Points | 1.1:1     |
|                           | 1.3:1     |

#### Temperature Range

|                       |                 |
|-----------------------|-----------------|
| Non-UL Temp Rating:   | 200°C           |
| UL Temp Rating:       | 105°C           |
| Operating Temp Range: | -70°C To +200°C |

#### Mechanical Characteristics

|                                      |               |
|--------------------------------------|---------------|
| Bulk Cable Weight:                   | 26 lbs/1000ft |
| Max Recommended Pulling Tension:     | 70 lbs        |
| Min Bend Radius During Installation: | 0.25 in       |
| Min Bend Radius During Operation:    | 0.75 in       |
| Min Bend Radius/Installation:        | 0.25 in       |
| Min Flexing Radius:                  | 0.75 in       |

#### Standards

|               |                |
|---------------|----------------|
| UL AWM Style: | UL Style 10245 |
| RG Type:      | RG-402/U Type  |

## Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-01-01                    |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                           |
| MII Order #39 (China RoHS):           | Yes                           |

## Suitability

|                       |     |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

## Flammability, LSOH, Toxicity Testing

|                     |                 |
|---------------------|-----------------|
| Other Flammability: | Horizontal Wire |
|---------------------|-----------------|

## Part Number

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

## Variants

| Item #       | Color | Footnote |
|--------------|-------|----------|
| 1673A TIN100 | TIN   | C        |
| 1673A TIN250 | TIN   | C V      |
| 1673A TIN50  | TIN   |          |
| 1673A TIN500 | TIN   |          |

|           |  |
|-----------|--|
| Footnote: | C - CRATE REEL PUT-UP.   |
| Footnote: | V - 250' PUT-UP EXACT LENGTH MAXIMUM OF 3 PIECES, MINIMUM LENGTH 50'. 500' PUT-UP EXACT LENGTH MAXIMUM OF 5 PIECES, MINIMUM LENGTH 50'. 1000' PUT-UP EXACT LENGTH MAXIMUM OF 8 PIECES, MINIMUM LENGTH 50'. |

## Product Notes

|        |   |
|--------|---|
| Notes: | Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---|

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.