



**Newlink FAS L Hangers**

- Convenient Sizes: 4", 6", 8", 12"
- Electro Zinc Resistant Finish
- NEC Approved
- NEWMAX-25 Year Certification available (\*)

**Technical Specifications**

<b>Steel</b>	<b>(Min. Yield = 33KSI) (35 KSI for Stainless)</b>
<b>Plain</b>	Hot rolled pickled and oiled steel per ASTM A569 or A570
<b>Pre-Galvanized</b>	Mill galvanized steel per ASTM A653 CS or SS G90
<b>Hot Dip Galvanized After Fabrication</b>	Plain steel which is hot dipped after fabrication per ASTM A123
<b>Stainless Steel</b>	Type 304 or 316L fully annealed stainless steel
<b>NEC Permitted (types of cables)</b>	<ul style="list-style-type: none"> <li>○ Power and Control Tray Cable (Type TC) - NEC Article 336</li> <li>○ Power Limited Tray Cable (Type PLTC) - NEC Sections 725-61© and 725.82(E)</li> <li>○ Instrument Tray Cable (Type ITC) - NEC Article 727</li> <li>○ Optical Fiber Cables - Article 770</li> <li>○ Fire Alarm Circuit Conductors - Article 760</li> <li>○ Communication Cables - Article 800</li> <li>○ Mineral Insulated (MI)Cable - Article 332</li> <li>○ Metal Clad (MC) Cable - Article 330</li> </ul>

**Ordering Information:**

<b>P/N</b>	<b>Description</b>	<b>Includes</b>	<b>Set</b>	<b>Finish</b>
NEW-8504050	NEW-L Hanger 4"	L Bracket	1	Galvanized
NEW-8506050	NEW-L Hanger 6"	L Bracket	1	Galvanized
NEW-8508050	NEW-L Hanger 8"	L Bracket	1	Galvanized
NEW-8512050	NEW-L Hanger 12"	L Bracket	1	Galvanized

(\*) NEWMAX-25 Year Certification applies when a complete Newlink Cabling Channel is installed.