

Nissan Rogue 2014-2019

PART NUMBER: MV-25-03-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Cordless Drill, Phillips head tip

PARTS INCLUDED: VSM G3, J-Stem, Lock Plate, 2-#6 x 1/2

LOCATION: Right of radio



Step 1: Locate the seam just below the climate controls, use the DTRT and your hand to pop loose the climate controls. Just lay flat in front of the shifter.

Step 2: On the right hand side, position mount just below the bottom line of the radio and tight to the right edge of the bezel opening (pic2). Mark the location of the bottom 2 screw holes of the mount. Now either pre-drill pilot holes or using a cordless drill with the Phillips head tip and screw in the 2 screws provided.

Step 3: Pop back on the climate controls.

Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

View Instructions &
Updates Online at
www.pro-fit-intl.com