2016-2019 Honda Civic

PART NUMBER: TY-52-09-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drives seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Electric Screw Driver OR Cordless Drill, Phillips Screw tip

PARTS INCLUDED: VSM G3, Lock Plate, J-stem, 2-#8 x 1/2" screw


LOCATION: Right of Screen

Step 1: Using a DTRT remove the remove the 2 trim bezels that go along each side of the shifter and up to along the radio and climate controls. Held with retainer clips. Now remove the climate controls. Do not disconnect wires from climate control.

Step 2: Remove the 2 screws holding the radio on the underside of the radio. On the under side of the radio the climate control wires are held to the bottom of the radio, by pinching the clip pop out the clip. Now pull out the radio. No need to disconnect wires from radio.

Step 3: Position mount along the outer

Right edge of the opening (pic.3). The mount will be between the passenger dash and the right trim bezel that was removed in step 1. Mark screw locations and drill a pilot hole or just screw in the 2 provided screws using cordless drill.





Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073



Advanced