

Stock Tractor Rules

(All general rules apply)

- **Must follow contest rules.**
- **Only farm tractors with rubber tires. No cut tires, duals, 4WD's, chains, etc.**
- **No nitrous or propane.**
- **Hitching point to be a minimum of 20" from center of axle and a maximum of 20" high. Drivers must furnish a clevis or hitch point with at least 3.5 inch hole.**
- **No portion of tractor may interfere with sled or hitching the sled.**
- **Weights must be secured. Loss of weights will lead to immediate disqualification. No weights shall extend more than 12" from the tire. No protruding bolts will be allowed anywhere. No weight frame or weights may extend 24" beyond forward point of tractor.**
- **Tractors must have a hood and grill and have working brakes.**
- **Wheelie bars are highly recommended but not required.**
- **One adequately shielded factory sized turbocharger allowed.**
- **Must have an OEM block that could have been purchased new in the tractor with no visual modifications.**
- **No water injection allowed.**
- **All tractors must have straight vertical stack or factory exhaust.**
- **Must have engine side shields that are solid .125 aluminum or 12 gauge steel.**
- **Side shields must be complete length of the block and from the hood to 2 inches below the crankshaft throw. Side shields must be securely fastened and must be removable or hinge out of the way for inspection.**
- **Maximum rotary pump not to exceed 13 mm. Must be stock appearing.**
- **Front wheels off the ground 25" will be deemed unsafe by judges.**