

NP-2511D / NP-3511D

High speed

Lock-free Cutter

Thick Paper

Speed 200mm/sec. , -20°C~60°C

NP-3511D



*LED Bezel is an option

- Operating temp: -20°C~60°C
- High repeatability of 16 gray scale,
2D barcode printing (QR code (model2), PDF417)
- Lock-free cutter
- Paper thickness: 59~150μm
- Optional LED Bezel is attachable

NP-2511XD / 3511XD

High speed

Lock-free Cutter

Thick Paper

Paper Drop in type

NP-3511XD



Model name	NP-2511D / NP-2511XD			NP-3511D / NP-3511XD		
Print method	Direct line thermal dot					
Print speed	Max. 200mm/sec.					
Resolution	8dots/mm (203dpi)					
Number of dots/ line	416dots (Default)	432dots	448dots	576dots (Default)	560dots	640dots
Paper width	58mm(Default)	60mm	60mm	80mm (Default)	76mm	80mm
Print width	52mm(Default)	54mm	56mm(Max.)	72mm (Default)	70mm	80mm(Max.)
Paper diameter	Max.φ83mm					
Character	International, English, Greek, Polish, Russian, Scandinavian, Turkish, Chinese, Japanese					
Barcode	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODABAR, CODE128, QR code (model2), PDF417					
Interface	USB (V2.0 full speed) and Serial (RS232C)					
Cutter	Full cut and Partial cut (by command)					
Operating voltage	DC24V (NP-2521:DC12V)					
External dimensions	NP-2511/ NP-2521:106(W)x150(D)x75(H)mm			NP-3511:127(W)x150(D)x75(H)mm		
	NP-2511X:106(W)x170(D)x80(H)mm			NP-3511X:127(W)x170(D)x80(H)mm		