

“VINCO” LED PANEL LIGHT (Model: PLCV)

FEATURES:

- High efficiency LED
- Ultra thin casing design
- Multiple choices of shapes and sizes
- Reliable power supply ensures long lifetime and consistent performance

SPECIFICATIONS:

PARAMETERS	PLCV-60	PLCV-120	PLCV-180
System Power	6W	12W	18W
LED Chips/Packages	Epistar		
Color Temperature (CCT)	3000K, 4000K, 6000K		
CRI	80 Ra		
Luminous Flux	480 lumen	960 lumen	1450 lumen
Luminous Efficacy	80 lm/W		
Input Voltage	90-305 VAC (220VAC nominal), 50/60Hz		
Power Supply Efficiency	>90%		
Dimming	Non-dimmable (Dimming option is available)		
Beam Angle	120 Degrees		
Design Life	30,000 hours		
Housing Color	White (Power Coating)		
Housing Material	Diecast Aluminum		
Diffuser Material	Polycarbonate (frost)		
Net Weight	Round: 190g Square: 180g	Round: 330g Square: 360g	Round: 480g Square: 540g
Product Dimension (mm)	Round: D120*H12 Square: L110*W110*H12	Round: D170*H12 Square: L172*W172*H12	Round: D225*H12 Square: L225*W225*H12
Cuthole Size (mm)	Round: D105 Square: L95*W95	Round: D155 Square: L155*W155	Round: D205 Square: L205*W205

REVISION: 7

Date: 2017.10.01

Title: “VINCO” LED PANEL LIGHT

Model: PLCV

SHEET No: 1 of 2

Version: 6.0

“VINCO” LED PANEL LIGHT (Model: PLCV)

PRODUCT PHOTOS:



PHOTOMETRIC CURVES:

