

## “VINCO” LED TRACK LIGHT (Model: TLCV)

### FEATURES:

- ADJUSTABLE INSTALLATION BRACKET TO FIT IN VARIOUS CEILING CUTOUT SIZES
- Slim, yet robust housing design
- Thermal plastic housing
- Designed for commercial lighting; offices, hotels, shopping malls, restaurants, etc

### SPECIFICATIONS<sup>+</sup>:

Models	TLCV-250	TLCV-300
System Power	25W	30W
Color Temperature (CCT)	3000K, 4000K, 5000K, 5700K, 6500K (standard model)	
CRI	80 Ra	
Luminous Flux	2500 lm	3000 lm
Luminous Efficacy	100 lm/W	
Input Voltage	85-265 Vac (220VAC nominal), 50/60Hz	
Power Supply Efficiency	90%	
Dimming	Non-dimmable (Dimming option is available)	
Beam Angle	30 Degrees	
Design Life	40,000 hours	
Housing Color	Black (Power Coating)	
Housing Material	Thermal plastic	
Diffuser Material	Glass	
Housing Shape	Round	
Product Size	Ø93xH170mm	Ø93xH180mm

<sup>+</sup> Product specifications are subject to changes without notice.

REVISION: 1

Date: 2017.10.01

Title: “VINCO” LED TRACK LIGHT

Model: TLCV

SHEET No: 1 of 2

Version: 1.0

## “VINCO” LED TRACK LIGHT (Model: TLCV)

### PRODUCT PHOTOS:



### ORDERING INFORMATION: e.g., TLCV-30030N-8030

Series		Wattage		Color Temperature (CCT)		Dimming		CRI		Beam Angle	
TLCV	“VINCO”	250	25W	30	3000K	N	Non-dimmable	80	80 Ra	30	30 DEG
		300	30W	40	4000K	D	Dimmable				
				5057	5000K						
				65	5700K						
					6500K						

REVISION: 1

Date: 2017.10.01

Title: “VINCO” LED TRACK LIGHT

Model: TLCV

SHEET No: 2 of 2

Version: 1.0