

INI-TS-IG2000-ICMF

IntelliGEN™ 2000 Flex-Fuel Generator (IG2000)

(Made in the USA, U.S. Patent 9,175,601, U.S. Patent 9,188,033, and other U.S. and foreign patents pending)



Specs

- Start System: Manual Recoil Start
- Max Peak Output: 2000W (Sea Level)
(Gasoline and JP-8/F-24)
- Gasoline Nominal Output: 1600W (Sea Level)
- Gasoline Nominal Voltage: 110-240VAC, 50 or 60Hz, 12VDC
- JP-8/F-24 Nominal Output: 1250W (Sea Level)
- JP-8/F-24 Nominal Voltage: 110-240VAC, 50 or 60Hz, 12VDC
- AC Output Power outlets: Customer Specified
- DC Output Power outlets: 12V 8A (1)
- Dry Weight: 44.7 lb. (20 kg)
- Dimensions: 20.5" x 14.5" x 17.9"
(521 mm x 369 mm x 455 mm)
- Operating Temp: -4°F to 122°F / -20°C to 50°C
- Storage Temp: -40°F to 176°F (-40°C to 80°C)
- Operating Elevation: Sea Level to 10,000 ft.
(3048 m)
- Internal Tank: 1.1 gal (4.1 L), Quick connect for compressed fuels
- Color: CARC Tan or Green

Features

- Can use multiple fuel types (JP-8/F-24, F-34 "NATO", gasoline, propane, methanol, isopropanol)
- Lightweight, "One Man Portable"
- Quiet, small noise signature
- Plug-in compatible with Trinity™ Systems or stand-alone
- Immediate functionality on startup - No waiting
- Auto turn down when load is low
- 2,000 hour rated lifetime, low maintenance
- 2,000 hour/2 year limited warranty (repair or replace)
- Tunable for high elevation

INI-TS-IG2000-ICMF Includes

- 1 x IntelliGEN™ 2kW Flex-Fuel Generator v2.5
- 1 x Initial Oil Charge
- 1 x Exhaust Tubing Kit, 12.5 ft. (3.8 m)
w/ Clamp/Thumbscrew
- 1 x Operator Manual
- 2 x Cold Start Canisters*
- 1 x Quick Reference Card
- 1 x Maintenance Kit
- 2 x 10w40 Small Engine Oil
- 1 x (Parallel) "Y" Cable (W/ Adaptor)
- *Cold Start Canisters will be removed for AIR SHIPMENTS

