PORTABLE REBAR
BENDERS and CUTTERS

FASCUT®



FS-600 Bender Cutter Combo



FR-800-C Bender Cutter Combo



FR-800 Bender Only



FC-800 Cutter Only

MADE IN THE U.S.A. WITH PRIDE

Quickly cut and bend rebar at job sites or in your shop

www.fascut.com

Specifications				
	FS-600 Bender Cutter Combo	**FR-800-C Bender Cutter Combo**	**FR-800 Bender Only**	**FC-800 Cutter Only**
Bender Capacity Grade 60	1 bar - #6, #5, or #4 2 bars - #3	1 bar - #8, #7, or #6 2 bars - #5 3 bars - #4 4 bars - #3		n/a
Bending Speed	2-4 seconds	2 seconds/90° up to #5 bar and 7 seconds/90° up to #8 bar		n/a
Bend Angle Control	0 - 130°, infinitely variable with accurate repeat	0 - 190°, infinitely variable with 2 presets and accurate repeat Optional Programmable Angle Control available		n/a
Bender Method	Three point bending system	Rotary Turntable		n/a
Bend Die Diameters	2-1/2" and 3-3/4"	1-1/2", 3", 4-1/2", 6"		n/a
Cutter Capacity Grade 60	1 bar - #6 or #5 2 bars - #4 3 bars - #3	1 bar - #8, #7, or #6 2 bars - #5 3 bars - #4 4 bars - #3	n/a	1 bar - #8, #7, or #6 2 bars - #5 3 bars - #4 4 bars - #3
Cutting Speed	2-4 seconds	2-4 seconds	n/a	2-4 seconds
Cutter blade edges	8 usable sides	4 usable sides	n/a	4 usable sides
Operation Control	Push Button or optional Foot Pedal Automatic return on release	Foot Pedal Automatic return on release		Push Button or optional Foot Pedal Automatic return on release
Voltage	110-120 volts standard. 220-240 volts optional. 50/60 cycles, single phase			
Amperage	14 @ 110v / 7 @ 220v			
Power Supply	Two stage hydraulic pump driven by a 1 HP continuous duty electric motor			
Dimensions	26"L x 13"W x 16"H	32"L x 24"W x 31"H	32"L x 18"W x 31"H	26"L x 13"W x 18"H
Weight	180 pounds	390 pounds	290 pounds	190 pounds
Reference Fence Attachment	Optional - Adjustable material stop out to 4 feet			
Programmable Angle Control Option	n/a	 Holds up to 6 angles in memory and automatically sequences through them as the shape is being formed. Unplug and remove when not needed to use the standard manual angle control on the machine.		n/a

Features and specifications are subject to change without notice.

Fascut Industries has manufactured reliable rebar cutting and bending equipment in the U.S.A. since 1979.

FASCUT INDUSTRIES INC.

7248 INAMA RD.
SAUK CITY, WI 53583
TEL: 608-643-6678 FAX: 608-643-2682
E-MAIL: info@fascut.com WEB: www.fascut.com