



**T/S (Thiele/Small)
Parameter**

XTR-250D2N & D4N

XTR-250 D2N

Size: 250mm(10")
Rms: 750 W
Peak: 1500 W
Fms: 41.4 Hz
Res: 157.9 Ohm
Re: 4.0 Ohm
Qms: 4.35
Qes: 0.36
Qts: 0.33
Rms: 13.1 kg/s
Cms: 0.07 mm/N
Mms: 291.0 gr
Nref: 0.20 %
Bl: 25.1N/A
SPL: 84.9 dB
VAS: 10.3L
Rp: 46.7 Ohm
Lp: 37.0 mH
Cp: 534.3 uF
Le: 2.14 mH

XTR-250 D4N

Size: 250mm(10")
Rms: 750 W
Peak: 1500 W
Fms: 41.4 Hz
Res: 157.9 Ohm
Re: 4.0 Ohm
Qms: 4.35
Qes: 0.36
Qts: 0.33
Rms: 13.1 kg/s
Cms: 0.07 mm/N
Mms: 291.0 gr
Nref: 0.20 %
Bl: 25.1N/A
SPL: 84.9 dB
VAS: 10.3L
Rp: 46.7 Ohm
Lp: 37.0 mH
Cp: 534.3 uF
Le: 2.14 mH



+ 358 9 8700 200

FIN-01300 Sinikellontie 8, Vantaa

flextron@spldynamics.fi