

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

SECTION 1. IDENTIFICATION

Product name : SILASTIC™ 3496 Mould-Making Base
Product code : 04014375

Manufacturer or supplier's details

Company Identification : THE DOW CHEMICAL COMPANY
2030 DOW CENTER
MIDLAND MI 48674-0000
UNITED STATES

Telephone : 800-258-2436

24-Hour Emergency Contact : Chemtrec +1 800-424-9300

Local Emergency Number : 800-424-9300

E-mail address : SDSQuestion@dow.com

Recommended use of the chemical and restrictions on use

Recommended use : Polymer

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H361f Suspected of damaging fertility.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Silicone elastomer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Hexamethyldisilazane reaction with Silica	68909-20-6	>= 24 - <= 26
Zircon	14940-68-2	>= 5 - <= 6
Octamethylcyclotetrasiloxane	556-67-2	<= 0.1252

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Suspected of damaging fertility.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

|| Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- || Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- || Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde
Nitrogen oxides (NO_x)
Sulfur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
-

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid inhalation of vapor or mist.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hexamethyldisilazane reaction with Silica	68909-20-6	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
Zircon	14940-68-2	TWA	5 mg/m ³ (Zirconium)	OSHA Z-1
		TWA	5 mg/m ³ (Zirconium)	ACGIH
		STEL	10 mg/m ³ (Zirconium)	ACGIH
		TWA	5 mg/m ³ (Zirconium)	NIOSH REL
		ST	10 mg/m ³	NIOSH REL

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Octamethylcyclotetrasiloxane	556-67-2	TWA	(Zirconium) 10 ppm	US WEEL
------------------------------	----------	-----	-----------------------	---------

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Hexamethyldisilazane reaction with Silica

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Chemical customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : off-white

Odor : slight

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 100 °C

Flash point : > 100 °C
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not applicable

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version Revision Date: SDS Number: Date of last issue: 03/14/2017
6.0 10/18/2017 1521468-00007 Date of first issue: 03/19/2015

Relative vapor density : No data available

Relative density : 1.15

Solubility(ies)
 Water solubility : No data available

Partition coefficient: n-
 octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
 Viscosity, dynamic : 25,000 mPa.s

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- : Can react with strong oxidizing agents.
 tions : When heated to temperatures above 150 °C (300 °F) in the
 : presence of air, product can form formaldehyde vapors.
 : Safe handling conditions may be maintained by keeping vapor
 : concentrations within the occupational exposure limit for
 : formaldehyde.
 : See OSHA formaldehyde standard, 29 CFR 1910.1048
 : Formaldehyde may cause cancer. It is also toxic by inhalation,
 : skin absorption and ingestion, corrosive to skin and eyes, and
 : may cause skin sensitization and respiratory irritation.
 : Hazardous decomposition products will be formed at elevated
 : temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products
Thermal decomposition : Formaldehyde

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:

Hexamethyldisilazane reaction with Silica:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Zircon:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): 2975 ppm
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: On basis of test data.

Skin corrosion/irritation

Not classified based on available information.

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Ingredients:

Hexamethyldisilazane reaction with Silica:

Assessment: Repeated exposure may cause skin dryness or cracking.

Zircon:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: No skin irritation
Remarks: On basis of test data.

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

Hexamethyldisilazane reaction with Silica:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Zircon:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Species: Rabbit
Result: No eye irritation
Remarks: On basis of test data.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

Zircon:

Test Type: Maximization Test
Routes of exposure: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

||

Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test

Species: Guinea pig

Result: negative

Remarks: On basis of test data.

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Hexamethyldisilazane reaction with Silica:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Zircon:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: negative
Remarks: Based on data from similar materials

Octamethylcyclotetrasiloxane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: On basis of test data.

Test Type: Mutagenicity (in vitro mammalian cytogenetic test)
Result: negative
Remarks: On basis of test data.

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: On basis of test data.

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative
Remarks: On basis of test data.

Test Type: DNA damage and repair, unscheduled DNA syn-
thesis in mammalian cells (in vitro)

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Genotoxicity in vivo : Result: negative
Remarks: On basis of test data.

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (vapor)
Result: negative
Remarks: On basis of test data.

: Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: On basis of test data.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified based on available information.

Ingredients:

Zircon:

Species: Rat
Application Route: Ingestion
Exposure time: 103 weeks
Result: negative
Remarks: Based on data from similar materials

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility.

Ingredients:

Zircon:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Octamethylcyclotetrasiloxane:

- Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat, male and female
Application Route: inhalation (vapor)
Symptoms: Effects on fertility.
Remarks: On basis of test data.
- Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rabbit
Application Route: inhalation (vapor)
Symptoms: No effects on fetal development.
Remarks: On basis of test data.
- Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Ingredients:

Zircon:

Routes of exposure: inhalation (dust/mist/fume)
Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Octamethylcyclotetrasiloxane:

Routes of exposure: Ingestion
Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure: inhalation (vapor)
Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Routes of exposure: Skin contact
Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity

Ingredients:

Zircon:

Species: Rat
NOAEL: > 100.8 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 30 Days
Remarks: Based on data from similar materials

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Octamethylcyclotetrasiloxane:

Species: Rat
Application Route: Ingestion
Remarks: On basis of test data.

Species: Rat
Application Route: inhalation (vapor)
Remarks: On basis of test data.

Species: Rabbit
Application Route: Skin contact
Remarks: On basis of test data.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information

Ingredients:

Octamethylcyclotetrasiloxane:

Remarks: Results from a 2 year repeated vapor inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Zircon:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae : NOEC (Chlorella vulgaris (Fresh water algae)): > 200 mg/l
Exposure time: 15 d
Remarks: Based on data from similar materials

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Octamethylcyclotetrasiloxane:

- Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 0.0063 mg/l
Exposure time: 336 h
Remarks: No toxicity at the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility.
- Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l
Exposure time: 72 h
Remarks: No toxicity at the limit of solubility.
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l
Remarks: On basis of test data.
No toxicity at the limit of solubility.
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 0.0079 mg/l
Exposure time: 21 d
Remarks: On basis of test data.
No toxicity at the limit of solubility.

Ecotoxicology Assessment

- Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Persistence and degradability

Ingredients:

Octamethylcyclotetrasiloxane:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3.7 %
Exposure time: 28 d
Method: OECD Test Guideline 310
- Stability in water : Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7
Method: OECD Test Guideline 111

Bioaccumulative potential

Ingredients:

Octamethylcyclotetrasiloxane:

- Bioaccumulation : Species: Pimephales promelas (fathead minnow)
Bioconcentration factor (BCF): 12,400
- Partition coefficient: n-octanol/water : log Pow: 6.48 (25.1 °C)

Mobility in soil

No data available

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

Other adverse effects

Ingredients:

Octamethylcyclotetrasiloxane:

Results of PBT and vPvB assessment : Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACH Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.
- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylene glycol	107-21-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Reproductive toxicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9
Dimethyl siloxane, hydroxy-terminated	70131-67-8
Hexamethyldisilazane reaction with Silica	68909-20-6
Zircon	14940-68-2

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Zircon	14940-68-2
--------	------------

California Permissible Exposure Limits for Chemical Contaminants

Zircon	14940-68-2
--------	------------

The ingredients of this product are reported in the following inventories:

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

KECI : All ingredients listed, exempt or notified.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base




Version 6.0 Revision Date: 10/18/2017 SDS Number: 1521468-00007 Date of last issue: 03/14/2017
Date of first issue: 03/19/2015

- REACH : For purchases from Dow Chemical EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Chemical legal entities with the intention to export into EEA please contact your DC representative/local office.
- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- PICCS : Consult your local Dow Chemical office.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH	*	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average
US WEEL / TWA : Time weighted average

SAFETY DATA SHEET

SILASTIC™ 3496 Mould-Making Base



Version Revision Date: SDS Number: Date of last issue: 03/14/2017
6.0 10/18/2017 1521468-00007 Date of first issue: 03/19/2015

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/18/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8