

FANLESS & IP67 ENCLOSURES

WK347 IP67 System for CPU TDP < 15W Works under 75°C environment

- ◆ It work for 3.5" SBC
- ◆ The heat sink work for CPU TDP <10W under 75°C environment, or for TDP < 15W under 55°C environment
- ◆ Easy to install the HDD. System with removable HD access door. Just open the door, slid in the HD and done.
- ◆ System with Vent Vale, it can help release air pressure, hot air.
- ◆ We custom design all kinds of IP67 port to meet your requirement
- ◆ Quick develop time. Within 4~6 weeks, we can deliver the sample.



Aewin EM-6336 SBC

Processor: Intel ® Atom™ E3815, E3826, E3845CPU

Memory: 1 x SO-DIMM DDR3L 1066/1333 up to 8GB

Watchdog timer: 1~255 sec.

Ethernet : 2 x Intel ® i210AT Gigabit Ethernet

SSD: 1x Half-size Mini-PCIe support mSATA

Storage: 1 x SATA 6.0 Gb/s

Digital I/O: 8 bit programmable

LPC: 1 x LPC support TPM module

Expansion Interface: 1 x Full-Size Mini-PCIe

1 x Half-size Mini-PCIe or mSATA

Power Requirement: DC 8V~32V

Display: 1 x HDMI 1 x VGA 1 x 24-bit LVDS

Serial Port: 1 x RS232/422/485 & 3 x RS232

USB Port: 1 x USB 3.0 + 2 x USB2.0

Audio: Line-In/Out, Mic-In

Aewin EM-6337 SBC

Processor: Intel ® 5th generation CPU

i7-5650U, i5-5350U, i3-5010U

Memory: 1 x SO-DIMM DDR3L 1600 up to 8GB

Watchdog timer: 1~255 sec.

Ethernet : 1 x Intel ® i211AT + 1 x 218LM

SSD: 1x Half-size Mini-PCIe support mSATA

Storage: 1 x SATA 6.0 Gb/s

Digital I/O: 8 bit programmable

LPC: 1 x LPC support TPM module

Expansion Interface: 1 x Full-Size Mini-PCIe

1 x Half-size Mini-PCIe or mSATA

Power Requirement: DC 8V~32V

Display: Integrated 2 x HDMI, 1 x 24-bit LVDS

Serial Port: 1 x RS232/422/485 & 3 x RS232

USB Port: 2 x USB 3.0 + 4 x USB2.0

Audio: Line-In/Out, Mic-In

Model: WK347 Waterproof System

