

# EQUIPMENT SOLUTIONS



19 OCT- 18 DEC 2020

Alemlube proudly offers distributors and end users alike a complete portfolio of products providing solutions for all day, every day activities in Australian industry. Representing many of the world's leading equipment manufacturers and brands in the fields of lubrication & refuelling equipment, hose storage & retrieval solutions, spill containment products, automotive servicing equipment and oil storage, dispensing & monitoring equipment, Alemlube delivers quality, reliable and cost effective equipment solutions to improve your productivity.



**\$326.00**

SA400N

## Alemlube S Series Air Hose Reel

- Working pressure of 300psi (20bar)
- 15m of 12mm ID hybrid polymer hose
- Automatic and positive latching mechanism
- 1/2" BSP(f) inlet & outlet

**SA300N** also available with 18m x 10mm ID hybrid polymer hose & 0.9m lead in hose and 3/8" BSP(f) inlet/outlet **\$307.00**



**\$268.60**

HR40040

## Alemlube EL Series Air Hose Reel

- Supplied with 15m x 12mm ID PVC hose and 0.9m lead in hose
- 1/2" BSP inlet/outlet
- Maximum working pressure of 300psi (20bar)
- Constant speed control device ensures safe hose assembly rewind

**HR40030** also available with 20m x 10mm ID PVC hose and 0.9m lead in hose and 3/8" BSP(f) inlet/outlet **\$244.50**



**\$2,529.00**

505224N

## Samoa Twin Pedestal Spring Rewind Oil Hose Reel

- Heavy duty full metal construction
- Hose capacity: 15m x 19mm ID
- Hose pressure rating 1,500psi (103bar)
- 3/4" BSP(f) inlet/outlet

**505232** also available with 20m x 12mm ID delivery hose and 0.8m lead in hose **\$2,413.00**



**\$3,612.00**

8080-G

## Alemite Large Capacity Hose Reel

- Suitable for use with air, water, oil and fuel
- Sealed and plated bearings
- 1,000psi (60bar) hose pressure rating
- Supplied complete with 15m x 25mm ID hose

**8080-F** also available with 25m x 19mm capacity reel **\$3,732.00**

Alemlube

## Lockable Diesel Refuelling Storage and Dispensing Kits

Part Number	Capacity	Flow Rate	W/Meter	Price
L10040PA	100L	50L/min	—	<b>\$1,159.00</b>
L20040PA	200L	50L/min	—	<b>\$1,239.00</b>
L45040PA	450L	50L/min	—	<b>\$1,696.00</b>
L60040PA	600L	50L/min	—	<b>\$1,847.00</b>

- Heavy duty, robustly constructed polyethylene tank
- Built in nozzle holster
- Lockable lid aids diesel fuel security and protects dispensing kit components
- Dispensing kit consists of a 12V pump, antistatic fuel delivery hose, 2 metre battery cables and auto nozzle
- Forklift lift points and tie down capability
- Tank baffles aid vehicle stability
- Suits all marques of single and twin cab utes



**DISTRIBUTED BY**  
**ONE STOP LUBRICATION EQUIPMENT**

francois@onestoplubrication.com Ph 0487 372 894





DISTRIBUTED BY

ONE STOP LUBRICATION EQUIPMENT

francois@onestoplubrication.com Ph 0487 372 894

REFUELLING

ONE STOP  
LUBRICATION EQUIPMENT



\$487.00

52001

### 24V Diesel Refuelling Tank Kit

- Flow rates of up to 50L/min
  - Including 4m of antistatic fuel hose, 2m of battery cable, and manual nozzle
  - Ideal for intermittent diesel refuelling applications
- 52001A** as above but with an automatic shut-off nozzle **\$718.00**



\$209.10

50000

### 12V Submersible Transfer Kit

- Capable of flow rates of up to 32L/min
- Suitable for diesel, water, coolant and oils up to SAE20
- Includes 4m of fuel delivery hose, 4m of battery cable with on/off switch & clamps and a manual nozzle

**50001** as above but 24V **\$209.10**



\$553.00

732000

### 240V Diesel Fuel Transfer Pump

- Flow rates of up to 72L/min
- Vane type pump with sintered steel rotor and acetylic resin vanes
- 1" BSP(f) inlet/outlet
- Ideal for diesel fuel transfer out of bulk tanks where 240V power is available



\$1,012.00

326000

### 240V High Volume Diesel Fuel Transfer Pump

- Flow rates of up to 100L/min
- Vane type pump with sintered steel rotor and acetylic resin vanes
- 1" BSP inlet/outlet
- Suitable for the transfer of diesel fuel
- Continuous running operation



\$385.00

F20020N

### Alemlube EL Series 12V Diesel Refuelling Tank Kit

- Flow rates of up to 38L/min
- Suction capacity of up to 2m
- Equipped with a 12V DC motor and supplied with suction & delivery hoses, battery cable with clamps, inlet filter and a manual plastic nozzle



\$487.00

52000

### 12V Diesel Refuelling Tank Kit

- Capable of flow rates of up to 50L/min
- Includes 4m of antistatic fuel delivery hose, 2m of battery cable, a stainless steel & brass fuel filter and a manual nozzle
- Suction capacity of up to 2m

**52000A** as above but 24V **\$718.00**



\$1,449.00

395050

### 240V Heavy Duty High Volume Diesel Pump

- Flow rate of up to 140L/min at end of hose & auto nozzle
- 1" BSP outlet thread, 1-1/4" BSP inlet thread
- Sintered steel rotor & acetal resin vanes
- Cast iron body with rust resistant coating



\$3,234.00

213000

### 24V Diesel Refuelling System

- Integrated dual 12V pumps deliver up to 45L/min
- Versatile, compact & easy to install pump, reel, filter and auto shut off nozzle kit simplifies diesel fuel transfer
- Hose reel supplied complete with 15m x 3/4" ID hose



\$2,160.00

50070

### 240V Diesel Fuel Dispenser

- Flow rates of up to 70L/min
- Includes a self priming vane pump, meter, intake filter, 4m of antistatic delivery hose, auto shut off nozzle, support bracket and built in nozzle holster

**50070P** as above but with mounting pedestal **\$2,730.00**



\$2,371.00

50090

### 240V Diesel Fuel Dispenser

- Flow rates of up to 90L/min
- 30 mins duty cycle, IP 45 protection grade
- Complete with self priming vane pump, 4-digit mechanical meter, 4m of antistatic delivery hose, and an automatic shut off nozzle with swivel connection

**50090P** as above but with mounting pedestal **\$2,940.00**



\$3,234.00

212000

### 12V Diesel Refuelling System

- Integrated dual 12V pumps deliver up to 45L/min
- Versatile, compact & easy to install pump, reel, filter and auto shut off nozzle kit simplifies diesel fuel transfer
- Hose reel supplied complete with 15m x 3/4" ID hose



\$2,592.00

339000

### 240V High Volume Diesel Pump

- Flow rates of up to 190L/min
- Self-priming rotary vane electric pump
- Maximum operating pressure of 58psi (4bar)
- 2" BSP(f) flanged inlet and outlet ports
- No power cable included, an electrician must hard wire



\$1,159.00

L10040PA

### Lockable Diesel Refuelling Storage and Dispensing Kit

- Heavy duty, robustly constructed polyethylene tank
- Built in nozzle holster
- Unique user friendly design with lockable lid to aid fuel and dispensing kit security
- Tank baffles aid vehicle stability
- Suits all marques of single and twin cab utes



\$1,326.00

6840EDN

### Mobile Diesel Storage and Dispensing Kit with 12V Electric Pump

- Flow rate of up to 40L/min
- Tank capacity of 68 litres
- 4 metre x 19mm ID PVC delivery hose
- Ergonomic grip for ease of handling and lifting
- Roto-molded linear polyethylene tank - impact resistant, UV stabilised



\$3,766.00

430TFD

### Portable Bunded Diesel Storage & 12V Dispensing Kit

- 12V Piusi By-Pass fuel pump dispenses up to 50L/min
- Auto shut off nozzle with 4m x 3/4" ID delivery hose
- Ideal for mine sites or other sites where only bunded tanks are allowed



\$5,410.00

M4400-ML

### Tool & Fuel Kit

- Fuel transfer rates of up to 40L/min
- Integrated tool box, fuel tank, 12V diesel fuel transfer pump and secure enclosed cabinet
- Two lockable sides provide tool and fuel pump security
- 400L fuel tank capacity
- Dimensions of 1,300mm (L) x 720mm (W) x 880mm (H)



\$1,142.00

6820HDN

### Mobile Diesel Storage and Dispensing Kit

- Flow rate of up to 20L/min
- Tank capacity of 68 litres
- Rotary drum pump can deliver up to 20L/min
- 3 metre x 19mm ID PVC delivery hose
- Ideal for topping up of ride on lawn mowers, small farm machinery, golf carts, jet skis, chain saws, motor bikes and snow mobiles



\$1,847.00

L60040PA

### Lockable Diesel Refuelling Storage and Dispensing Kit

- Flow rates of up to 50L/min
- 600L capacity
- Heavy duty, robustly constructed polyethylene tank
- Dispensing kit consists of a 12V pump, 4m antistatic fuel delivery hose, 2m battery cables and automatic nozzle





# DISTRIBUTED BY ONE STOP LUBRICATION EQUIPMENT

francois@onestoplubrication.com Ph 0487 372 894

## LUBRICANTS

### ONE STOP LUBRICATION EQUIPMENT



**\$1,957.00**

**ALE-20BAH  
3/4" Aluminium Diaphragm Pump**

- Maximum flow rates of 100L/min
- 3/4" BSP(f) inlet/outlet
- Maximum delivery per cycle of 350mL
- Also suitable for the transfer of diesel fuel, gear oil, engine oil, antifreeze and waste water



**\$967.00**

**353120  
3:1 Ratio Oil Transfer Tank Pump**

- Flow rates of up to 35L/min
- Suitable for bulk tank application
- Air inlet pressures of between 40-140psi (3-10bar)
- 1/2" BSP(f) fluid outlet
- 1/4" BSB(f) air inlet
- **354120** as above but suits 205L drums
- **\$1,001.00**



**\$1,564.00**

**504250  
Samoa Twin Pedestal Oil Hose Reel**

- Maximum working pressure of 2,300psi (160bar)
- 1/2" BSP(m) inlet/outlet
- Supplied complete with 15m x 1/2" ID R1 hose and 0.8m inlet hose
- Full 1/2" ID port, shaft and swivel
- Heavy duty double pedestal construction



**\$474.00**

**SOI700  
S Series Oil Hose Reel**

- 1/2" BSP(f) inlet/outlet
- Supplied with 10m x 12mm ID hose & lead in hose
- Impact resistant UV stabilised covers for maximum durability
- Automatic and positive latching mechanism
- Working pressure of up to 2,000psi (138bar)



**\$1,247.00**

**347120  
5:1 Ratio Oil Transfer Tank Pump**

- Can service up to 8 reels
- Maximum free flow of up to 30L/min
- 3/4" BSP(f) fluid outlet
- 3/8" BSP(f) air inlet
- **348120** as above but suits 205L drums **\$1,298.00**



**\$2,445.00**

**ALE-25BAH  
1" Aluminium Diaphragm Pump**

- Maximum flow rates of 160L/min
- 1" BSP(f) inlet/outlet
- Maximum delivery per cycle of 350mL
- Suitable for the transfer of diesel fuel, gear oil, engine oil, waste oil, antifreeze and waste water



**\$896.00**

**O30050  
Alemlube EL Series Oil Transfer Kit with Meter**

- Flow rates of up to 10L/min
- Automatically cuts off when the preset amount of lubricant is dispensed
- Includes a 3:1 ratio oil pump, 1/2" hydraulic hose, electronic oil meter and adjustable 2" bung adaptor
- Maximum operating pressure of 450psi (30bar)
- **O30040** also available but with on/off gun & 12L/min **\$805.00**



**\$2,713.00**

**O30070  
Alemlube EL Series Mobile 205L Oil Transfer Kit**

- Transfer kit flow rates of up to 8L/min
- High mobility kit complete with 3:1 ratio oil pump, oil hose reel with 15m x 1/2" ID hydraulic hose, electronic oil meter, 2" bung adaptor to suit 205L drum and robust heavy duty trolley
- **O30060** also available but delivers up to 10L/min **\$1,635.00**



**\$5,829.00**

**378110N  
Samoa 205L Mobile Oil Transfer Kit**

- Adjustable flow rates of up to 10L/min
- Supplied with 3:1 air operated oil pump, 15m hose reel, electronic meter and heavy duty drum trolley
- 3:1 ratio oil pump suits 205L drums
- Electronic oil meter maximum pressure of 1,000psi (69bar)



**\$3,329.00**

**454600N  
Stationary Oil Pump, Reel and Meter Kit**

- Adjustable flow rates of up to 10L/min
- Includes a 3:1 ratio drum pump, 10m hose reel, electronic meter and a 2m pump to hose reel connection hose
- 3:1 ratio pump suits 205L drums
- **454599N** also available but with on/off oil gun **\$2,569.00**



**\$4,233.00**

**454695  
IBC Oil Storage and Transfer Kit**

- 3:1 ratio pump, dual pedestal hose reel with 10m of hose, a top mounting bracket and electronic oil meter
- IBC not included
- **454695C** also available with IBC **\$4,733.00**



**\$1,633.00**

**454110N  
Samoa Oil Transfer Kit with Meter**

- 3:1 ratio pump, 3m x 1/2" ID hydraulic hose & electronic resettable meter
- Flow rates of up to 12L/min
- Air pressure range from 20psi to 140psi
- **454111N** also available but with on/off gun **\$1,137.00**



**\$1,297.00**

**365300  
Samoa Electronic Preset Oil Meter**

- Automatically cuts off when the preset amount of lubricant is dispensed
- Maximum flow rate of 30L/min, minimum flow rate of 1L/min
- 1/2" BSP(f) swivel supplied standard
- Maximum operating pressure of 994psi (69bar)



**\$290.41**

**363114  
Samoa Oil Control Valve**

- Flow rates of up to 40L/min
- Maximum working pressure of 1,450psi (100bar)
- 1/2" BSP(f) inlet port & swivel
- Ergonomic grip and trigger reduces operator fatigue
- Manual open/close nozzle operation minimises annoying oil drips & leaks



**\$1,137.00**

**365654  
Samoa High Flow Metered Oil Control Valve**

- Dispenses & meters synthetic and mineral oils
- Flow rates of up to 70L/min
- Maximum working pressure of 1,450psi (100bar)
- Measures in litres, quarts, pints and gallons
- 3/4" BSP inlet/outlet



**\$640.00**

**O30080  
Alemlube EL Series Digital Oil Meter**

- Delivers up to 35L/min
- Pressure range of 70-725psi (5-50bar)
- 5 digit liquid crystal display
- 1/2" BSP(f) inlet connection
- Suitable for the transfer of engine, gear, hydraulic oils up to SAE130 and ATF



**\$450.00**

**363054  
Samoa High Volume Oil Control Valve**

- Flow rates of up to 70L/min
- Maximum working pressure of 1,450psi (100bar)
- 3/4" BSP(f) inlet port & swivel
- Suitable for use in the transport, mining, construction and manufacturing sectors and in service vehicle applications



**\$1,297.00**

**365534  
Samoa Electronic Oil Meter**

- Maximum flow rate of 30L/min
- Electronically meters and totalises the amount of lubricant dispensed
- Fluid inlet is a 1/2" BSP(f) swivel
- Maximum operating pressure of 1,450psi (100bar)
- Manual open/close nozzle minimises annoying oil drip and leakage



DISTRIBUTED BY

ONE STOP LUBRICATION EQUIPMENT

francois@onestoplubrication.com Ph 0487 372 894

WORKSHOP EQUIPMENT, WASTE OIL & SAFETY

ONE STOP  
LUBRICATION EQUIPMENT



- 41008  
**Drum Funnel with Cover**
- Easily screws into all standard 60L and 205L drums
  - Large 8L capacity
  - Removable lid with attached safety cable
  - Heavy duty internal breather pipe
  - Built in strainer

\$51.90



\$386.00

- CR30060  
**Alemlube EL Series 240V Electric Cable Reel - 15amp**
- Supplied with 20m of 3 x 2.5mm<sup>2</sup> cable
  - Maximum power when coiled is 1,600W, when uncoiled 3,200W
  - CR30050 also available but 10amp & with 1.5mm<sup>2</sup> cable and power when coiled is 1,000W, when uncoiled 2,000W **\$354.00**



\$382.00

- BRP5216  
**Alemlube Safety Barrier Reel**
- Provides a temporary barrier to clearly identify dangerous areas
  - Supplied complete with 16m x 52mm of durable red/white band with hook & eyelet
  - Automatic spring rewind mechanism
  - A must for addressing workplace and employee safety



\$382.00

- BRP5216-YAB  
**Alemlube Danger Barrier Reel**
- Provides a temporary barrier to clearly identify dangerous areas
  - Supplied complete with 16m x 52mm of durable yellow/black band with eyelet
  - Compact design suitable to mount in most workplace environments



\$566.00

- ECRP24025  
**Alemlube 240V Electric Cable Reel**
- The ideal and safest way to store electric cable
  - Supplied with 25m x 3 x 1.5mm<sup>2</sup> wires cable & plugs
  - Maximum power when coiled 800W - uncoiled 2,000W



\$63.60

- 41009  
**205L Drum Top Pan**
- Works with most hand & air operated drum pumps
  - Easily fits most standard sized 205L drums
  - Suitable for use with oil, diesel, petrol, kerosene, water and all fluids compatible with polyethylene
  - Minimises valuable resources waste
  - Drum pump not included



\$231.20

- 41006N  
**Manual Waste Oil Extractor**
- Ideal for extracting waste oil from motor vehicles, motor bikes, marine engines, lawn mowers and stationary engines
  - Automatic shut off when waste oil or water is extracted
  - Complete with probe kit to suit various dipsticks



\$640.00

- 30080  
**Alemlube Waste Oil Drainer**
- Transfers and captures waste oil from crankcases, transmissions and differentials
  - Catchment bowl capacity of 20L
  - Holding tank capacity of 80L
  - Equipped with a pneumatic safety relief valve calibrated at 14psi (1bar)



\$1,395.00

- 30101  
**Mobile Waste Oil Extractor/Drainer**
- Extracts and captures waste oil from crankcases, transmissions and differentials
  - Clear inspection chamber capacity of 12L
  - Holding tank capacity of 80L
  - Suction speed of 6.5 L/min



\$2,257.00

- 372000  
**Samoa Waste Oil Drainer / Extractor**
- Drains and/or extracts waste oil from cars and light commercial vehicles
  - Drain bowl capacity of 20L
  - Holding tank capacity of 100L
  - Suction hose includes a rubber grip and a non drip cap



\$1,121.00

- 372400  
**Samoa Waste Oil Drainer**
- Premium quality and European engineering
  - Drain bowl capacity of 20L
  - Unique specially molded tray can be used to hold bolts, filters and washers
  - Waste fluids can be pressurised or pumped out of the 100L capacity holding tank



\$600.00

- 42100  
**Commercial Vehicle Mobile Waste Oil Drainer**
- Holding tank capacity of 100L
  - Sturdy and durable construction
  - 145mm high swivelling front rubber wheels facilitate accurate mobility
  - Ideal for busy truck and bus workshops



\$4,172.00

- AA579  
**Alemlube Automotive Automatic Wheel Balancer**
- European quality and appearance
  - Laser pointer makes wheel balancing and a quicker easier proposition
  - Automatic distance and wheel diameter measuring
  - 9 Balancing modes



\$96.40

- 20088  
**LED Slimline Work Light**
- 7W COB LED, min-max 60-700lm
  - 3W SMD top LED, 120lm
  - 80 CRI, 6500K
  - 3.7V 2600mAh Li-ion battery
  - 16 / 1.5 hour main light runtime
  - 9.5 hour top light runtime
  - 4 hour charge time



\$43.80

- 5000MFN  
**5L Multi Purpose Oil Measure**
- Polyethylene oil measure will not dent, scratch or corrode
  - Flexible delivery spout makes the topping up of engines, gear boxes, diffs, transmissions and crank cases a quick and easy proposition
  - 2000MFN as above but 2L capacity **\$34.30**



- Clean Funnels**
- 10430CF 1,420mL capacity - slim line delivery port **\$13.60**
  - 10350CF 1,420mL capacity - high flow delivery port **\$13.70**
  - 10270CF 1,180mL capacity **\$13.10**
  - 10220CF 450mL capacity **\$7.60**



\$78.30

- 20066N2  
**LED Work Light with Aircon Gas Leak Detection Capabilities**
- Provides valuable assistance when undertaking close inspection work under & around vehicles
  - The UV light is ideal for detecting Ultra Violet leak detection dye used in vehicle air conditioning systems



\$16,005.00

- AAWA8CCD  
**Alemlube Automotive Wheel Aligner**
- Large 24" LCD screen is easy to read and analyse
  - Blue tooth transmission between the front heads and the cabinet
  - 90,000 vehicle data start database
  - Full customer database





# DISTRIBUTED BY ONE STOP LUBRICATION EQUIPMENT

francois@onestoplubrication.com Ph 0487 372 894

## GREASING

**ONE STOP**  
LUBRICATION EQUIPMENT



**\$43.70**

**G10020N  
Alemlube  
EL Series  
Lever Action  
Grease Gun**

- Grease pressures of up to 8,000psi (552bar)
- Delivery rates of up to 0.95g per stroke
- Robust die cast head assembly
- Heavy duty 4 jaw coupler

**G10010N** also available but trigger action, 1.15g per stroke, up to 4,000psi (275bar) **\$000.00**



**\$94.10**

**600A  
Lever Action Grease Gun**

- Delivers up to 1.6g of grease per stroke
- 450g cartridge
- Grease pressures of up to 12,000psi (828bar)
- Suitable for all grease grades up to NLGI3
- Unique Ever-Flow System enables the use of thick/tacky greases



**\$1,323.00**

**670AN5  
20V Lithium-ion Cordless Grease Gun**

- Delivery rates of up to 170g/min (high) & 113g/min (low)
- Grease pressures of up to 10,000psi (690bar)
- Up to 35 cartridges per battery charge
- Built in Intelligence
- LCD with real time battery capacity, grease level and grease metering information



**\$128.30**

**660AN  
Trigger Action Grease Gun**

- Delivers up to 1.1g of grease per stroke
- 450g cartridge
- Grease pressures of up to 8,500psi (586bar)
- Twin Lock System seals the piston and eliminates the possibility of dummy lubrication
- 4 jaw coupler and flexible 30cm long extension



**\$360.00**

**680AN  
Air Operated Grease Gun**

- Develops grease pressures of up to 3,290psi (226bar)
- Pressure ratio of 40:1
- Delivers up to 182g per minute
- Recommended maximum air pressure of up to 98psi (6bar)
- Suits 450g cartridge or bulk grease
- Suitable for use with grease up to NLGI2



**\$39.50**

**14512  
Quick Release Grease Gun Coupler**

- Works with all grease gun types
  - pneumatic, manual and battery
- 1/8" BSP(f) thread
- Working pressure of 10,000psi (690bar)

**A14512** with hanging packaging **\$40.90**  
**14510** as above but 135mm long **\$58.90**  
**14511** also available but 1/8" NPT(f) 90mm long **\$48.40**  
 • A14510 & A14511 hanging packs also available



**\$534.00**

**6320-3  
Alemite Grease Control Valve**

- Heavy duty grease control valve capable of continuous flow or preset measured shots
- 1/4" NPT(f) inlet
- Manufactured in the USA



**\$781.00**

**G100120  
Alemlube EL Series 20kg Grease Kit**

- Heavy duty grease control valve
- 4m long hose assembly
- Maximum fluid pressure of 5,800psi (400bar)
- All types of grease up to NLGI2
- Delivers up to 600g/min
- Drum not included



**\$1,282.00**

**424170  
Samoa 20kg Grease Kit**

- Delivery rates of up to 0.9kg/min
- 55:1 ratio air motor develops grease pressures of up to 7,950psi (548bar)
- Supplied with a 4m long hose assembly enabling quicker and easier greasing of your plant and equipment
- Drum not included



**\$1,438.00**

**424150  
Samoa 20kg Grease Kit with Trolley**

- High pressure 55:1 ratio pump
- Up to 7,950psi (548bar) grease pressure
- Ideal for busy workshops where greasing is undertaken all day, every day
- Drum not included



**\$1,948.00**

**428262  
180kg Air Operated Grease Kit**

- 55:1 ratio grease pump develops up to 7,950psi (548bar)
- Integral filter eliminates the chance of pump tube contamination
- Grease control valve has single shot or continuous flow option
- 1/4" BSP(f) inlet thread
- Drum not included



**\$213.40**

**413080  
Samoa Grease Control Valve c/w Z-Swivel & Rigid Extension**

- Maximum working pressure of 7,150psi (500bar)
- High pressure rigid outlet with 3 jaw coupler
- Single shot or continuous flow option
- Rigid outlet with 3 jaw coupler
- Heavy duty three way swivel
- 1/4" BSP(f) inlet thread
- Suitable for use with pneumatic, hydraulic and electric grease pumps and kits



**\$972.00**

**ACON0820-MAK  
Alemlube Construction Major Grab Kit**

- Automatic Greasing System Repair kit to suit construction machines
- Replacement fittings, high grease pressure hose (5m) / tube (10m) to repair damaged grease lines and/or broken fittings
- Assorted thread sizes to suit metric & imperial: 1/8" BSP, 6mmx1mm, 8mmx1mm, 10mmx1mm

**ACON0820-MIK** also available but Construction Minor Grab Kit, without tube/hose **\$452.00**



**\$79.70**

**G10090  
Alemlube EL Series Grease Nipple Assortment Kit**

- Includes 90 of your most popular grease nipples and 10 grease nipple dust covers in a convenient compartmentalised carry kit
- Manufactured in Germany

**G100100SS** EL Series Stainless Steel Grease Nipple Assortment Kit **\$467.00**



**\$27.00**

**BT0544  
Alemlube Hose End**

- Reusable hose ends
- 7/16" JIC to Beka Max 8.3mm hose
- Includes hose sleeve and stud

**BT0566** 8.3 hose end with sleeve reusable 7/16" JIC 90 **\$51.70**  
**FAZ03552-00** Bulkhead grease nipple connects to 6mm grease tube **\$23.60**



**\$134.50**

**100120100-20  
Alemlube Grease Tubing**

- Polyamide tube 20m x 6mm - grease filled
- Maximum burst pressure of 3,900psi (269bar)
- Ideal for mine sites, industrial plants, petrochemical facilities, contractors and off road vehicles, wheel loaders, extractors and cooling towers

**100120200-10** also available but with 10m x 8.3mm diameter 280bar tubing **\$176.60**



**\$98.20**

**L4674  
Agricultural Grease Nipple Assortment Kit**

- 120 of your most popular grease nipples in a convenient compartmentalised refillable carry kit

**L4676** 100 Metric grease nipple assortment kit **\$85.90**  
**L4675** 101 Industrial grease nipple assortment kit **\$95.20**



**\$245.60**

**ATAT0820-MIK  
Alemlube Transport Minor Grab Kit**

- Automatic Greasing System Repair kit to suit trucks & trailers
- Replacement fittings, to repair damaged or broken fittings
- Assorted thread sizes to suit metric & imperial: 1/8" BSP, 6mmx1mm, 8mmx1mm, 10mmx1mm

**ATAT0820-MAK** also available but Transport Major Grab Kit inclusive of 10m tube / 5m hose **\$619.00**



# DISTRIBUTED BY ONE STOP LUBRICATION EQUIPMENT

francois@onestoplubrication.com Ph 0487 372 894

## Pulsarlube Single & Multi Point Grease Lubricators

**ONE STOP**  
LUBRICATION EQUIPMENT



### Pulsarlube E Series

- Electro-chemical operation generates inert nitrogen gas
- Grease pressure of up to 70psi (5bar)
- Frequent low volumes

Part Number	Pulsarlube E Series	Price
E60/PL1	60cc - Filled with PL1 Grease	\$73.30
E120/PL1	120cc - Filled with PL1 Grease	\$78.90
E240/PL1	240cc - Filled with PL1 Grease	\$87.50



### Pulsarlube MSP Series

- Long term reliability electro-mechanical lubricator
- Operating pressure of up to 870psi (60bar)
- Large LCD screen & easy to program
- Dispenses grease when machine is operative

Part Number	Pulsarlube MSP Series	Price
MSP250-VAC/MAIN	250cc - Filled with PL1 Grease	\$600.00
MSP500-VAC/MAIN	500cc - Filled with PL1 Grease	\$750.00



### Pulsarlube M Series

- Long term reliability electro-mechanical lubricator
- Operating pressure of up to 870psi (60bar)
- Large LCD screen & easy to program
- Dispenses grease when machine is in operation
- Up to 8 points of multipoint lubrication

Part Number	Pulsarlube M Series	Price
M125/PL1	125cc - Filled with PL1 Grease	\$414.00
M250/PL1	250cc - Filled with PL1 Grease	\$430.00
M500/PL1	500cc - Filled with PL1 Grease	\$532.00



### Pulsarlube Mi Series - Vibration Activated Lubrication

- Dispenses grease when machine is in operation and detects vibration
- The only lubricator to react to vibration in the market
- Long term reliability electro-mechanical lubricator
- Operating pressure of up to 870psi (60bar)
- Large LCD screen & easy to program

Part Number	Pulsarlube Mi Series	Price
Mi60/MAIN	60cc - Filled with PL1 Grease	\$637.00
Mi125/MAIN	125cc - Filled with PL1 Grease	\$631.00
Mi250/MAIN	250cc - Filled with PL1 Grease	\$647.00

NEW



\$149.90



\$2,568.00



\$2,692.00



\$4,718.00



\$1,560.00

NEW



\$350.00

ST1-10-YE-BK

### 10L Spill Tray with Platform

- Fluid capacity of 10L
- Innovative and efficient stacking and storage ability
- 100% recyclable polyethylene construction
- Non-skid removable platform
- Can be used without the deck in place
- Dimensions: 155mm (H) x 400mm (W) x 300mm (D)

SJ-120-002C

### 2 Drum Spill Container

- Fluid capacity of 230L
- 100% recyclable polyethylene construction
- Non-skid removable platform
- Deck incorporates hand inserts and holes for inspection and pump insertion
- Dimensions: 410mm (H) x 1200mm (W) x 800mm (D)
- Drum not included

SJ-510-001

### IBC & Drum Spill Containers

- Solid construction and practical design
- Sump capacity of 1,100L
- Compatible with most forklifts and pallet trucks
- Dimensions: 1,680mm (L) x 1,680mm (W) x 700mm (H)
- IBC not included

SJ-520-001

### Double IBC Spill Container

- Non-skid removable deck
- Sump capacity of 1,165 litres to underside of the deck
- Dimensions: 575mm (H) x 2,260mm (W) x 1,460mm (D)
- Manufactured in the UK
- IBC's not included

SJ-300-006C

### 4 Drum Workfloor & Spill Container

- Slip resistant texture
- Cannot rust or corrode
- Sump capacity of 240L
- Dimensions of 1,600mm (L) x 1,600mm (W) x 150mm (H)
- Drums not included

ST2-60-YE-BK

### 60L Spill Tray with Platform

- Fluid capacity of 63L
- Innovative and efficient stacking and storage ability
- 100% recyclable polyethylene construction
- Non-skid removable platform
- Can be used without the deck in place
- Dimensions: 265mm (H) x 1000mm (W) x 600mm (D)

401A

### Ryton Rotary Drum Pump

- Flow rates of up to 20L/min
- Ryton and stainless steel construction provides excellent chemical compatibility
- Suitable for 60L or 205L drums
- Suitable for the transfer of low viscosity chemicals, lacquers, AdBlue® and mild acids

\$320.00

JP-140-PVDF-HC-1000

### 205L Chemical Drum Pump Kit with Polypropylene Pump Tube - 240V

- Flow rates of up to 49L/min
- Supplied with electric motor & poly pump tube, 2m PVC hose, stainless steel hose clamps and polypropylene nozzle
- Suitable for hydrofluoric acid, sodium, hydrochloric, sulphuric acid to a concentration of 90%
- JP-140-PVDF-HC-1200 also available to suit 1,000L IBC's \$2,631.00

\$2,511.00

JP-180-PP-HC-1000

### 205L Chemical Drum Pump Kit with Polypropylene Pump Tube - 240V

- Flow rates of up to 93L/min
- Supplied with electric motor, 1,000mm polypropylene pump tube, 2m PVC hose, stainless steel hose clamps and polypropylene nozzle
- Suitable for hydrochloric acid, phosphoric acid, liquid fertiliser, citric acid, iron(II) & iron(III), chloride and distilled water
- JP-180-PP-HC-1200 also available to suit 1,000L IBC's \$2,642.00

\$2,531.00

JP-280-PVDF-HC-1000

### 205L Drum Pump Kit with PVDF Pump Tube - 240V

- Flow rates of up to 112L/min
- Supplied with electric motor, 1,000mm PVDF pump tube, 2m multi-purpose chemical hose, stainless steel hose clamps and PVDF nozzle
- Suitable for hydrofluoric acid, sodium, hydrochloric, sulphuric acid to a concentration of 90%
- JP-280-PVDF-HC-1200 also available to suit 1,000L IBC's \$4,563.00

\$4,361.00

JP-280-ALU-HC-1000

### 205L Drum Pump Kit with Aluminium Pump Tube - 240V

- Flow rates of up to 112L/min
- Supplied with electric motor, 1,000mm pump tube, 2m mineral oil hose, stainless steel hose clamps and aluminium nozzle
- Suitable for synthetic oils, hydraulic oils and engine oils up to 1000 M/PAS, diesel and liquid soap
- JP-280-ALU-HC-1200 also available to suit 1,000L IBC's \$2,911.00

\$2,831.00

301A

### Polypropylene Rotary Drum Pump

- Flow rates of up to 20L/min
- Polypropylene, teflon and stainless steel construction offer's excellent chemical resistance
- Suitable for the transfer of herbicides, pesticides, chemicals and mild detergents
- Aluminium-free. This pump is ideal for use in underground mines
- Suitable for 60 or 205L drums and bulk tanks

\$225.40





DISTRIBUTED BY

ONE STOP LUBRICATION EQUIPMENT

francois@onestoplubrication.com Ph 0487 372 894

HOSE STORAGE & RETRIEVAL

ONE STOP  
LUBRICATION EQUIPMENT



**\$1,882.00**

505924  
**Samoa 3/4" Spring Rewind Hose Reel**

- 15m capacity bare reel
- Dual ball bearing spool support results in very low rotary friction
- Optimised power spring and low friction design ensure smooth & comfortable operation
- Unique non ratch out design enables total mounting flexibility (7 different positions)
- True 3/4" fluid section maximises product delivery



**\$3,076.00**

508225

**Samoa 1" High Volume Hose Reel**

- Long-life heavy duty double arm design
- Supplied with 15m x 1" BSP(f) ID hose
- 1,250psi (86bar) hose pressure rating
- 1" port nickel coated steel shaft and swivel
- Suitable for use with fuel, oil, air, water and waste oil



**\$2,031.00**

HR90005

**Alemlube EL Series 1" Air, Water & Fuel Hose Reel**

- Reinforced steel frame provides maximum strength and stability
- Working pressure of up to 300psi (20bar)
- 30m x 25mm ID rubber hose & hose stop
- 1.5mm thick robust drum with stiffening ribs and flange edges



**\$1,095.00**

HR90015

**Alemlube EL Series 1" Air & Water Spring Rewind Hose Reel**

- Reinforced steel frame provides maximum strength & stability
- Working pressure of up to 300psi (20bar)
- 8m x 25mm ID rubber hose & hose stop
- 1.5mm thick robust drum with stiffening ribs & flange edges



**\$1,394.00**

750030

**3/4" Fuel Hose Reel**

- Latest hydraulic system design principles result in reduced pressure loss even for high flow pumps
- Maximum operating pressure of up to 145psi (10bar)
- Supplied with 10m x 1" fuel delivery hose and hose stop complete with swivel and elbow




**\$3,017.00**

7342

**Alemite 1" Heavy Duty Hose Reel**

- Double pedestal heavy duty bare reel
- Maximum working pressure of up to 1,000psi (69bar)
- Capable of storing and retrieving 15m x 1" ID hose or 21m x 3/4" ID hose
- Superior bearing performance reduces torque load on power spring for smooth retraction and durability



**\$1,357.00**

117-5-100

**3/4" Hand Rewind Hose Reel**

- High performance, compact hand crank hose reel
- Standard working pressures of up to 4,000psi (276bar)
- Reel handles fluid temperatures from -29°C up to +99°C
- Stores and retrieves up to 30m x 19mm ID hose



**\$2,149.00**

1175-6-100

**1" Large Capacity Hand Rewind Air, Water or Fuel Hose Reel**

- Working pressures of up to 3,000psi (207bar)
- 1" NPT(f) inlet/outlet
- All metal construction
- Can store and retrieve up to 30m x 25mm ID hose
- Hose not included



**\$1,850.00**

HR90025

**Alemlube EL Series 3/4" Air & Water Spring Rewind Hose Reel**

- Reinforced steel frame provides maximum strength & stability
- Working pressure of up to 300psi (20bar)
- 20m x 19mm ID rubber hose & hose stop
- 1.5mm thick robust drum with stiffening ribs & flange edges
- Reliable spring life of 20,000 cycles and positive ratchet lock design



**\$1,769.00**

504351

**Samoa 3/8" Twin Pedestal Grease Hose Reel**

- Maximum working pressure of 4,060psi (280bar)
- 3/8" BSP(m) inlet/outlet
- Supplied complete with 15m x 3/8" ID hose and 0.8m inlet hose
- 504350 also available but with 15m x 1/4" ID hose and 0.8m inlet hose and 1/4" BSP(m) inlet/outlet **\$1,682.00**



**\$2,890.00**

1185-1524

**1-1/2" Hand Rewind Bare Hose Reel**

- All metal construction
- Engineered and designed for use in challenging, heavy duty applications
- Pressures of up to 600psi (41bar)
- Capable of storing and retrieving 22m x 38mm ID hose
- Suitable for air, water, fuel and waste oil



**\$7,102.00**

1195-932-A

**2" Large Capacity Air Rewind Bare Hose Reel**

- Working pressures up to 600psi (41bar)
- 2" NPT(f) inlet/outlet
- All metal construction
- Can store and retrieve up to 18m x 48mm ID hose
- Suitable for air, water, fuel and waste oil



**\$369.00**

WP1290

**Alemlube Large Capacity Water Hose Reel**

- Stores and retrieves up to 30m x 12mm ID hose
- 3/4" BSP(m) inlet/outlet
- Durable impact and weather resistant covers ensure a long working life
- Convenient carry handle facilitates easy movement of the hose reel as required



**\$548.00**

SO600

**Oxy-Acetylene Hose Reel**

- 15m x 6mm ID hose & 0.9m lead in hoses
- 5/8" BSP inlet/outlet
- Maximum working pressure of 300psi (21bar)
- Automatic and positive latching mechanism
- Impact resistant UV stabilised covers for maximum durability
- Ideal for back of UTE or service vehicle mobile use



**\$605.00**

SOP620

**Oxy-Propane Hose Reel**

- 15m x 6mm ID hoses & 0.9m twin rubber lead in hoses
- Impact resistant UV stabilised covers for maximum durability
- 5/8" UNF inlet/outlet
- Maximum working pressure of 300psi (20bar)
- Ideal for back of UTE or service vehicle mobile use



**\$397.00**

SP610

**LPG Hose Reel**

- 20m x 6mm ID hose & 0.9m lead in hose
- 5/8" UNF inlet/outlet
- Maximum working pressure of 300psi (20bar)
- Ideal for back of UTE or service vehicle mobile use
- Can be mounted on the wall or ceiling



**\$392.00**

SA630

**Argon Hose Reel**

- 20m x 6mm ID hose & 0.9m lead in hose
- Impact resistant UV stabilised covers for maximum durability
- Automatic and positive latching mechanism
- 5/8" UNF inlet/outlet
- Maximum working pressure of 300psi (20bar)
- Ideal for back of UTE or service vehicle mobile use



**\$410.00**

HR30080C

**EI Series Hot Water Hose Reel With Nozzle**

- Supplied complete with 15m x 12mm ID hybrid polymer hose and 1.2m lead in hose
- 3/4" BSP(f) inlet
- Maximum working pressure of 300psi (20bar)
- Temperature range from -40°C to +80°C
- HR30080 also available but without nozzle **\$267.80**





DISTRIBUTED BY

ONE STOP LUBRICATION EQUIPMENT

francois@onestoplubrication.com Ph 0487 372 894

GREASING, FUEL & OIL

ONE STOP  
LUBRICATION EQUIPMENT



**\$97.00**

**G10010NP  
Alemlube EL Series Trigger Action Grease Gun**

- Grease pressures of up to 4,000psi (276bar)
- Delivery rates of up to 1.15g per stroke
- Heavy duty 4 jaw coupler
- Exceptional value for money for cost conscious customers



**\$530.00**

**G10040N  
Alemlube EL Series 18V Lithium-ion Cordless Grease Gun**

- Generates grease pressures of up to 10,000psi (690bar)
- Capable of delivering up to 80g/min
- 25 minutes continuous working time
- Spare battery, recharger, 106cm long grease gun flex and plastic moulded carry case supplied standard



**\$6,280.00**

**KPL-24EX  
24V 20kg Grease Kit**

- A unique product, this 24V, 20kg grease pump kit is ideal for mining & heavy industrial applications
- Working pressure of 4,000psi (276bar)
- Dispenses up to 70-80g/min
- **EPL-240SP** also available but 240V, dispenses up to 120-190g/min **\$6,533.00**



**\$9,100.00**

**ALEMLUBE ALS 20  
Automatic Grease Lubrication System**

- One of the leading lubrication systems for trucks and trailers
- Designed for use with #2 heavy duty EP grease
- High pressure progressive distribution system – up to 4,200psi
- Reservoir sizes of 4kg, 8kg and large bulk fill versions for mining available



**\$1,117.00**

**415002  
Samoa Grease Metering Control Valve with Flexible Extension**

- Maximum operating pressure of 7,150psi (500bar)
- Accurate to  $\pm 2\%$
- Battery life of up to 10,000 hours
- Ideal for applications where over or under lubrication can result in costly bearing failures and downtime



**\$156.70**

**660ANP  
450g Trigger Action Grease Gun & Carry Case**

- Convenient & handy storage for an extra grease cartridge
- Grease pressures of up to 8,500psi (586bar)
- High volume / high pressure option facilitates fast and efficient greasing
- Ever-Flow System enables the use of thick tacky greases even in the coldest conditions



**\$61.50**

**52007  
Manual Diesel Fuel Nozzle**

- Capable of flow rates up to 150L/min
- Suitable for gravity feed applications and applications including pressures of up to 140psi (10bar)
- 1" BSP(f) swivel included
- Ideal for farm tank applications
- **52155** as above but for unleaded petrol **\$63.70**



**\$466.00**

**52040  
12V Self Priming Diesel Fuel Transfer Pump**

- Flow rates of up to 50 L/min
- Self-priming 12V electric pump with on/off switch
- Duty cycle of 30 mins. on / 30 mins. off
- Maximum working pressure of 22psi (1.5 bar)
- BSP inlet & outlet connections



**\$1,484.00**

**52004A  
12V High Volume Auto Diesel Pump**

- Flow rates of up to 80L/min
- Includes an automatic shut off nozzle
- Telescopic down tube suits fuel tanks up to 1,000mm deep
- 1" BSP(f) inlet/outlet
- Duty cycle of 30 minutes on / 30 minutes off
- **52004** also available with manual nozzle, 75L/min **\$1,221.00**



**\$1,027.00**

**M150SA  
12V GPI Heavy Duty Auto Diesel Pump**

- Flow rates of up to 49L/min
- Duty cycle of 30 minutes on, 30 minutes off
- Suitable for 205L drums or bulk tanks up to 1,000mm deep
- Automatic nozzle
- **M150S** also available with manual nozzle 56L/min **\$915.00**



**\$175.60**

**611200  
Alemlube Fuel Tank Filter**

- Capable of delivering flow rates of up to 100L/min
- Maximum pressure 50psi (3.5bar)
- Suitable for use with diesel & petrol
- For use with pumps up to 100L/min
- Bursting pressure 145psi (10bar)
- Includes 1 x filter head and 1 x filter element
- 1" flanged BSP(f) inlet/outlet



**\$458.00**

**51008  
1" Mechanical Diesel Fuel Meter**

- Accurate between flow rates of 20L/min and 120L/min
- Maximum working pressure of 142psi (10bar)
- 1" BSP(f) inlet/outlet ports
- Suitable for gravity feed or pump applications
- 3 digit display
- Also suitable for use with kerosene
- **51007** as above but 4 digit display **\$477.00**



**\$27.00**

**7701A  
1L Multi Purpose Top Up Kit**

- Ideal for topping up difficult to access oiling points in the workshop and at home
- Suitable for all oils, automatic transmission fluids, brake fluids and some hand cleaners
- Not suitable for combustible fluids



**\$118.40**

**001083  
Container Pump with T- Handle**

- Designed to use with 5 or 10L containers
- Simple extension sleeve extends the reach of the pump for 10L drums
- Approximately 14 strokes per litre
- 1.4m non-kink PVC hose with spiral inlay
- Storage port on the lid for the nozzle when not in use



**\$154.70**

**001021-25  
10L Oil Container - 25mm Pour Lid Kit**

- Fully sealed system reduces the chance of lubricant contamination
- Colour coding accurately identifies fluids to minimise cross contamination
- Quick fill port for safe contaminant free refills
- Large flat square base surface for stability and easy iPouch labelling for MSDS documents



**\$217.70**

**001021-PU  
10L Oil Container Pump Kit**

- Manufactured in high density HDPE
- Prevents cross contamination
- Suitable for use with a variety of lubricants, fluids and coolants
- **001014-PU** as above but 5L capacity **\$183.70**



**\$120.80**

**001014-25  
5L Oil Container - 25mm Pour Lid Kit**

- Colour coding accurately identifies fluids to minimise cross contamination
- Quick fill port for safe contaminant free refills
- Quick changing colour coding handles and bands means no more stocking of specific coloured pour lids saving time and money
- **001014-12** as above but with 12mm pour lid kit **\$103.80**



**\$55.00**

**6603A  
1L Brake Cleaner Sprayer**

- Large filling opening
- Safety valve at 36psi (2.5bar) with depressurisation option
- Easy tool free maintenance
- Ergonomic design
- Strong translucent bottle with level indicator
- Not suitable for use with acids



# EQUIPMENT SOLUTIONS



19 OCT- 18 DEC 2020



**\$356.00**

51039

## 1" Automatic Diesel Nozzle

- Automatically cuts off when a fuel tank is full
- Can operate with flow rates of up to 120L/min
- 1" BSP(f) swivel included
- Suitable for applications involving an electric diesel transfer pump



**\$459.00**

5060AN

## Heavy Duty Hi-Flo Refuelling Drum Pump

- Low torque, high volume easy to use pump delivers up to 110L/min
- Delivery rates of 1.1 litres per rotation
- Supplied complete with 2.6m of UV and fuel resistant hose, spout, in built spout holster, 3-piece downtube, heavy duty bung adaptor
- **5080AN** as above but with FA2 filter **\$721.00**



**\$164.00**

501A

## Rotary Action Drum Pump

- Delivery rates of up to 18L/min or 0.26L per rotation
- Suitable for the transfer of diesel, petrols, kerosene, lube oil and machine oil
- 2" BSP bung adaptor
- Anti static fuel hose
- Includes 2.2m of farm tank hose, bung adaptor, rubber gasket, a four chamber rotor assembly, spout and spout holster



**\$51.90**

8828N2

## 20L Gear Oil Drum Pump

- Capable of delivering up to 110mL per stroke
- Downtube extension and extra Rieke adaptor make the pump suitable for use with a variety of 20L drums available on the market
- Ideal pump for the transfer of engine, gear, diff and hydraulic oils in busy vehicle servicing workshops



**\$5,902.00**

AA236A

## Alemlube Automotive 26" Tilt Back Tyre Changer with Helper Arm

- Pneumatically operated tilting column
- Automatic pneumatic right help arm device
- Tubeless tyre inflating device
- Large 26" turntable suitable for low profile tyres
- 240V 10amp power supply



**\$157.20**

FA2N

## Fuel Tank Filter

- Fuel filter suitable for use with gravity feed fuel tanks and with hand, air or electric drum pumps
- Features a 10 micron fuel filter element, a drain cock and a replaceable clear plastic bowl
- 1" BSP(f) inlet/outlet

**DISTRIBUTED BY**



**ONE STOP LUBRICATION EQUIPMENT**  
francois@onestoplubrication.com Ph 0487 372 894



Stores advertised on page one of this catalogue are independent businesses. Every effort has been made to ensure that advertised stock is available, but due to factors beyond the control of Alemlube Pty Ltd not all products advertised in this catalogue are available at all stores. Pricing for the products are special prices available through to 18th of December 2020. Regular prices vary from store to store. The catalogue pricing is calculated in good faith as the average regular price at the time of preparation. Alemlube Pty Ltd will do everything possible, within reason, to maintain stocks of advertised products but cannot be responsible for unforeseen shortfalls beyond their control.

All products are covered by a 2 year warranty (unless otherwise stated) and with the aid of our sixty five strong nationwide Authorised Agent Network, technical support for all Alemlube products featured in this catalogue will never be far away. E.&O.E. Copyright 2020. Reproduction in whole or part is prohibited without written approval. All prices shown include GST. Freight charges may be applicable and may vary from region to region.