

Door Pull Installation Instructions

Roadie Designs Ltd accepts no responsibility for, and are not liable for any damage to your car or person/persons caused through use of products or services purchased through Roadie Designs Ltd, be it indirect, special, incidental or consequential damages. If you have any questions regarding the terms of use outlined here, please do not hesitate to contact us at www.roadiedesigns.co.uk/contact



Remove door handle cover reflector cap.
Undo all 4 screws.



Remove door handle/speaker surround.



Remove door card



Unscrew the 3 screws holding the handle unit.



Unclip the tweeter & led light (if you have one). I prefer to take out the tweeter itself so it doesn't get damaged.



Slide the cable cover back and unclip the cable from the handle mechanism.



Remove the pin from the unit. A tap with a hammer loosens it then pull out with pliers



Remove the handle and spring (these are no longer needed, keep in safe place if you wish to reverse the process) Keep the pin as this is required



With the hole location template, drill a hole using the supplied drill bit in the back of the door handle unit.



Place the correct mechanism (labelled DS - Drivers Side, PS - Passenger Side) in the unit



Tap the pin through the unit and mechanism until it is showing on the other side.



Insert the sleeve nut through the mechanism.



Place the strap over the sleeve nut.



Screw the flanged bolt into the sleeved nut until tight.



Plug the speaker and cable in including the led (if you have one).



Clip the cable into the mechanism.



Slide the cable cover back and into the handle housing.



Screw in the screws for the handle housing. Now test the new door pull by closing the door and pulling the strap to open. The Mechanism may catch on the door metal work, use the supplied rubber washers to step the door handle off the door



Re-attach the door card.



Re-attach the handle/speaker surround



Slide the strap through the cover plate. Place the long Allen bolt through the centre hole and locate the hole previously drilled. Tighten until cover plate is secure (do not over tighten).



Re-attach all the bolts holding the door card and slide the door handle cover on. Stand back and enjoy your new Door Pull opener.