

# DASHIN SERIES VACUUM



DS-1

## 直結式真空泵浦 STANDARD VACUUM PUMP

泵浦組立流量達到：

7.2m<sup>3</sup>/h (60Hz)

- 輕巧，馬達直結驅動
- 適用於低流量
- 維修簡易
- 運轉安靜

Manufactured Flow of Pump is:

7.2m<sup>3</sup>/h (60Hz)

- Light, motor is direct to drive
- Applicable to low flow
- Easy to repair and maintain
- Silent running

### 規格SPECIFICATIONS:

型式 MODEL	轉速 ROTATION	排出流量 DESIGNED EXHAUST VELOCITY	到達真空度 OBTAINABLE VACUUM	使用真空度 FREQUENTLY USE VACUUM	壓力 USUAL EXHAUST PRESSURE	直徑 DIAMETER OF EXHAUST PIPE	馬力 POWER	尺寸 SIZE(LxWxH) (mm)	重量 WEIGHT(kg)
DS-1	1720r.p.m(60Hz)	120//min	680mmHg	Under 450mmHg	Under 0.6kg/cm <sup>2</sup>	3/8 PT	SINGLE PHASE 110V 220V 0.25Kw4P	233x192x206	SINGLE BODY 11kg

## 單體真空泵浦 SINGLE VACUUM PUMP

泵浦設計流量達到：

34.6m<sup>3</sup>/h (50Hz)

41.2m<sup>3</sup>/h (60Hz)

- 泵浦，驅動可自行設計
- 運用於各自動化工業及印刷等

Designed Flow of Pump is:

34.6m<sup>3</sup>/h (50Hz)

41.2m<sup>3</sup>/h (60Hz)

- May self-design the pump and driving
- Applicable to various of automated industry and printing



DS-3~8

### 規格SPECIFICATIONS:

型式 MODEL	轉速 ROTATION	排出流量 DESIGNED EXHAUST VELOCITY	到達真空度 OBTAINABLE VACUUM	使用真空度 FREQUENTLY USE VACUUM	壓力 USUAL EXHAUST PRESSURE	直徑 DIAMETER OF EXHAUST PIPE	馬力 POWER	尺寸 SIZE(LxWxH) (mm)	重量 WEIGHT(kg)
DS-3	1450r.p.m(50Hz)	235//min	600mmHg				SINGLE PHASE 3PHASE 0.4Kw4P	263x154x224	SINGLE BODY 10.5kg
	1730r.p.m(60Hz)	280//min							
DS-5	1450r.p.m(50Hz)	405//min		Under 450mmHg	Under 0.6kg/cm <sup>2</sup>	3/4 PT	3PHASE 0.75Kw4P	275x156x228	SINGLE BODY 13kg
	1730r.p.m(60Hz)	480//min							
DS-6	1450r.p.m(50Hz)	575//min	660mmHg				3PHASE 1.5Kw4P	335x160x245	SINGLE BODY 15.5kg
	1730r.p.m(60Hz)	685//min							
DS-8	945r.p.m(50Hz)	1130//min		Under 400mmHg	Under 0.5kg/cm <sup>2</sup>	1PT	3PHASE 2.2Kw6P	375x235x325	SINGLE BODY 45kg
	1135r.p.m(60Hz)	1350//min							