

DA SHIN SERIES VACUUM

標準式真空泵浦 STANDARD VACUUM PUMP



DS-3E~8E

泵浦組合流量達到：

56.7m³/h (50Hz)

68.1m³/h (60Hz)

- 馬達連軸驅動泵浦設計
- 換裝方便 • 操作速捷

Assembled Flow of Pump is:

56.7m³/h (50Hz)

68.1m³/h (60Hz)

- Pump's motor is joint axle driving design
- Convenient to change and install
- Fast operation

規格SPECIFICATIONS:

| 型式 MODEL | 轉速 ROTATION | 排出流量 DESIGNED EXHAUST VELOCITY | 到達真空度 OBTAINABLE VACUUM | 使用真空度 FREQUENTLY USE VACUUM | 壓力 USUAL EXHAUST PRESSURE | 直徑 DIAMETER OF EXHAUST PIPE | 馬力 POWER | 尺寸 SIZE(LxWxH) (mm) | 重量 WEIGHT(kg) |
|-------------|-----------------|-----------------------------------------|-------------------------------|-----------------------------------|------------------------------------|-----------------------------------|--------------------------------|---------------------------|-----------------------------|
| DS-3E | 1450r.p.m(50Hz) | 235//min | 600mmHg | | | | SINGLE PHASE 3PHASE 0.4Kw4P | 480x222x265 | BODY OF THE MACHINE 21kg |
| | 1730r.p.m(60Hz) | 280//min | | | | | | | |
| DS-5E | 1450r.p.m(50Hz) | 405//min | | Under 450mmHg | Under 0.6kg/cm ² | 3/4 PT | 3PHASE 0.75Kw4P | 560x270x265 | BODY OF THE MACHINE 27kg |
| | 1730r.p.m(60Hz) | 480//min | | | | | | | |
| DS-6E | 1450r.p.m(50Hz) | 575//min | 660mmHg | | | | 3PHASE 1.5Kw4P | 650x270x283 | BODY OF THE MACHINE 36kg |
| | 1730r.p.m(60Hz) | 685//min | | | | | | | |
| DS-8E | 945r.p.m(50Hz) | 1130//min | | Under 400mmHg | Under 0.5kg/cm ² | 1PT | 3PHASE 2.2Kw6P | 775x325x357 | BODY OF THE MACHINE 80kg |
| | 1135r.p.m(60Hz) | 1350//min | | | | | | | |