

SP221-150U/150H LED LOW BAY LUMINAIRE

APPLICATIONS

Ideal for mounting heights between 12 to 24 feet

- * Retail Environments
- * Grocery Stores
- * Warehouses

REPLACEMENT COMPARISON

TYPE	WATTS	ENERGY SAVINGS
SUNPETRA LOW BAY	150	
350W METAL HALIDE	385	61%
400W METAL HALIDE	440	66%
450W METAL HALIDE	495	70%

SPECIFICATIONS

BASE TYPE / CONNECTION	DIRECT WIRED
BEAM ANGLE	180°
CCT	30/40/50/6000K
CRI	>75
DIMENSIONS - MM	605 x 410 x 410
INCHES	23.8 x 16.1 x 16.1
DIMMABLE	NO
IP RATING	65
LIFE SPAN TO 70%	>50,000 HRS
LINE VOLTAGE	100~277VAC / 200~480VAC
LUMENS	13,200
OPERATING TEMP	-25°C ~+55°C
POWER CONSUMPTION	150W
POWER FACTOR	0.95
WARRANTY	5 YEARS
WEIGHT	7.6 Kg / 16.8 Lbs
OPTIONS	



LED CHIPS BY

SAMSUNG

POWER SUPPLY BY



CERTIFICATIONS

