

## SP201-150U/150H LED HIGH BAY LUMINAIRE

### APPLICATIONS

*Ideal for mounting heights between 20 to 40 feet*

- \* Warehouses
- \* Commercial Facilities
- \* Manufacturing Facilities

### REPLACEMENT COMPARISON

TYPE	WATTS	ENERGY SAVINGS
SUNPETRA HIGH BAY	150	
300W METAL HALIDE	330	55%
350W METAL HALIDE	385	61%
400W METAL HALIDE	440	66%

### SPECIFICATIONS

BASE TYPE / CONNECTION	DIRECT WIRED
BEAM ANGLE	120°
CCT	30/40/50/6000K
CRI	>75
DIMENSIONS - MM	495 x 488 x 488
INCHES	19.5 x 19.2 x 19.2
DIMMABLE	NO
IP RATING	65
LIFE SPAN TO 70%	>50,000 HRS
LINE VOLTAGE	100~277VAC / 200~480VAC
LUMENS	13,700
OPERATING TEMP	-25°C ~+55°C
POWER CONSUMPTION	150W
POWER FACTOR	0.95
WARRANTY	5 YEARS
WEIGHT	6.6 Kg
OPTIONS	AVBL. WITH 45° AND 90° REFLECTOR



LED CHIPS BY

**SAMSUNG**

POWER SUPPLY BY

**MW**  
MEAN WELL

### CERTIFICATIONS

