

SP702-080U/080H LED RETROFIT KIT

APPLICATIONS

For high bay / low bay HID bulb replacements

- * Warehouses
- * Commercial Facilities
- * Manufacturing Facilities
- * Retail and Show Rooms

REPLACEMENT COMPARISON

TYPE	WATTS	ENERGY SAVINGS
SUNPETRA LED RETROFIT KIT	88	
200W METAL HALIDE	220	60%
225W METAL HALIDE	247	64%
250W METAL HALIDE	275	68%



SPECIFICATIONS

BASE TYPE / CONNECTION	DIRECT WIRED
BEAM ANGLE	110°x130°
CCT	5000K
CRI	>80
DIMENSIONS - MM	268 x 173 x 124
INCHES	10.6 x 6.8 x 4.9
DIMMABLE	NO
IP RATING	65
LIFE SPAN TO 70%	>50,000 HRS
LINE VOLTAGE	90~277VAC / 347~480VAC
LUMENS	8,000
OPERATING TEMP	-25°C ~+55°C
POWER CONSUMPTION	88W
POWER FACTOR	0.90
WARRANTY	5 YEARS
WEIGHT	1.3 kg / 2.9 lbs
OPTIONS	

LED CHIPS BY



POWER SUPPLY BY



CERTIFICATIONS

