

SP261-100U/100H CANOPY LUMINAIRE

APPLICATIONS

Ideal for mounting heights up to 14 feet

- * Canopies
- * Parking Structures
- * Stairwells



REPLACEMENT COMPARISON

TYPE	WATTS	ENERGY SAVINGS
SUNPETRA CANOPY LIGHT	100	
200W METAL HALIDE	220	55%
250W METAL HALIDE	275	64%
250W SODIUM	275	64%
300W SODIUM	330	70%

SPECIFICATIONS

BASE TYPE / CONNECTION	DIRECT WIRED
BEAM ANGLE	150°
CCT	5500K
CRI	>80
DIMENSIONS - MM	232 x 315 x 315
INCHES	9.1 x 12.4 x 12.4
DIMMABLE	NO
IP RATING	65
LIFE SPAN TO 70%	>50,000 HRS
LINE VOLTAGE	90~277VAC / 347~528VAC
LUMENS	9,000
OPERATING TEMP	-30°C ~+60°C
POWER CONSUMPTION	100W
POWER FACTOR	0.90
WARRANTY	5 YEARS
WEIGHT	3.9 kg / 8.6 lbs
OPTIONS	

LED CHIPS BY



POWER SUPPLY BY



CERTIFICATIONS

