



2' X 6' RADOME



TRANSPARENT VIEW TO SHOW
BRACKET



STAMP

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
ELECTRIC TECH CONSTRUCTION, INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
ELECTRIC TECH CONSTRUCTION, INC. IS
PROHIBITED.

REVISIONS			
DESCRIPTION	DATE	BY	REV
NOT FOR CONSTRUCTION UNLESS LABELED AS CONSTRUCTION SET			



PROJECT NAME

SITE NAME

SITE CASCADE

SHEET TITLE

RADOME DETAILS




TYP. FRP-RADOME CONNECTION

NOTES:

- QUANTITY:TWO EACH RADOMES
- CUSTOM MOLDED FRP RADOME IS TO BE FABRICATED FROM CHOPPED FIBERGLASS REINFORCED FIRE RETARDANT POLYESTER HETRON RESIN WITH SMOOTH PAINT-READY EXTERIOR.
- ALL CUSTOM MOLDED FRP SURFACES EXPOSED TO SUNLIGHT MUST BE PAINTED TO PROTECT FROM WEATHERING AND UV DEGRADATION.
- ETECH FRP IS NOT RESPONSIBLE FOR ANALIZING RADOME OR LOAD CARRYING CAPACITY OF MAST OR EXISTING STRUCTURES.
- TYPICAL FRP CONNECTION HAS 3 LAYERS OF FIBERGLASS OVERLAY TO ALL ADJACENT EDGES.
- SEE ARCHITECTURAL DRAWINGS FOR ADDITIONAL INFORMATION.

OFFSET MOUNT DETAILS



ITEM #	PART NAME	QTY.
1	2' X 6' FIBERGLASS RADOME (2 PIECE)	1
2	OPTIONAL BONNET TOP	1
3	3" X 3" ELA OFFSET MOUNT	2
4	STEEL U-BOLT 1/2"	2
5	3" X 3" ELA CLIP	4
6	3/8" FRP FLAT HEAD BOLT	22
7	3/8" FRP HEX NUT	30
8	3/8" FRP ALL THREAD	4
9	1/2" STEEL HEX NUT	4
10	1/2" STEEL FLAT WASHER	4
11	1/2" STEEL LOCK WASHER	4



STAMP

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ELECTRIC TECH CONSTRUCTION, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ELECTRIC TECH CONSTRUCTION, INC. IS PROHIBITED.

REVISIONS

DESCRIPTION	DATE	BY	REV

NOT FOR CONSTRUCTION UNLESS LABELED AS CONSTRUCTION SET

PROJECT NAME

SITE NAME

SITE CASCADE

SHEET TITLE