

# AS-7.5 & AS-10 SPECS

## 20" HYDRAULIC INSERTION PRESS

The Auto-Sert 20" Hydraulic Insertion Press is a high-powered, versatile machine which provides the flexibility to work with both flat and formed parts of varying sizes. The control panel is located on the front face at eye-level for quick and easy adjustment during operation, and tooling part storage is conveniently placed within the machine itself, eliminating the need for extra shelf and storage space within the shop. Available in 7.5 and 10 ton capacity.

DESCRIPTION	AS-7.5/20" THROAT	AS-10/20" THROAT
TONNAGE CAPACITY	Minimum 350 lbs. Maximum 15,000 lbs.	Minimum 350 lbs. Maximum 20,500 lbs.
THROAT DEPTH TO BACK	20" (508mm)	20" (508mm)
THROAT DEPTH TO TOP	20" (508mm)	20" (508mm)
RAM STROKE	6" (152mm)	6" (152mm)
HYDRAULIC PRESSURE	Minimum 40 P.S.I. Maximum 3,000 P.S.I.	Minimum 40 P.S.I. Maximum 3,000 P.S.I.
OIL RESERVOIR CAPACITY	12 gallons (45.42 lit.)	12 gallons (45.42 lit.)
ELECTRICAL SPECS	208/230/415/460/575 V 3 Phase 50/60 Hz	208/230/415/460/575 V 3 Phase 50/60 Hz
HEIGHT	79" (2007mm)	79" (2007mm)
WIDTH	36" (914mm)	36" (914mm)
DEPTH	45" (1143mm)	45" (1143mm)
WEIGHT	1900 lbs. (862kgs.)	1900 lbs. (862kgs.)

  
AUTO-SERT



Auto-Sert AS-7.5 - 20 in. Hardware Insertion Press