



**Specifications**  
**SIERRA Incline Platform Lift**

- Model:** IPL500
- Rated Load:** 500 lbs
- Drive:** Rack and Worm Gear / 24 VDC 1/8 HP Motor w/Brake
- Power Supply:** 115VAC, 15Amp Grounded
- Control Circuit:** 24 VDC
- Platform:** 25" X 36"  
 Manual Fold  
 Power Folding Ramps for Entry/Exit
- Travel:** 40' Maximum
- Speed:** 14 FMP
- Controls:** Constant Pressure Rocker Switch on Platform  
 Infrared Wireless Call-Send Controls  
 Device Provided
- Manual Lowering:** Incline Platform Lifts Meets: ASME A18.1-2008, Section 6  
 CAN/CSA B44.1-2011/ASME A17.5-2011  
 ETL Listed - Control No. 3148125
- Safety Design Standards:**
- Safety Features:** Overspeed Governor  
 Upper & Lower Landing Limits  
 Upper & Lower Final Limits  
 Ramp obstruction Sensors  
 Under Platform Safety pan Obstruction Sensors  
 Drive Chassis Obstruction Sensors  
 Non-Skid Platform Surface

**LH Shown**  
**RH Opposite**

DRAWN TB	1/3/2012		16805 E. 168th St. Lester, WI 53009-1611	
CHECKED			816-837-0811	
<small>This document is the property of Harmar and is delivered upon the express condition that the contents will not be disclosed or used without the written consent of Harmar.</small>		<b>TITLE</b> <b>IL500 Sierra Incline Platform Lift</b>		
<b>THIRD ANGLE PROJECTION</b> 		Telecon 1100 31" A.1 304 A.205 11/16 A.205 Ang A.2P	<b>SIZE</b> FINISH <b>D</b>	<b>DWG NO</b> <b>IL500 25x36 TYP</b>
		SCALE		<b>REV</b> SHEET 1 OF 1