

# LAMBERTS LINIT

## LINIT product range

The tolerance of the above given dimensions are in compliance with the specifications of the EN 572, if not otherwise specified in the respective Lamberts' product specification.

Explanation of abbreviations:

NP (Normal Production):

The LAMBERTS LINIT types marked with "NP" are manufactured regularly, as standard, in short intervals between the production runs and are mostly kept in stock, as demand permits.

SP 1 (Special Production):

The LAMBERTS LINIT types marked with "SP 1" are usually manufactured in regular special productions. These are, however, only possible when the order is for a certain minimum quantity, or, if the minimum quantity is fallen short of, the order can be directly combined with the basic normal production "NP" and other special orders "SP 1". These products are usually kept in stock in smaller quantities.

SP 2 (Special Production):

The LAMBERTS LINIT Types marked with "SP 2" are manufactured in infrequent special production runs (approx. two to three times a year). These can only be performed when the order is for a certain minimum quantity or, if the minimum quantity is fallen short of, the order can be directly combined with the first Special production "SP 1" and other special orders "SP 2".

SP 3 (Special Production):

The LAMBERTS LINIT Types marked with "SP 3" are manufactured in extremely seldom special production runs (usually maximally once a year). These are only possible when the order is for a certain minimum quantity or, if the minimum quantity is fallen short of, the order can be directly combined with other special orders "SP 3".

If you are interested in LAMBERTS LINIT glass types of the "SP" category, we request that the planner should consult us in due time prior to the tender and that the general contractor should consult us in due time prior to submission of a bid or before accepting an order, in order to determine whether sufficient quantities are in stock from previous productions, and can be used for the respective order, or whether the defined minimum order quantities for the respective special production are met.

Spare quantities for any breakage or repairs must be accounted for by the customer in the order quantity.

A subsequent production is only possible when the required minimum production quantities are reached again (for information concerning a concrete project case please contact our sales personnel).

Under certain conditions it is possible to make reservations, especially for rarer special productions "SP 2" and "SP 3"!

For all other LINIT types that are not explicitly listed in the table or not marked with an abbreviation "NP" or "SP" it must be clarified in advance as to whether these are technically and/or commercially feasible. This must be clarified by the planner in due time prior to the tender and by the general contractor prior to the submission of a bid or acceptance of an order.

The above specifications on Normal and Special Productions relate to average demand situations and are only for basic orientation regarding possible constellation and availability. In the case of concrete projects, however the respective product availability as well as delivery times must be clarified by the planner in due time prior to the tender and by the general contractor prior to the submission of a bid or acceptance of an order.

The company Glasfabrik LAMBERTS GmbH & Co. KG reserves the right to change the range of products without prior announcement!


All details are subject to correction and on basis of our General Business Terms and Conditions and Technical Delivery Terms!

# LAMBERTS

## LAMBERTS LINIT U-glass Product Range

LINIT Glass type:	width w / mm	flange height h / mm	thickness t / mm	weight		uncoated	coated glass		
				kg / m <sup>2</sup>	kg / m		1.7 W	solex	azur
P 23 504	232	41	6	ca. 19,5	ca. 4,50	SP 3	-	-	-
P 23 504, 8 lw	232	41	6	ca. 19,5	ca. 4,50	SP 3	-	-	-
P 26 504	262	41	6	ca. 19,0	ca. 5,00	NP	NP	SP 1	NP
P 26 504, 8 lw	262	41	6	ca. 19,0	ca. 5,00	NP	SP 1	-	SP 1
P 26 clarissimo	262	41	6	ca. 19,0	ca. 5,00	SP 1	SP 2	-	-
P 26 clarissimo, 8 lw	262	41	6	ca. 19,0	ca. 5,00	SP 1	-	-	-
P 33 504	331	41	6	ca. 18,2	ca. 6,00	NP	SP 1	-	-
P 33 504, 10 lw	331	41	6	ca. 18,2	ca. 6,00	SP 2	SP 2	-	-
P 50 504	498	41	6	ca. 17,0	ca. 8,50	NP	SP 1	SP 2	SP 1
P 50 clarissimo	498	41	6	ca. 17,0	ca. 8,50	NP	SP 1	-	SP 1
P 23/60/7 504	232	60	7	ca. 25,5	ca. 6,00	NP	SP 1	-	SP 1
P 23/60/7 504, 8 lw	232	60	7	ca. 25,5	ca. 6,00	SP 1	SP 2	-	SP 2
P 26/60/7 504	262	60	7	ca. 24,6	ca. 6,50	NP	NP	SP 1	NP
P 26/60/7 504, 8 lw	262	60	7	ca. 24,6	ca. 6,50	NP	SP 2	-	SP 2
P 26/60/7 504, 8+2 lw	262	60	7	ca. 24,6	ca. 6,50	SP 3	-	-	-
P 26/60/7 504, 16 lw	262	60	7	ca. 24,6	ca. 6,50	SP 2	-	-	-
P 26/60/7 clarissimo	262	60	7	ca. 24,6	ca. 6,50	NP	SP 1	-	SP 1
P 26/60/7 clarissimo, 8 lw	262	60	7	ca. 24,6	ca. 6,50	SP 1	-	-	-
P 26/60/7 solar	262	60	7	ca. 24,6	ca. 6,50	NP	SP 1	-	SP 1
P 26/60/7 solar, low iron	262	60	7	ca. 24,6	ca. 6,50	SP 3	-	-	-
P 26/60/7 cord	262	60	7	ca. 24,6	ca. 6,50	SP 1	SP 1	-	SP 1
P 26/60/7 prismsolar	262	60	7	ca. 24,6	ca. 6,50	SP 2	-	-	-
P 33/60/7 504	331	60	7	ca. 23,5	ca. 7,70	SP 1	SP 2	-	SP 2
P 33/60/7 504, 10 lw	331	60	7	ca. 23,5	ca. 7,70	SP 3	-	-	-

lw = longitudinal wires



Obviously, from a certain minimum requirement quantity, it is also possible to add your desired decor into LINIT channel shaped glass. When planning this, appropriate development times and costs must be observed.



The extent to which the various LINIT types fulfil country-specific building regulations (e.g. authorisations etc.) can be found at [www.lamberts.info](http://www.lamberts.info) or from our sales personnel.