

2-Port USB 3.0 PCI-E [x1] Frame Grabber Card



Features

- PCI-Express® [x1] Gen. 2 Compliant
- 1 Independent USB 3.0 Host Controller
- Support Lockable USB Connector



Specifications

| System | |
|-----------------------|---|
| Bus Interface | PCI-Express® [x1], Gen 2 |
| USB | 1 independent USB3.0 host controller 900mA @ 5V for each port Compliant with USB 3.0 Specification Revision 1.0 |
| USB Connector | 2 USB 3.0 Type-A connectors with lockable screw threads |
| OS Support | Windows® 10, Windows® 8.1 (32/64-bit), Windows® 7(32/64-bit) Linux |
| Power Supply | |
| Power Requirement | From PCIe bus |
| Mechanical | |
| Dimensions (W x D) | 78mm(W) x 71.1mm(D) |
| Environmental | |
| Operating Temperature | 0°F ~ 122°F(0°C ~ 50°C)(according to IEC68-2-14 with 0.5 m/s with air-flow ; with industrial devices) |
| Storage Temperature | -49°F ~ 185°F(-45°C ~ 80°C) |
| Storage Humidity | 5 ~ 95% @ 40°C, non-condensing |

Ordering Information

- PER-T500-A10-00
2-Port USB 3.0 PCI-E [x1] Frame Grabber Card