



# NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

## Dura-Flow 800™

Polyurethane (TPU) Lining/Nylon 6-6 Double Jacket

### Dura-Flow 800™ FEATURES

- Exclusive **DURA-CORD®** advanced air-textured Nylon 6-6 continuous filament warp yarns, resulting in superior toughness, abrasion resistance, cut resistance, tear strength and heat resistance when compared to competitive nylon, spun polyester or filament polyester warp constructions. **DURA-CORD®** is the registered trademark for NAFH. Fire hose sold under this brand is specifically manufactured by NAFH.
- Unique **Ultra-Shield™** high performance polymeric coating seals each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The **Dura-Thane™** polyurethane (TPU) inner lining is extremely light weight and compact, and is a National Sanitation Foundation (NSF 60) approved material for safely conveying drinking water.

- The **Friction Fighter System™** results in an extremely smooth waterway surface, significantly reducing friction loss and improving nozzle performance.
- With less weight and reduced coil diameters, **Dura-Flow 800™** folds more tightly into high rise hose packs and requires less hose bed space, while at the same time providing more maneuverability and flexibility than traditional hose types.
- The result is an extremely strong and flexible hose with exceptional heat, abrasion, chemical and kink resistance.
- As the name implies, this product was created to provide superior durability as well as delivering exceptional flow characteristics.
- Both the hose and couplings are made in the USA, performance shall meet and exceed NFPA 1961 standards.

**Applications include Attack, High Rise, CAFS and Potable Water**

**Available in 50 and 100 foot lengths**



 **FAMILY OWNED  
AMERICAN MADE**

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCLPD
1½"	DF-800	800 PSI	400 PSI	1 <sup>15</sup> / <sub>16</sub> "	12 lbs.
1¾"	DF-800	800 PSI	400 PSI	2 <sup>3</sup> / <sub>16</sub> "	14 lbs.
2"	DF-800	800 PSI	400 PSI	2 <sup>7</sup> / <sub>16</sub> "	17 lbs.
2½"	DF-800	800 PSI	400 PSI	3"	21 lbs.
3"	DF-800	800 PSI	400 PSI	3 <sup>17</sup> / <sub>32</sub> "	27 lbs.

**DURA-CORD®** is a registered trademark of North American Fire Hose Corporation. All rights reserved.

DF-800,™ Dura-Flow 800,™ Ultra-Shield,™ Friction Fighter System™ and Dura-Thane™ are all trademarks of North American Fire Hose Corporation.

All rights reserved.

Revision 2019A

## NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

[NAFHC.com](http://NAFHC.com)

